

Product Specification

Test	Specification
UV Absorbance – 260 – 400 nm	<= 0.01
UV Absorbance – 230 nm	<= 0.15
UV Absorbance – 220 nm	<= 0.30
Assay (CH ₃ CHOH CH ₃)	>= 99.8 %
Residue after Evaporation	<= 1.0000 ppm
Water (H ₂ O)	<= 0.06 %
LC/MS Suitability – Largest Response on ESI – Positive Mode (as Reserpine)	<= 50 ppb
Trace Impurities – Aluminum (Al)	<= 50.0 ppb
Trace Impurities – * Calcium (Ca)	<= 50.0 ppb
Trace Impurities – Iron (Fe)	<= 50.0 ppb
Trace Impurities – Magnesium (Mg)	<= 50.0 ppb
Trace Impurities – Potassium (K)	<= 50.0 ppb
Trace Impurities – * Sodium (Na)	<= 50.0 ppb

For Laboratory, Research or Manufacturing Use

* May change over time due to extraction from glass container

Barbara Rykowska
Quality Assurance CoordinatorFor questions on this Product Specification please contact Technical Service at technical.service@avantorsciences.com
Avantor Performance Materials Poland S.A. Sowinskiego 11 Gliwice 44-101 Poland Tel: +48 322392000