SHOWA 545

The nitrile technology of the SHOWA 545 durable gloves ensure superb grip as well as oil and cut resistance. When working outdoors or in dirty environments, the elasticated wrist cuff prevents debris from entering the glove to ensure comfort over long periods of wear. Ensure precision and dexterity, even when assembling greasy components, with the 545 gloves.



BENEFITS

- Cut-resistant
- Oil-resistant
- Seamless knit
- Extra Grip
- Flexible
- Breathable

FEATURES

- HPPE reinforced
- Seamless knit
- Nitrile palm coating
- Rough grip
- Ergonomic

INDUSTRIES

Manufacturing

Mechanical

Mining

HAZARDS

Cut

NORMS & CERTIFICATES

Cat II

CE

EN 388:2016+A1:2018

4242B

TRADES & APPLICATIONS

- Automotive repairs and maintenance
- Maintenance
- Component Assembly
- Dry & oily parts assembly
- Carpentry

GET IN TOUCH
SHOWA Interntional B.V. | WTC - Tower 2 - Strawinskylaan 1077 XX Amsterdam - The Netherlands
showagroup.com | info@showagroup.eu
© SHOWA GROUP 2024 | All rights reserved

SHOWA 545

PACKAGING

- Pair per polybag: 10
- Polybags per case: 12
- Pair per case: 120

LENGTH

210 - 240mm

COATING

- Nitrile

LINERS

- Cut resistant - HPPE
- Knit weight - Light-weight

SIZES

6/S | 7/M | 8/L | 9/XL

MATERIAL

- HPPE
- Seamless knit

USER INSTRUCTIONS

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

GET IN TOUCH
SHOWA Interntional B.V. | WTC - Tower 2 - Strawinskylaan 1077 XX Amsterdam - The Netherlands
showagroup.com | info@showagroup.eu
© SHOWA GROUP 2024 | All rights reserved