

JALAS® 3500 WHITE

EN ISO 20345:2011, S1 SRC

PROPERTIES
Highest level of protection, excellent grip, perfect fit, extra comfortable, breathable, excellent shock absorption

SPECIFICATION

TYPE OF SHOE **Safety footwear, sandals**

FITTING **Regular**

SIZE RANGE (EU) **36-47**

COLLECTION **White**

PLATFORM **M-Sport**

UPPER MATERIAL **PU-coated leather, textile**

TOECAP MATERIAL **Aluminium**

LINING MATERIAL **Polyester, polyamide**

SOLE MATERIAL **Plastic shank, PU outsole**

INSOLE **FX2 Pro**

INSOLE MATERIAL **Textile, soft EVA, polyester-based conductive thread, double shock absorption zones in Poron® XRD®**

FASTENING **Velcro®**

COLOUR **White, black**

SIZE	ART. NO.	EAN NO.
36	3500-36	6408487430985
37	3500-37	6408487430992
38	3500-38	6408487431005
39	3500-39	6408487431012
40	3500-40	6408487431029
41	3500-41	6408487431036
42	3500-42	6408487431043
43	3500-43	6408487431050
44	3500-44	6408487431067
45	3500-45	6408487431074
46	3500-46	6408487431081
47	3500-47	6408487431098

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-01-12

A MEMBER OF SATRA TECHNOLOGY CENTRE
Finnish Institute of Occupational Health
SP Technical research institute of Sweden



JALAS® 3500 WHITE

FEATURES
Low weight, oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

PRIMARY PROTECTION
Prevents risk of:, toe injuries, antistatic

PRIMARY ENVIRONMENTS OF USE
Indoors

PRIMARY AREAS OF USE
Laboratory work, paint spraying work

CE

- Aluminium toecap
- Oil-resistant outsole
- Ergothan Shock Absorption System
- Anti-static properties
- ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-01-12

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB
Box 7, SE-793 21 Leksand, Sweden
Phone +46 (0) 247 360 00
Fax +46 (0) 247 360 10
info@ejendals.com
order@ejendals.com
www.ejendals.com

JALAS® 3500 WHITE



COMPLIANCE
EN ISO 20345:2011

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

A: Electrical resistance (between 0.1-1000 Mega Ohms

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

BGR 191: Orthopedic footwear adjustment according to German BGR 191. Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

CE

Aluminium toecap

Oil-resistant outsole

Ergothan Shock Absorption System

Anti-static properties

ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-01-12

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB
Box 7, SE-793 21 Leksand, Sweden
Phone +46 (0) 247 360 00
Fax +46 (0) 247 360 10
info@ejendals.com
order@ejendals.com
www.ejendals.com