JALAS® 3030 ZENIT

EN ISO 20345:2011, S2 SRC



ZENIT COLLECTION

reddot design award
winner 2012

PROPERTIES

Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

SPECIFICATION

TYPE OF SHOE **Safety footwear, low shoes**

FITTING **Regular**

SIZE RANGE (EU) **36-47**

COLLECTION **Zenit**

PLATFORM **Zenit**

UPPER MATERIAL **PU-coated leather, split leather**

TOECAP MATERIAL **Aluminium**

LINING MATERIAL **Polyamide, polyester**

SOLE MATERIAL **PU midsole, plastic shank, RPU outsole**

BIND SOLE MATERIAL **SBS**

INSOLE **FX2 Supreme**

INSOLE MATERIAL **Textile, soft EVA, polyester-based conductive thread, merino wool, double shock absorption zones in Poron® XRD®**

FASTENING **Laces**

COLOUR **Black, grey, red**

SIZE	ART. NO.	EAN NO.
36	3030-36	6408487441332
37	3030-37	6408487441349
38	3030-38	6408487441356
39	3030-39	6408487441363
40	3030-40	6408487441370
41	3030-41	6408487441387
42	3030-42	6408487441394
43	3030-43	6408487441400
44	3030-44	6408487441417
45	3030-45	6408487441424
46	3030-46	6408487441431
47	3030-47	6408487441448

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-03-01

A MEMBER OF SATRA TECHNOLOGY CENTRE

Finnish Institute of Occupational Health

SP Technical research institute of Sweden



JALAS® 3030 ZENIT

FEATURES
Oil-resistant outsole, anti-static properties, padded shaft edge in memory foam, ventilating insole, stabilizator, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

PRIMARY PROTECTION
Prevents risk of:, toe injuries, antistatic

PRIMARY ENVIRONMENTS OF USE
Outdoors

CE

- Aluminium toecap
- Water repellent
- Oil-resistant outsole
- Ergothan Shock Absorption System
- Stabilizator
- Anti-static properties
- ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-03-01

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB
Box 7, SE-793 21 Leksand, Sweden
Phone +46 (0) 247 360 00
Fax +46 (0) 247 360 10
info@ejendals.com
order@ejendals.com
www.ejendals.com

JALAS® 3030 ZENIT



COMPLIANCE
EN ISO 20345:2011

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

WRU: Water-resistant upper

A: Electrical resistance (between 0.1-1000 Mega Ohms

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

BGR 191: Orthopedic footwear adjustment according to German BGR 191. Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

CE

- Aluminium toecap
- Water repellent
- Oil-resistant outsole
- Ergothan Shock Absorption System
- Stabilizator
- Anti-static properties
- ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-03-01

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB
Box 7, SE-793 21 Leksand, Sweden
Phone +46 (0) 247 360 00
Fax +46 (0) 247 360 10
info@ejendals.com
order@ejendals.com
www.ejendals.com