1-800-518-0364 / 1-450-973-9420
1-450-973-6373
www.ga-international.com
www.labtag.com | www.industritag.com

Product Data Sheet

Clear CryoSTUCK® Tape – TAQ Tape Material

Transparent Cryogenic Tape for Frozen Surfaces

Facestock Material:	Thermoplastic Film
Adhesive Type:	Permanent
Media Thickness:	4.5 mil ± 10%
Support Liner Thickness:	2.3 mil ± 10%
Finish:	Glossy
Lower Temperature Resistance:	-196°C (-321°F)
Upper Temperature Resistance:	+150°C (+302°F)
Minimum Application Temperature:	-80°C (-112°F)
Storage Instructions:	Between +15°C and +25°C (+59°F to +77°F) at 50% RH, in original packaging
Compliance:	Please contact quality_assurance@ga-international.com for compliance and regulatory information.
Product Warranty:	Refer to our *Terms and Conditions* found on https://www.labtag.com/resources/terms-and-conditions/.

The specifications provided herein are based on the information supplied by the primary material manufacturer (s) and tests conducted by GA International Inc. The end-user shall independently determine the suitability of the labels for the purpose for which they were purchased.

Last Update: October 25, 2024

USA
P.O. Box 2633
Champlain, NY
12919, United States

CANADA
4455 Rue Louis-B.-Mayer
Laval, QC
H7P 6B5, Canada

NETHERLANDS
Runweg 28A
5258 BN Berlicum
Netherlands

UK
Preston Park House, South Road
Brighton, East Sussex BN1 6SB
United Kingdom