TECHNICAL SPECIFICATION

EYE AND FACE PROTECTION

Stealth™ Coverlite™ Overspec

Clear K Rated / ASA940-061-300



DESCRIPTION

The stylish and spacious design of the Stealth™ Coverlite™ means that they comfortably fit over prescription spectacles, whilst maintaining a modern look, unlike traditional, bulkier overspectacles. Stealth™ Coverlite™ feature pantoscopic arms, allowing the lens to be tilted for easy fitting over prescription eyewear. Materials and technology first used in Stealth™ 16g combined with the robust, low base, minimum curve lens offer optimal vision, comfort, and compatibility.

OPTIONS

Clear K & N Rated (ASA940-0A3-000)

Clear K Rated (ASA940-061-300)

Smoke K Rated (ASA940-063-000)

SAFETY STANDARDS

EN 170 • EN 166

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

RADIATION PROTECTION BREAKDOWN filtering effect Scale Number
2C

Manufacturer's Trademark
JSP Dagger

Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s ˚ Maximum protection for glasses
F

Resistance to Surface Damage by Fine Particles (optional)
K

LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1.2

Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1

The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5˚C and +55˚C) Optional
T

Product Weight
34g

FEATURES



Flexible Frame

The Stealth™ CoverLite™ spectacle frame is both flexible and springy so that the product can fit any head size whilst still providing a comfortable and secure fit.



Pantoscopic Grip Arms

The arms of the Stealth™ CoverLite™ are pantoscopic so that they can be angled above the arms of prescription eyewear. The arms have soft grip pads on them to create a secure and comfortable fit.



Optically Perfect

The robust, low base, minimum curve, optical Class 1 lens provides optimal vision to the wearer.



Ultra Lightweight

Made with materials and technology used on the Stealth™16g, the Stealth™ Coverlite™ is the lightest overspectacle on the market, weighing just 34g. This improves wearer comfort and prevents unnecessary fatigue.



Overspectacle

The stylish and spacious design of the Stealth™ Coverlite™ means that they can comfortably fit over prescription eyewear whilst having a modern look, unlike traditional, bulkier overspectacles.



K&N Lens Coating

The Stealth™ CoverLite™ lens is coated both sides with our PremierShield™ K rated anti-scratch and N rated anti-mist coating.

RANGE

STEALTH COVERLITE

VIDEOS

youtu.be/gM7Lx0x8o4c

DOWNLOADS

Image Pack (ZIP)
Declaration of Conformity (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.