7250

50 liter Nestable drum with handles



Product part	Product code	Materials
Drum	7250	HDPE
Handle	6800	HDPE
Lid	7140	HDPE
Gasket	H14	EPDM

Capacity	Liters	US Gallons
Brimful	53.5	14.13
When closed	50.5	13.34

Hazardous material information	
Hazardous material type	Solids
Packaging group	I – II – III
UN marking	1H2/X65/Y65/Z65/S/--/NL/CurTec 3198
Maximum gross mass (kg)	X=65 Y=65 Z=65

Weight	Grams	Ounces
Drum	2125	74.96
Handles	90	3.18
Lid	417	14.71
Gasket	28	0.99
Total	2660	93.84

Weight tolerance
All products have a tolerance of ±4% of the initial weight mentioned on this data sheet

Dimensional tolerances	%
Height	±2.5
Diameter	±1.5

Wall thickness	mm
Minimal wall thickness	≥1.8
Nominal wall thickness	≥2.5

Colors	Color code	PMS references
Drum*	White 004	/
Lid*	Blue 605	301 C
Handle	Black 101	/

** Other colors available on request*


Product identification	Drum	Lid
Manufacturer ID	Bottom	--
Product code	Bottom	--
Recycle logo / Material type	Bottom	Inside
Date clock	Bottom	Inside
UN-mark	Side wall	--
Food logo	Bottom	--
Material track clock	Bottom	--
CFR49-mark	Bottom	--

Other information
Maximum filling temperature is 70°C/ 158°F Contents must have cooled to 30°C/ 86°F before containers can be closed and stacked DoC available on request UN certificate available on request MVTR declaration available on request Watertightness declaration available on request User manual available on request All drums can be made tamper evident with application of compact seal # 7800

DISCLAIMER

CurTec manufactures packaging material for a wide range of purposes. This declaration is restricted to the packaging material as it leaves the production facility. CurTec has neither control over final end use of the product nor over processing conditions. It is therefore the responsibility of the end user to check compliance with the relevant regulations and to validate material performance in the end application through proper end use testing.

© 2020 Property of CurTec International B.V. All rights explicitly reserved, it is not allowed to copy or communicate to other parties without written consent of CurTec.



Title	Revision	Rev. Date	Units
7250 Nestable drum 50 liter	0	12-12-2019	mm

This document is property of CurTec Nederland B.V.
and may not be copied or communicated without written consent.
All Rights Reserved