




**Robust, reliable single channel pump head
for versatile applications
in the lab and industry**


Usable* for:

rotarus® smart	Serie 30 and 40
rotarus® standard	Serie 50 and 100
rotarus® flow	Serie 50 and 100
rotarus® volume	Serie 50 and 100


PK 10-24

rotarus® PK 10-24	Order No. 951 10 20 21
Characteristics	Hinged tubing bed Simple tube insertion Automatic tube fixing Concave tubing bed and convex rollers extend the tube service life Cell protecting For high viscosity media
Functions	Single channel Cascadable 3 stainless steel rollers For tubes with 2.4 mm wall thickness Inner diameter 4.8 mm – 9.5 mm
Housing	Aluminum anodized
Dimensions (L / W / H in mm)	75 / 130 / 110
Weight	1.58 kg
Range of speeds	0.2 – 500 1/min
Head and tube detection through RFID	yes
Safety	Tubing bed open/closed monitoring
Flow rate range**	
Series 30	33 - 3800 ml/min
Series 40	10 - 2300 ml/min
Series 50	0.66 - 1100 ml/min
Series 100	17 - 5200 ml/min


Flow rates in combination with series 30




Flow rates in combination with series 40



Flow rates in combination with series 50



Flow rates in combination with series 100



*Great suction height, great discharge head / delivery pressure, great viscosity, great particle load necessitate qualified advice.

**Indicated flow rates are approximate values measured with water, at 0 meters suction lift and free outlet.