ERGOMAT.COM

Ergomat Classic Mat

The Classic Mat is the original ergonomic bubble profile mat. The Classic Mat boasts the longest warranty in the industry. Customers still have many of these original mats in service over 20 years later. Available in 2 profiles: Classic and Classic Deluxe.



ERGONOMIC

BEVELED EDGE

ANTI-STATIC

ISO CLEANROOM CERTIFIED

2 Profiles

Classic Deluxe



Thickness .6" (1.5 cm)

Classic



Thickness .6" (1.5 cm)

BENEFITS

ERGONOMIC : Designed to stimulate circulation in feet, legs and lower back. Circulation is stimulated by the unique, patented surface profile of Ergomat mats, which forces muscular response.

BEVELED EDGES : Molded w/ bevels. Yellow bevels can be added. Bevels will never curl up, eliminating trip hazards.

ANTI-STATIC : Ideal for environments requiring static control.

ISO CLEANROOM CERTIFIED : Classic Mats are ISO Cleanroom Class 5 (Class 100) rated .

ANY SIZE ANY SHAPE: Can be custom made in any size and shape, creating one continuous surface to eliminate seams and trip hazards.

SILICON FREE: All Ergomat mats are silicon free.

TRUE WARRANTY: Ergomat stands 100% behind our products with full replacement coverage if our product fails to perform as promoted within that period. At Ergomat we call this a ***True Warranty***.

www.ergomat.com - info@ergomat.com

North & South America: +1-440-282-4651 | **English (EU):** + 44 3308 280 084 | **Danish:** + 45 702 21 840 | **Dutch**: + 31 73 61 30 530 | **Swedish:** + 46 42 16 36 00
German: + 49 9524 30 367-50 | **French:** + 33 1 446 410 28

Rev. 01/13/2021

Ergomat Classic Mat

	CLASSIC	CLASSIC DELUXE
Material	Foamed Polyurethane	
Color	Grey	
Weight	2500 g +/- 50 g // 5.5 lbs +/- 0.1 lbs	2790 g +/- 50 g // 6.15 lbs +/- 0.1 lbs
Length without beveled edges	91 cm +/- 1% // 35.8" +/- 0.38"	
Width without beveled edges	60 cm +/- 1% // 23.6" +/- 0.38"	
Thickness	15 mm // 0.6"	15 mm // 0.6"
Density	380 kg/m^3 +/- 10 % ISO 2781	
Hardness	22-30 Sh A DIN 53505	
Compression Pressure face = ø 100mm % by pressure of 240kg	50% Tinby A/S Standard	
Abrasion Load = 5 N	180 mm^3 // 7 in^3 ISO 46 49 (5 N)	
Electrical Resistance Surface point to point % 50 RH	1x10^9 Ω-5x10^9 Ω ESDSTM7	
Breaking Point/Tensile Strength	2 Mpa EN ISO 527-1	
Elongation at Break	500% EN ISO 527-1	
Tearing Strength	4 N/mm ASTM D 624	
Thermal properties		
Minimum use	0°C // 32°F	
Maximum use	32°C // 90°F	
Maximum short duration	40°C // 115°F	
UV-Resistance	Inferior	
Hydrolic Resistance	Inferior	
Cleanroom Application	ISO Class 5 (100) EN ISO 14644-1	
Warranty	8 years	

www.ergomat.com - info@ergomat.com

North & South America: +1-440-282-4651 | **English (EU):** + 44 3308 280 084 | **Danish:** + 45 702 21 840 | **Dutch**: + 31 73 61 30 530 | **Swedish:** + 46 42 16 36 00
German: + 49 9524 30 367-50 | **French:** + 33 1 446 410 28