



Laboratory



AcroPrep™ 24-well Filter Plates With Omega™ Membrane

Description

The Pall AcroPrep 24-well filter plates use high performing Omega membranes to offer superior performance for ultrafiltration needs. The 24-well format allows filtration of up to 7 mL of sample, eliminating the need to process samples with more labor intense methods and resulting in a time saving because continuity of membrane media is important to researchers, these plates contain the same superior ultrafiltration membrane found in various other device formats. Researchers can confidently incorporate these plates into their workflow without costly and time-consuming membrane evaluation.

The Omega Advantage

The Omega ultrafiltration membrane is a polyethersulfone membrane specifically modified to minimize protein and nucleic acid binding. The Omega membrane works on the premise of size exclusion, where samples are fractionated by molecular weight. Larger molecules can be separated from smaller molecules by selecting the appropriate molecular weight cut-off (MWCO) and filtering the sample through these plates by either centrifugation, vacuum, or positive pressure. The membrane modifications prevent binding of the biomolecules to the membrane and facilitates the concentration of the larger molecules on top of the membrane.

Characteristics of the Omega membrane include:

- Typically results in $\geq 90\%$ recovery of target biomolecules
- Low binding results in less membrane fouling, which can cause retention performance to decay
- Available in a variety of MWCOs for use with wide range of biomolecules
- High membrane consistency allows performance reliability



Application Versatility

- Concentration and purification of peptides, proteins, oligonucleotides, DNA, and RNA
- Clean-up of labelling and PCR reactions
- Desalting and buffer exchange
- Fractionation based on size exclusion

AcroPrep 24-Well Filter Plate Features

- Receiver plate and lid are included
- Intrinsic plate and membrane properties minimize sample loss from non-specific binding
- Automation friendly – compatible with all major automation platforms
- Designed in accordance with the ANSI/SLAS X-2004 standards
- Vacuum compatible – Compatible with all popular vacuum and positive pressure manifolds
- Centrifugation – Suitable for centrifugation with compatible rotors

Specifications

Materials of Construction

Filter Media

Omega (modified polyethersulfone membrane)

Plate Housing

Polypropylene

Lid

Polystyrene

Dimensions

Length: 12.8 cm (5.0 in.)

Width: 8.6 cm (3.4 in.)

Height (With receiver plate): 73.9 mm (2.9 in.)

Height (Without receiver plate): 37.4 mm (1.5 in.)

Well-Bottom Area: 1.6 cm² (0.24 in.²)

Recommended Working Volume

7 mL for vacuum

6 mL for centrifugation

Recommended Operating Vacuum

38 cm Hg (15 in. Hg)

Recommended Centrifugal Force

1,500 x g

Recommended Positive Pressure

50 psi

Typical Hold Up Volume

Membrane pore size (kDa)

		1	3	10	30	50	100
Hold Up	Centrifuge	19.3	9.8	26.5	24.6	12.8	7
	Vacuum	14	21.2	74.9	14.6	28.8	28.5
Volume	Positive	7.7	15.6	2.8	28.1	70.9	59.3
	Pressure						
Processing	Centrifuge	170	135	70	60	60	100
	Vacuum	165	135	85	60	60	30
Time (min)	Positive	155	70	45	50	55	25
	Pressure						

MWCO Selection Guide

MWCO Selection for Protein Applications

MWCO	Biomolecule Molecular Weight
1K, yellow	3K-10K
3K, gray	10K-20K
10K, blue	30K-90K
30K, red	90K-180K
50K, green	150K-300K
100K, clear	300K-900K

MWCO Selection for Nucleic Acid Applications

MWCO	Base Pairs (DS)	Bases (SS)
1K, yellow	5-16 Bp	9-32 Bs
3K, gray	16-32 Bp	32-65 Bs
10K, blue	50-145 Bp	95-285 Bs
30K, red	145-285 Bp	285-570 Bs
50K, green	240-475 Bp	475-950 Bs
100K, clear	475-1,450 Bp	950-2,900 Bs

Ordering Information

VWR US Cat. No.	VWR EU Cat. No.	Pall Part No.	Description	Pkg
76457-260	738-0236	97049	1K Omega	8/pkg
76457-262	738-0235	97050	1K Omega	2/pkg
76457-264	738-0234	97051	3K Omega	8/pkg
76457-266	738-0233	97052	3K Omega	2/pkg
76457-268	738-0232	97053	10K Omega	8/pkg
76457-270	738-0231	97054	10K Omega	2/pkg
76457-272	738-0230	97055	30K Omega	8/pkg
76457-274	738-0229	97056	30K Omega	2/pkg
76457-276	738-0228	97057	50K Omega	8/pkg
76457-278	738-0227	97058	50K Omega	2/pkg
76457-280	738-0226	97059	100K Omega	8/pkg
76457-282	738-0225	97060	100K Omega	2/pkg



Ordering:
vwr.com

© 2021 Pall Corporation. Pall, , AcroPrep, and Omega are trademarks of Pall Corporation. ® indicates a trademark registered in the USA.
Filtration. Separation. Solution. is a service mark of Pall Corporation.

3/21, PDF, GN20.1123

Filtration. Separation. Solution.SM


VWR.COM

Prices, product, and/or services details are current when published and subject to change without notice. | Certain products or services may be limited by country, federal, state, provincial, or local regulations. | VWR, part of Avantor, makes no claims or warranties concerning sustainable/green products. Any claims concerning sustainable/green products are the sole claims of the manufacturer and not those of VWR International, LLC and/or Avantor, Inc. or affiliates. Offers valid in countries listed above, void where prohibited by law or company policy, while supplies last. | Trademarks are owned by Avantor, Inc. or its affiliates, unless otherwise noted. | Visit vwr.com to view our privacy policy, trademark owners, and additional disclaimers. © 2021 Avantor, Inc. All rights reserved.

0320 Lit. No. 160198W