

## B0667B - Yellowstone Mid

**Collection:** Record

**Upper:** Microfibre + Hi-Tech Fabric

**Insole:** Wire Lace System

**Lining:** SmellStop Antibacterial

**Midsole:** Fresh'n Flex

**Toecap:** SlimCap

**Sole:** AirTech + Tpu-Skin

**Outer Carton:** 10

### Record

Record antifatigue footwear collection offers an answer to the demand for lightweight design.

### Base

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.



## Standards

EN ISO 20345: 2011 S3 (FO ESD SR)

EN 61340-4-3 S3

## Features

- 200 joules resistant toe-cap
- Puncture resistant sole
- Shock absorption in the heel region
- Anti-static footwear
- Hydrocarbons resistant
- Electronic devices protection from electrostatic discharges
- Metal free
- Orthopaedic made to measure footbed, complying with european norms DGUV112-191
- Women's width
- Men's width
- SRC - Slip resistant outsole to prevent slips and trips on ceramic and steel surfaces

**B0667B - Yellowstone Mid**  
**Commodity Code: 6404199000****Test House**

Cert No: N° F-113-05779-22

**Carton Dimensions/Weight**

| Item        | Colour | Len  | Wid  | Hgt  | Weight(Kg) | Cubic(m³) | EAN13         | DUN14 |
|-------------|--------|------|------|------|------------|-----------|---------------|-------|
| B0667BBKR35 |        | 68.0 | 41.0 | 38.0 | 1.0460     | 0.1059    | 8052530126806 |       |
| B0667BBKR36 |        | 68.0 | 41.0 | 38.0 | 1.0840     | 0.1059    | 8052530126639 |       |
| B0667BBKR37 |        | 68.0 | 41.0 | 38.0 | 1.1160     | 0.1059    | 8052530126646 |       |
| B0667BBKR38 |        | 68.0 | 41.0 | 38.0 | 1.1270     | 0.1059    | 8052530126653 |       |
| B0667BBKR39 |        | 68.0 | 41.0 | 38.0 | 1.2110     | 0.1059    | 8052530126660 |       |
| B0667BBKR40 |        | 68.0 | 41.0 | 38.0 | 1.2170     | 0.1059    | 8052530126677 |       |
| B0667BBKR41 |        | 68.0 | 55.0 | 38.0 | 1.2860     | 0.1421    | 8052530126684 |       |
| B0667BBKR42 |        | 68.0 | 55.0 | 38.0 | 1.3490     | 0.1421    | 8052530126691 |       |
| B0667BBKR43 |        | 68.0 | 55.0 | 38.0 | 1.4180     | 0.1421    | 8052530126707 |       |
| B0667BBKR44 |        | 68.0 | 55.0 | 38.0 | 1.3860     | 0.1421    | 8052530126714 |       |
| B0667BBKR45 |        | 68.0 | 55.0 | 38.0 | 1.4780     | 0.1421    | 8052530126721 |       |
| B0667BBKR46 |        | 68.0 | 55.0 | 38.0 | 1.5050     | 0.1421    | 8052530126738 |       |
| B0667BBKR47 |        | 68.0 | 55.0 | 38.0 | 1.5990     | 0.1421    | 8052530126745 |       |
| B0667BBKR48 |        | 68.0 | 55.0 | 38.0 | 1.6330     | 0.1421    | 8052530126752 |       |