

JALAS® 1615 E-SPORT

EN ISO 20345:2011, S3 SRC CI

PROPERTIES
Excellent grip, perfect fit, extra comfortable, good shock absorption, light

SPECIFICATION

TYPE OF SHOE **Safety footwear, low shoes**

NAIL PROTECTION MATERIAL **Plasma-treated composite (PTC) textile**

FITTING **Regular**

SIZE RANGE **36-47**

COLLECTION **E-Sport**

PLATFORM **M-Sport**

UPPER MATERIAL **PU-coated leather, split leather**

TOECAP MATERIAL **Aluminium**

LINING MATERIAL **Polyester, polyamide**

SOLE MATERIAL **Plastic shank, PU outsole**

INSOLE **FX2 Classic**

INSOLE MATERIAL **Textile, soft EVA, polyester-based conductive thread, shock absorption zone in Ergothan**

FASTENING **Laces**

COLOUR **Black, grey, red**

SIZE	ART. NO.	EAN NO.
36	1615-36	6408487438394
37	1615-37	6408487438400
38	1615-38	6408487438417
39	1615-39	6408487438424
40	1615-40	6408487438431
41	1615-41	6408487438448
42	1615-42	6408487438455
43	1615-43	6408487438462
44	1615-44	6408487438479
45	1615-45	6408487438486
46	1615-46	6408487438493
47	1615-47	6408487438509

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2015-11-25

A MEMBER OF SATRA TECHNOLOGY CENTRE
Finnish Institute of Occupational Health
SP Technical research institute of Sweden



JALAS® 1615 E-SPORT

FEATURES
Low weight, oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, water repellent, reflector, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

PRIMARY PROTECTION
Prevents risk of:, toe injuries, nail penetration, antistatic

PRIMARY ENVIRONMENTS OF USE
Outdoors, indoors, environments with risk for outsole penetration

CE

- Aluminium toecap
- Nail protection in plasma-treated composite (PTC) textile
- Water repellent
- Oil-resistant outsole
- Ergothan Shock Absorption System
- Anti-static properties
- ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2015-11-25

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB
Box 7, SE-793 21 Leksand, Sweden
Phone +46 (0) 247 360 00
Fax +46 (0) 247 360 10
info@ejendals.com
order@ejendals.com
www.ejendals.com

JALAS® 1615 E-SPORT



CE

Aluminium toecap

Nail protection in plasma-treated composite (PTC) textile

Water repellent

Oil-resistant outsole

Ergothan Shock Absorption System

Anti-static properties

ESD

COMPLIANCE
EN ISO 20345:2011

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

S3: S2 + P

WRU: Water-resistant upper

P: Penetration-resistant outsole

CI: Cold insulation

A: Electrical resistance (between 0.1-1000 Mega Ohms

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

BGR 191: Orthopedic footwear adjustment according to German BGR 191. Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2015-11-25

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB
Box 7, SE-793 21 Leksand, Sweden
Phone +46 (0) 247 360 00
Fax +46 (0) 247 360 10
info@ejendals.com
order@ejendals.com
www.ejendals.com