

TECHNICAL SPECIFICATION

EYE AND FACE PROTECTION



Swiss One SEEZ

1SEZBG23CKN / 1SEZBG23CKN



DESCRIPTION

This exceptional eyewear concept unites innovative technologies and high-tech features and benefits... !

Wraparound style, 10 lens base curve provides amazing optical clarity, integrated browguard for comfort and protection, Swiss One Flexofit technology non-slip side arms utilise shape memory material which can be formed to provide optimal fit and security, flexible nose bridge provides added comfort and grip...

OPTIONS

1SEZBG23CKN (1SEZBG23CKN)

1SEZBG23SKN (1SEZBG23SKN)

1SEZLGB23CKN (1SEZLGB23CKN)

SAFETY STANDARDS

EN 170 • EN 166



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 3 / Issued 9 Dec 2021 / Copyright 2018 - 2021. JSP Limited. All Rights Reserved.



SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN filtering effect
Scale Number
2C



Manufacture's Trademark Swiss One
Swiss One



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s °
Maximum protection for glasses
F



Resistance to Surface Damage by Fine Particles (optional)
K

Excellence Coating (KN Anti-Scratch/Anti-Mist)
Yes

Lightweight
Yes

Flex Nose Bridge
Yes

Memory Form Side Arms
Yes



Product Weight
27g



LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1.2



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional
T



Resistance to fogging (optional)
N

Lens Base Curve
10

Soft End Tips - Flex Flat Temple Pressure Free
Yes

Rotating Side Arms
Yes

FLEXoFIT Technology
Yes

FEATURES



Anti-mist

Anti-mist



Lens Curve

Lens curve



Lightweight

Lightweight



Memory Form

Memory form



Soft Nose Pad

Soft nose pad



Flexofit Technology

Flexofit technology



Anti-scratch

Anti-scratch



High Performance Coating

Anti-scratch / anti-fog high performance coating



Rotating Arms

Rotating arms



Soft End Tips

Soft end tips



Flex Nose Bridge

Flex nose bridge

RANGE

DOWNLOADS

[Image Pack \(ZIP\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 9 Dec 2021 / Copyright 2018 - 2021, JSP Limited. All Rights Reserved.





 [Declaration of Conformity \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 9 Dec 2021 / Copyright 2018 - 2021. JSP Limited. All Rights Reserved.

