TECHNICAL SPECIFICATION

EYE AND FACE PROTECTION

Thermex™ Double Lens Goggle

Default / AGM020-723-000



DESCRIPTION

With polycarbonate outer lens and acetate inner lens, the Thermex™ goggle offers unrivalled anti-fogging performance in extreme environments. The unique Thermex™ Moisture Control Patch works to balance air pressure build-up caused by heat or altitude. The goggle features NBR foam surround for enhanced comfort and improved fit.

OPTIONS

Default (AGM020-723-000)

SAFETY STANDARDS

EN 166 • EN 170

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

RADIATION PROTECTION BREAKDOWN filtering effect Scale Number
2C

Manufacturer's Trademark
JSP Dagger

Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles.
B

Protection from Liquid Droplets
3

Resistance to Molten Metals and Hot Solids (optional)
9

Resistance to fogging (optional)
N

Lens Material
Polycarbonate Outer Lens - Acetate Inner Lens

Product Weight
107g

LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1.2

Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1

The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5˚C and +55˚C) Optional
T

Protection from Large Dust Particles (up to 40 um grain size)
4

Resistance to Surface Damage by Fine Particles (optional)
K

RX Insert
Optional

Material
Face Seal Material NBR - Nitrilebutadiene Rubber

FEATURES



Double Lens Protection

Medium energy (B grade) impact at extremes of temperature, with additional testing conducted at -40°C.



Comfort

NBR foam on the goggle housing provides a comfortable fitting to a wide range of facial profiles.



Fog-free Vision

The unique Thermex™ Moisture Control Patch works to balance air pressure build-up caused by heat or altitude to ensure distortion free optical class 1 vision.

RANGE

THERMEX™

DOWNLOADS

Image Pack (ZIP)
Declaration of Conformity (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.