TECHNICAL DATA SHEET



WILL S3 CI
86771

Sz. 36-50

LABELLING ACCORDING TO STANDARD

In accordance with EN ISO 20345 S3 SRC/ CI	
Form C 	• Men's safety winter boot, high cut
SRC SLIP RESISTANCE — SLIP RESISTANCE: When it comes to slip resistance as defined by EN ISO 20345, SRC signifies the best possible rating a safety shoe can reach.	CI COLD INSULATED — COLD INSULATED

FIT

ANATOMICAL

AREAS OF APPLICATION

- Outdoor areas
- Cold areas, working in winter
- Road construction etc.
- Areas where exposure to moisture is expected (S2)
- Areas where there is a risk of penetration from pointed and sharp objects (S3)

FEATURES

Design	▪ Functional design
Zipper	▪ Allows shoe to be put on quickly ▪ Comfort-Plus
Certification in accordance with DGUV rule 112-191	▪ Certified for orthopaedic modifications / inserts

FEATURES

Sizes (unisex model)	▪ Expanded size range Available in sizes 36-50
Reflective material 	▪ Good visibility in the dark
PU toe protection (polyurethane)	▪ Directly applied toe protection ▪ Excellent wear protection in the toe area ▪ Protects the upper leather in this area against premature wear

UPPER MATERIAL

Cowhide leather	▪ Areas of application S2/S3 ▪ Natural material ▪ Wear-resistant ▪ Breathable ▪ Water penetration/absorption in accordance with EN ISO 20345 S2

LINING

Winter lining	▪ 50% wool, 30% polyester, 20% acrylic ▪ Good ventilation ▪ Skin-friendly ▪ High absorption of moisture ▪ Comfortable

TOE PROTECTION CAP

Steel toe cap 	▪ Protection against impacts of min. 200 joules and pressure loading of min. 15 kN ▪ Permanent edge coverage for cushioning ▪ Ergonomically shaped ▪ Comfortable toe-room ▪ Good coverage of the little toe area

INLAY SOLE

Full-length fleece inlay sole	▪ Fleece material ▪ Exchangeable ▪ Sturdy ▪ Good moisture absorption and release for a comfortable foot climate ▪ Antistatic

INSOLE

Antistatic soft-fleece insole	▪ Antistatic, even when 100% dry and without the need for additional aids to provide a bridge to the outsole ▪ Approx. 50% lighter than comparable soles made of natural materials ▪ Flexible and shape-retaining ▪ Good air permeability ▪ Excellent wear resistance ▪ High moisture absorption ▪ Quick drying (virtually overnight)

PENETRATION PROTECTION

Steel midsole  	▪ Fulfils the additional requirements for penetration protection in accordance with EN ISO 20344 / 20345 ▪ Fulfils the penetration safety standard EN 12568 ▪ Corrosion-resistant ▪ Stainless steel

OUTSOLE

	SAFETY-GRIP deep-treaded double-density sole with profile	▪ S-line shaped configuration of the tread blocks, for an ergonomic foot roll ▪ Excellent slip resistance ▪ Antistatic
	Outsole: PU 	▪ Colour: black ▪ 6 mm profile depth ▪ Particularly abrasion-resistant ▪ Heat-resistant to approx. 130°C, flexible at cold temperatures to approx. -20°C ▪ Oil and fuel resistant
	Midsole: PU	▪ The soft PU core provides a good impact absorption and high wearing comfort