TECHNICAL DATA SHEET

MASON Pro Mid ESD S3 Typ 2 No. 7681102 Sz. 36 - 48







LABELLING ACCORDING TO STANDARD

Standard for safety footwear EN ISO 20345:2022 S3	Basic requirement for S3: **A** Antistatic shoe - **E** Energy absorption in the heel - **FO** Fuel resistance - **WPA** Water penetration and absorption - **P** Penetration resistance - Closed heel area - Profiled outsole
Additional requirements	**FO** FUEL RESISTANCE **SR** SLIP RESISTANCE on ceramic tile with glycerine. **SC** SCUFF CAP The overcap manages a certain amount of abrasion.

FORM

Safety boot 	Form B - in size 42, the upper height must be at least 11.3 cm.

FIT		
ERGO-ACTIVE foot-type system	ERGO-ACTIVE foot type system with three fit variants The right shoe for everyone: Three different types of lasts do not only take into account length and width of the foot, but also toe length, heel width and angle of the ball of the foot.	
	Foot type 1: • For larger feet • Short toes • Wide ball and heel area • Steep ball angle	
	Foot type 2: • For normal feet • Long toes • Medium-wide ball and heel area • Flat ball angle	
	Foot type 3: • For slim feet • Medium-sized toes • Narrow ball and heel area • Medium ball angle	
AREAS OF APPLICATION		
Areas of application	Indoors and outdoors Areas where exposure to moisture is expected (S2) Areas where there is a risk of penetration from pointed and sharp objects (S3) Areas where there is a risk of electrostatic discharge (ESDS/ESD)	
FEATURES		
ESD equipment	Thanks to its excellent discharge capability, the shoe is suitable for work in ESD sensitive or electrostatically protected areas (EPA). The shoes comply to the standard 61340-5-1.	
Certification in accordance with DGUV rule 112-191	• Certified for orthopaedic modifications / inserts	
Full, padded bellows tongue	• Excellent wearing comfort: The tongue prevents pressure marks and avoids dirt from entering into the shoe.	
Collar padding	• Excellent wearing comfort: the ankle-wrapping, softly padded upper edge provides for stability and grip in the shoe.	
Reflective material	• Good visibility in the dark	
TPU scuff cap	• Excellent wear protection in the shoe tip • Protects the upper leather in this area against premature wear	

FEATURES	
Winner Plus X Award	The independent jury for the Plus X Award, the Innovation Prize for Technology, Spot, and Lifestyle, grants a total of seven seals of approval to brands that offer products with a competitive edge in terms of quality and innovation. ELTEN has always seen itself as an innovative business at the cutting edge of technology.
UPPER MATERIAL	
Cowhide leather	• Areas of application S1/S2/S3 • Natural material • Wear-resistant • Breathable • Water penetration/absorption in accordance with EN ISO 20345 S2
LINING	
Breathable fabric lining	• Climate-regulating • Good ventilation • Skin-friendly • High absorption and emission of moisture
Heel pocket lining	• The abrasion-resistant microfibre material is particularly sturdy and provides for a pleasant wearing comfort.
TOE PROTECTION CAP	
Steel toe cap 	• Protection against impacts of min. 200 joules and pressure loading of min. 15 kN • Permanent edge coverage for cushioning • Ergonomically shaped • Comfortable toe room • Good coverage of the little toe area
INLAY SOLE	
Semi-orthopaedic inlay sole ESD 	• ESD EQUIPMENT: Protection against electrostatic discharge (ESD). The full-length, exchangeable inlay sole is conductive and designed for the use in ESD safety footwear according to the standards DIN EN ISO 20345 and DIN EN 61340-5-1. • The sole’s footbed is tailored to the fit of the shoe as well as to the natural, intact longitudinal arch of the foot. • The improved heel damping is kind to the entire musculoskeletal system – from foot to spinal column. • Improvement of the shoe climate thanks to the PU foam's open cell structure. So the foot is always kept comfortably dry. • The extreme softness of the PU foam absorbs shocks on impact and increases walking comfort.

INSOLE	
ESD soft-fleece insole	ESD equipment: Protection against electrostatic discharge (ESD), and without using additional means fulfilling a bridge function to the outsole. • Approximately 50 % lighter than comparable soles made of natural materials • Flexible and shape-retaining • Good air permeability • Excellent wear resistance • High moisture absorption • Quick drying (virtually overnight)
PENETRATION RESISTANCE	
Steel midsole	Best possible protection from below: The corrosion-resistant midsole made of stainless steel complies with the penetration safety standard EN 12568 and furthermore fulfils the additional requirements for penetration protection in accordance with EN ISO 20344 / 20345. Particularly recommendable when working in areas where there is an increased risk of injuries due to pointed or sharp objects, such as in the construction industry.
OUTSOLE	
ERGO-ACTIVE double-density sole with profile  	• Excellent slip resistance • Antistatic
	Outsole: PU (polyurethane) • Colour: lightgrey • Profile depth: 4.0 mm • Abrasion-resistant • Heat-resistant to approx. 130°C • Flexible at cold temperatures to approx. -20°C • Oil and fuel resistant
	Midsole: PU (polyurethane) • The soft PU core provides a good impact absorption and high wearing comfort