ReliaDisc™

760104

Characteristics:

Celluloseacetat (CA) membrane
100 units per pack
Non sterile packaging

Applications:

Widely used for clarification of aqueous solutions, nutrient media, buffers, and sera.

Benefits:

Hydrophilic
Chemical resistance to alcohol and oil
Thermal stability up to 180°C max

Physical properties	Units	Typical Value
Diameter	mm	47
Thickness	µm	120
Pore Size	µm	0.45
Flow Rate for water	ml/(min cm² bar)	69
Burst Pressure	bar	1,2
Bubble Point with water (acc. DIN 58355)	bar	1,9
Extractable content in water	%	< 1

25.06.2019 Rev01

All indicated data to be understood as typical average values.

This product is manufactured in conformance with the Quality Management standard DIN EN ISO 9001.

Contact office:

Ahlstrom-Munksjö Germany GmbH
Niederschlag 1
D-09471 Bärenstein
Germany

T: +49 (0) 37347 / 83-0
F: +49 (0) 37347 / 83-64
Email: filtrak@ahlstrom-munksjo.com
www.ahlstrom-munksjo.com

DISCLAIMER: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed, including without limitation any warranty of merchantability and fitness for use. All users of the material are responsible for assuring that it is suitable for their needs, environment and end use. All data is subject to change as Ahlstrom-Munksjö deems appropriate. Refer to www.ahlstrom-munksjo.com for contact information.

© Ahlstrom-Munksjö 2017