TECHNICAL SPECIFICATION

HEAD PROTECTION

EVOLite® Skyworker™ Micro Peak Revolution®Wheel Ratchet Vented

White / AJS260-000-100



DESCRIPTION

The EVOLite® Skyworker™ helmet has a suspension system and shell structure that has been designed to be used for industrial, mountaineering, rescue and leisure activities.

Meeting the EN 12492 standard. A helmet complying to the mountaineering standard is impact tested with two 5kg strikers. A hemispherical striker is dropped from 2 metres onto the crown of the helmet and a flat striker from 500mm on to the front, rear or side by tilting the headform to 30°. In all cases, the transmitted force through the neck of the headform must not exceed 10kN. Two penetration tests with a 3kg pointed striker are also performed within a 50mm radius of the helmet's crown without making contact with the headform.

Conforms to the mandatory shock absorption and penetration requirements of EN 397 industrial standard.

OPTIONS

White (AJS260-000-100)

Blue (AJS260-000-500)

Black (AJS260-001-100)

Orange (AJS260-000-800)

Green (AJS260-000-300)

Yellow (AJS260-000-200)

SAFETY STANDARDS

EN 12492 • EN 397

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

Peak
Micro

Side Impact Resistance
25 Joules

Molten Metal
Yes

Minimum Temperature
-40˚C

Recyclable
Shell

Depth Adjustment
3D Harness

Universal Accessories Slot
Yes

Reflective Option
Optional

BSI Kitemark
Yes

JSPCheck
Yes

Impact Resistance
100 Joules

Lateral Deformation
Yes

Maximum Temperature
+50˚C

ABS Shell
Yes

Textile
Harness

Wheel Ratchet
Yes

Ventilation
Yes

ID card holder
Optional

Fitted 4 point chinstrap (EN12492 Compliant)
Fitted

Product Weight
382g

FEATURES



EPS Liner

Side, front and rear impact protection from the shock absorbing EPS liner. The liner is vented to increase comfort whilst maintaining a high protection factor.




CR2™ Reflective

Using Class RA2, high intensity reflective. CR2™ is the biggest step-up in night time visibility/reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.



Most Secure Fit

Fully adjustable 4-point chinstrap with quick release buckle. Easy to use Revolution® wheel ratchet and 3D adjustment that offers 1-2-3 point harness depth settings for a perfect fit.



Ventilation Option

Side and rear ventilation for optimum air movement inside the shell, reducing helmet temperatures by an average 2-3 degrees.



Supreme Comfort

6-point terylene cradle harness system with 3D adjustment offering1-2-3 point harness depth settings and an Egyptian cotton Chamlon™ sweatband.



Accessories

A universal attachment slot enables firm fitting of a range of Surefit™ safety visors and ear defenders.



JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

LOGO

- [x] Front
- [x] Back
- [x] Sides

RANGE



VIDEOS

www.youtube.com/watch?v=2X3TSz5STxw

DOWNLOADS

Image Pack (ZIP)

Declaration of Conformity (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.