MICROFLEX®
ADVANCED DISPOSABLE HAND PROTECTION

63-864
Durable Latex Exam Glove

NRL
Latex

Dependable protection with a reliable grip

- **Enhanced finger thickness, for extra protection in rugged environments**
- **Textured fingertips for a more secure, confident grip when handling slippery and oily objects**
- **Double chlorinated for easy donning and a comfortable feel**
- **Excellent protection for automotive aftermarket work**



Industries

- Automotive
- Automotive Aftermarket
- Life Sciences
- Machinery and Equipment

Recommended For

- Inspection, selecting, checking parts
- General Purpose Auto Aftermarket
- Oil, fluids and filter change
- Engine transmission and repair
- Tire rotation & changes
- Maintaining lab furniture and equipment
- Sample taking and processing
- Raw material sample collection
- Inspection (picking, checking and marking)



MICROFLEX®
ADVANCED DISPOSABLE HAND PROTECTION

63-864
Durable Latex Exam Glove

TECHNICAL DATA SHEET

PRODUCT INFORMATION

	63-864
Material	Natural Rubber Latex
Color	Natural
Glove Design	Chlorinated, Powder-Free, Textured Fingers
Cuff	Beaded
Manufacturing/QMS Audit Standards	MDD 93/42/EEC
Regulatory	Category III, EC 1935/2004, EC 2023/2006, EN ISO 374-1:2016, EN ISO 374-5:2016, EN 420:2003 + A1:2009, EN 421:2010, EN 374:2003, European Directive 89/686/EEC
Packaging	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Malaysia
User Needs Segment	Robust
Available sizes	XS (5.5 - 6), S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10)
Anti-static	No
Vulcanization Chemical Accelerators	• Zinc Dibutyldithiocarbamate (ZDBC) • Zinc Diethyldithiocarbamate (ZDEC) • Natural rubber proteins *Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.*


PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	245 / 9.6		ASTM D3767,ASTM D6977,EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.16 / 6.3		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.20 / 7.9		ASTM D3767,EN 420
	BEFORE AGING	**AFTER AGING**	
Ultimate Tensile Strength (MPa)	≥ 27	≥ 21	ASTM D412 & D573
Elongation at Break (%)	≥ 750	≥ 600	ASTM D412
Force at break (N)	≥ 6	≥ 12	EN 455-2

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	63864060	63864070	63864080	63864090	63864100

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region
Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region
Ansell Global Trading Center (Malaysia) Sdn Bhd
T: +603 8310 6688
F: +603 8310 6699

North America Region
Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region
Ansell Commercial Mexico S.A. de C.V.
T: +52 442 248 1544 / 248 3133

Australia
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia
Ansell PYC
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2022 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

Ansell