# TECHNICAL DATA SHEET



## LENNY S3
## No. 12321

**Sz. 36-48**

## LABELLING ACCORDING TO STANDARD

| | |
|---|---|
| In accordance with EN ISO 20345 S3 SRC | |
| Form A  | ▪ Safety shoe, low cut |
| SRC SLIP RESISTANCE | SLIP RESISTANCE: When it comes to slip resistance as defined by EN ISO 20345, SRC signifies the best possible rating a safety shoe can reach. |

## FIT

## AREAS OF APPLICATION

| | |
|---|---|
| | ▪ Indoors and outdoors<br>▪ Industry, storage, transport, construction etc.<br>▪ Areas where exposure to moisture is expected (S2)<br>▪ Areas where there is a risk of penetration from pointed and sharp objects (S3) |

## FEATURES

| | |
|---|---|
| Design | ▪ Modern and sporty design |
| Full, padded bellows tongue | ▪ Extremely comfortable<br>▪ Prevents pressure points<br>▪ Prevents penetration of dirt |
| Padded upper edge | ▪ Extremely comfortable<br>▪ Protects the Achilles tendon |
| Sizes (unisex model) | ▪ Expanded size range<br>▪ Available in sizes 36-48 |

## FEATURES

| | |
|---|---|
| PU toe protection (polyurethane) | ▪ Directly applied toe protection<br>▪ Excellent wear protection in the toe area<br>▪ Protects the upper leather in this area against premature wear |

## UPPER MATERIAL

| | |
|---|---|
| Cowhide leather | ▪ Areas of application S2/S3<br>▪ Natural material<br>▪ Wear-resistant<br>▪ Breathable<br>▪ Water penetration/absorption in accordance with EN ISO 20345 S2 |

## LINING

| | |
|---|---|
| Climate-regulatin textile lining | ▪ Climate-regulating<br>▪ Good ventilation<br>▪ Skin-friendly<br>▪ High absorption and emission of moisture |
| Heel pocket lining | ▪ Abrasion-resistant microfibre material, sturdy<br>▪ Comfortable |

## TOE PROTECTION CAP

| | |
|---|---|
| Steel toe cap   | ▪ Protection against impacts of min. 200 joules and pressure loading of min. 15 kN<br>▪ Permanent edge coverage for cushioning<br>▪ Ergonomically shaped<br>▪ Comfortable toe-room<br>▪ Good coverage of the little toe area |

## INLAY SOLE

| | |
|---|---|
| Full-length inlay sole | ▪ Excellent moisture absorption and release providing a comfortable foot climate<br>▪ Exchangeable<br>▪ Sturdy<br>▪ Antistatic |

## INSOLE

| | |
|---|---|
| Antistatic soft-fleece insole | ▪ Antistatic, even when 100% dry and without the need for additional aids to provide a bridge to the outsole<br>▪ Approx. 50% lighter than comparable soles made of natural materials<br>▪ Flexible and shape-retaining<br>▪ Good air permeability<br>▪ Excellent wear resistance<br>▪ High moisture absorption<br>▪ Quick drying (virtually overnight) |

## PENETRATION PROTECTION

| | |
|---|---|
| Steel midsole  | ▪ Fulfils the additional requirements for penetration protection in accordance with EN ISO 20344 / 20345<br>▪ Fulfils the penetration safety standard EN 12568<br>▪ Corrosion-resistant<br>▪ Stainless steel |

## OUTSOLE

| | | |
|---|---|---|
|  | Double-density sole with profile<br>NEW BASIC | ▪ Antistatic<br>▪ Excellent slip resistance |
| | Outsole: PU | ▪ Colour: grey<br>▪ Particularly abrasion-resistant<br>▪ Heat-resistant to approx. 130°C, flexible at cold temperatures to approx. -20°C<br>▪ Oil and fuel resistant |
| | Midsole: PU | ▪ Colour: black<br>▪ The soft PU core provides a good impact absorption and high comfort |