UltraTape
Adhesive Tape & Labels for Critical Environments

PRODUCT DATASHEET

UT1165 Striped Over Laminated Floor Marking Cleanroom Tape

DESCRIPTION

UltraTape 1165 / 0165 is a highly durable floor marking tape designed to withstand high traffic and frequent cleaning. Its over laminated finish provides vibrant striped colors which are abrasion and chemical resistant.

- Designed for cleanroom use
- Chemical resistant, stands up to regular wiping and moping
- Stands up to foot, cart and forklift traffic
- Long term durability, colors don't fade

PROPERTIES

Backing	Laminated Vinyl
Adhesive	Rubber
Total Thickness	9.1 mils (0.23 mm)
Adhesion to Stainless Steel	21 oz. / in. (0.24 kg/25mm)
Elongation	200%
Operating Temperature	-20°F to 140°F (-28°C to 60°C)
Tensile Strength	5.9 kg (33 lbs./in)
Length	18 yards
Colors	Black/White (BW), Black/Yellow (BY), Green/White (GW), Red/White (RW)

To achieve ultimate adhesion, the bonding surface should be clean, dry, and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly in contact with the adhesive. Firm pressure is recommended to achieve good adhesive to surface contact.

UltraTape recommends that each user conduct their own test to determine the product's suitability for the intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.

9770 SW Wilsonville Road, Suite 400
Wilsonville, OR 97070
www.cleanroomtape.com

503.427.2880
503.482.5616

© UltraTape 2022 | Rev. 05/2022

ISO 9001:2015

UL LISTED

A division of DELPHON