



Dry Block Heater 3

Digital block heater for three aluminum blocks provides precise temperature control in small vessels. Included PT-1000 temperature sensor allows temperature control directly in the sample vessel. It is used with PCR tubes, PCR strips, Greiner tubes, microplates and cuvettes. The block heater is ideal for melting and boiling point determination, enzyme reactions, incubation and activation of cultures, immunoassays, DNA denaturation, culture media test, coagulation test, blood-urea-nitrogen determination and in situ hybridizations.

- Stepless adjustable temperature up to 120 °C
- Timer: Countdown, adjustable from 1 min to 99h 59min
- Counter: Display of heating time
- Highly versatile with a large number of blocks
- Error code display
- Fixed safety circuit
- Acoustic signal at end of test

Accessories: DB 1.1, DB 1.2, DB 1.3, DB 1.4, DB 1.5, DB 2.1, DB 2.2, DB 3.1, DB 3.2, DB 3.3, DB 4.1, DB 4.2, DB 4.3, DB 4.4, DB 4.5, DB 4.6, DB 4.7, DB 4.8, DB 4.9, DB 5.1, DB 5.2, DB 5.3, DB 5.4, DB 5.5, PT 1000.60 Temperature sensor, stainless steel, PT 1000.90 Temperature sensor, coated

Technical Data

Number of blocks	3
Heat output [W]	330
Heating temperature range [°C]	room temp. +5° - 120
Temperature display	yes
Heat control accuracy [±K]	1
Connection for ext. temperature sensor	DIN 12 878
Temperature stability within the blocks at 37°C [±°C]	0.2
Temperature stability within the blocks at 60°C [±°C]	0.4
Set-up plate material	Aluminium alloy
Set-up plate dimensions [mm]	96 x 228
Fixed safety circuit [°C]	150
Timer	yes
Time setting range [min]	1 - 5999
Dimensions (W x H x D) [mm]	151 x 73 x 380
Weight [kg]	1.6
Permissible ambient temperature [°C]	5 - 40
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 21
RS 232 interface	no
USB interface	no
Voltage [V]	220 - 240 / 115
Frequency [Hz]	50/60
Power input [W]	330

Ident. No. 0004025301