

JALAS® 6458 PRIMA WHITE

EN ISO 20345:2011, S3 SRC

PROPERTIES
Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

SPECIFICATION

TYPE OF SHOE **Safety footwear, low shoes**

NAIL PROTECTION MATERIAL **Plasma-treated composite (PTC) textile**

FITTING **Narrow/Regular**

SIZE RANGE **36-47**

COLLECTION **Green Line**

PLATFORM **Green Line**

UPPER MATERIAL **Microfiber**

TOECAP MATERIAL **Composite**

LINING MATERIAL **Polyester, polyamide**

SOLE MATERIAL **Plastic shank, PU outsole**

INSOLE **FX2 Pro**

INSOLE MATERIAL **Textile, soft EVA, polyester-based conductive thread, double shock absorption zones in Poron® XRD®**

FASTENING **Laces**

COLOUR **White, grey**

SIZE	ART. NO.	EAN NO.
36	6458-36	6408487503412
37	6458-37	6408487503429
38	6458-38	6408487503436
39	6458-39	6408487503443
40	6458-40	6408487503450
41	6458-41	6408487503467
42	6458-42	6408487503474
43	6458-43	6408487503481
44	6458-44	6408487503498
45	6458-45	6408487503504
46	6458-46	6408487503511
47	6458-47	6408487503528

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2015-08-28

Finnish Institute of Occupational Health

SP Technical research institute of Sweden

JALAS® 6458 PRIMA WHITE



FEATURES
Oil-resistant outsole, metal free, anti-static properties, polstered shaft edge, ventilating insole, water repellent, double shock absorption zones, conforms with IEC 61340-5-1 (ESD), good environmental choice

PRIMARY PROTECTION
Prevents risk of:, toe injuries, nail penetration, antistatic

PRIMARY ENVIRONMENTS OF USE
Outdoors, metal-free requirements for shoes, environments with risk for outsole penetration

CE

- Composite toecap
- Nail protection in plasma-treated composite (PTC) textile
- Water repellent
- Oil-resistant outsole
- Ergothan Shock Absorption System
- Anti-static properties
- ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2015-08-28

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB
Box 7, SE-793 21 Leksand, Sweden
Phone +46 (0) 247 360 00
Fax +46 (0) 247 360 10
info@ejendals.com
order@ejendals.com
www.ejendals.com

JALAS® 6458 PRIMA WHITE



COMPLIANCE
EN ISO 20345:2011

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

S3: S2 + P

WRU: Water-resistant upper

P: Penetration-resistant outsole

A: Electrical resistance (between 0.1-1000 Mega Ohms

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

BGR 191: Orthopedic footwear adjustment according to German BGR 191. Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

CE

- Composite toecap
- Nail protection in plasma-treated composite (PTC) textile
- Water repellent
- Oil-resistant outsole
- Ergothan Shock Absorption System
- Anti-static properties
- ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2015-08-28

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB
Box 7, SE-793 21 Leksand, Sweden
Phone +46 (0) 247 360 00
Fax +46 (0) 247 360 10
info@ejendals.com
order@ejendals.com
www.ejendals.com