



JALAS® 1828 JUPITER

EN ISO 20345:2011, S3 SRC CI HRO

PROPERTIES
Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

SPECIFICATION

TYPE OF SHOE **Safety footwear, boots/Ankle boots**

NAIL PROTECTION MATERIAL **Steel**

FITTING **Wide**

SIZE RANGE **35-50**

COLLECTION **Gran Premio**

PLATFORM **Enduro**

UPPER MATERIAL **PU-coated leather**

UPPER MATERIAL THICKNESS **1,6-1,8**

PRONOSE MATERIAL **PU**

TOECAP MATERIAL **Aluminium**

LINING MATERIAL **Polyester, polyamide**

SOLE MATERIAL **PU midsole, rubber outsole**

INSOLE **FX2 Pro**

INSOLE MATERIAL **Textile, soft EVA, polyester-based conductive thread, double shock absorption zones in Poron® XRD®**

FASTENING **Laces**

COLOUR **Black, grey, yellow**

SIZE	ART. NO.	EAN NO.	SIZE	ART. NO.	EAN NO.
35	1828-35	6408487502163	47	1828-47	6408487440557
36	1828-36	6408487502170	48	1828-48	6408487440564
37	1828-37	6408487440458	49	1828-49	6408487502194
38	1828-38	6408487440465	50	1828-50	6408487502187
39	1828-39	6408487440472			
40	1828-40	6408487440489			
41	1828-41	6408487440496			
42	1828-42	6408487440502			
43	1828-43	6408487440519			
44	1828-44	6408487440526			
45	1828-45	6408487440533			
46	1828-46	6408487440540			

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2016-04-11

A MEMBER OF SATRA TECHNOLOGY CENTRE
Finnish Institute of Occupational Health
SP Technical research institute of Sweden



JALAS® 1828 JUPITER

FEATURES
ProNose toe reinforcement, wide fit, heat-resistant outsole, oil-resistant outsole, anti-static properties, padded boot shaft, ventilating insole, pull loops, water repellent, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

PRIMARY PROTECTION
Prevents risk of:, toe injuries, nail penetration, antistatic

PRIMARY ENVIRONMENTS OF USE
Outdoors, environments with risk for outsole penetration, harsh environments

CE

- Aluminium toecap
- Ergothan Shock Absorption System
- Nail protection in steel
- Anti-static properties
- Heat-resistant outsole
- ESD
- Water repellent
- Oil-resistant outsole
- ProNose toe reinforcement
- Wide fit

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2016-04-11

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB
Box 7, SE-793 21 Leksand, Sweden
Phone +46 (0) 247 360 00
Fax +46 (0) 247 360 10
info@ejendals.com
order@ejendals.com
www.ejendals.com

JALAS® 1828 JUPITER



COMPLIANCE
EN ISO 20345:2011

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

S3: S2 + P

WRU: Water-resistant upper

P: Penetration-resistant outsole

HRO: Heat-resistant outsole compound tested at 300°C

CI: Cold insulation

A: Electrical resistance (between 0.1-1000 Mega Ohms

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

BGR 191: Orthopedic footwear adjustment according to German BGR 191. Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

CE

- Aluminium toecap
- Ergothan Shock Absorption System
- Nail protection in steel
- Anti-static properties
- Heat-resistant outsole
- ESD
- Water repellent
- Oil-resistant outsole
- ProNose toe reinforcement
- Wide fit

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2016-04-11

EJENDALS AB
Box 7, SE-793 21 Leksand, Sweden
Phone +46 (0) 247 360 00
Fax +46 (0) 247 360 10
info@ejendals.com
order@ejendals.com
www.ejendals.com