

Certificate of Conformity

VWR Catalogue Number	115-0047
Description	Multi-layer adhesive floor mats, PureStep 30 layers, 8 µm ±20% mm thickness, 610 mm Length, 762 mm Width, Blue
Lot Number	UU0249
Country of Origin	Manufactured in China
Date of Issue (yyyy-mm-dd)	2023-05-12

Quality System Compliance

Products are manufactured under the **ISO 9001:2015 & ISO 14000:2015** standard. Products are inspected and controlled through whole production processing in accordance with current applicable product specifications and QC SOP.

QC Testing

Representative products samples are collected and inspected in accordance with current applicable QC requirements.

Product Specifications

Material	Low Density Polyethylene, (LDPE) Blend, with 20% biohybrid resin.
Sterilization	Not Applicable.
ATP Assay	Not Applicable.
DNase & RNase Free	Not Applicable.
BSE/TSE	No use of any raw material produced from or substances derived from animal origin. The manufacturing process of the product does not use any ingredient of animal origin and no material derived from or exposed to animals affected by or under quarantine for transmitting Animal Bovine Spongiform Encephalopathy/Spongiform Encephalopathy (BSE)/(TSE).
Cytotoxicity	Not Applicable.
Non-Pyrogenic Statement	Not Tested.

Latex Statement	This product is not made from natural rubber latex.
BPA Statement	Bisphenol are not used in the manufacture of the raw material and are not expected to be present.
DEHP Statement	Please see RoHS information below.
RoHS	No substances (Lead, Cadmium, Mercury, Hexavalent Chromium (Cr6+), Poly Brominated Biphenyls (PBB), Poly Brominated Diphenyl ethers (PBDE), Bis(2-Ethyhexyl) Phthalate (DEHP), Benzyl Butyl Phthalate (BBP), Dibutyl Phthalate (DBP), Diisobutyl Phthalate (DIBP)) are used in manufacturing the raw materials and final product. No routinely analyse is performed.
REACH Statement	No substances as listed on >Substance of Very High Concern< candidate list published 2022-06-10 are used in manufacturing of the raw materials used to produce this product. No routinely analysis is performed.
Storage Conditions	Store at 12-35 °C (54-95F).

Disclaimer: VWR states that this declaration will not discharge the user from their obligation to ensure the product is suitable for the intended use. The purpose of the product is for use in laboratory only.
This document has been produced electronically and is valid without a signature.

Annex

Mat Layers: Low Density Polyethylene.

1.8 mil (45 micron) for 30 Layer, 4 mat**
 1.4 mil (35 micron) for 30 Layer, 8 mat and 60 Layer**

Adhesive: 0.3 mil (7 micron) acrylic based**

Peel Adhesive: 9.0 oz. (250g)/25mm, Individual layers (+/- 50g)
 24 oz. (700g)/25mm, Bottom layer. (+/- 50g)

Surface		Bottom	
Tack Spec	Tack Actual	Tack Spec	Tack Actual
190-230	177	550-650	616