

JALAS® 3520 WHITE

EN ISO 20345:2011, S2 SRC

PROPERTIES
Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

SPECIFICATION

TYPE OF SHOE **Safety footwear, loafers**

FITTING **Regular**

SIZE RANGE **36-47**

COLLECTION **White**

PLATFORM **M-Sport**

UPPER MATERIAL **PU-coated leather**

TOECAP MATERIAL **Aluminium**

LINING MATERIAL **Polyester, polyamide**

SOLE MATERIAL **Plastic shank, PU outsole**

INSOLE **FX2 Pro**

INSOLE MATERIAL **Textile, soft EVA, polyester-based conductive thread, double shock absorption zones in Poron® XRD®**

FASTENING **Elasticated opening**

COLOUR **White**

SIZE	ART. NO.	EAN NO.
36	3520-36	6408487431104
37	3520-37	6408487431111
38	3520-38	6408487431128
39	3520-39	6408487431135
40	3520-40	6408487431142
41	3520-41	6408487431159
42	3520-42	6408487431166
43	3520-43	6408487431173
44	3520-44	6408487431180
45	3520-45	6408487431197
46	3520-46	6408487431203
47	3520-47	6408487431210

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2015-09-30

A MEMBER OF SATRA TECHNOLOGY CENTRE
Finnish Institute of Occupational Health
SP Technical research institute of Sweden



JALAS® 3520 WHITE

FEATURES
Oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, water repellent, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

PRIMARY PROTECTION
Prevents risk of:, toe injuries, antistatic

PRIMARY ENVIRONMENTS OF USE
Outdoors, indoors

PRIMARY AREAS OF USE
Laboratory work, paint spraying work

CE

- Aluminium toecap
- Water repellent
- Oil-resistant outsole
- Ergothan Shock Absorption System
- Anti-static properties
- ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2015-09-30

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB
Box 7, SE-793 21 Leksand, Sweden
Phone +46 (0) 247 360 00
Fax +46 (0) 247 360 10
info@ejendals.com
order@ejendals.com
www.ejendals.com

JALAS® 3520 WHITE



COMPLIANCE
EN ISO 20345:2011

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

WRU: Water-resistant upper

A: Electrical resistance (between 0.1-1000 Mega Ohms

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

BGR 191: Orthopedic footwear adjustment according to German BGR 191. Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

CE

- Aluminium toecap
- Water repellent
- Oil-resistant outsole
- Ergothan Shock Absorption System
- Anti-static properties
- ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2015-09-30

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB
Box 7, SE-793 21 Leksand, Sweden
Phone +46 (0) 247 360 00
Fax +46 (0) 247 360 10
info@ejendals.com
order@ejendals.com
www.ejendals.com