TECHNICAL DATA SHEET

Item Code PL 1140 - 1141 - 1142

GENERAL FEATURES		
Description	Graduated heavy duty bucket with spout - Iron handle	
Raw material	Body	Low Density Polyethylene (LDPE)
	Cap	-
	Inner-cap	-
Usage	Heavy duty bucket with iron handle. It features large spout and flat bottom for easy pouring and total emptying.	

TECHNICAL SPECIFICATIONS	
Semitransparency	No
Colour	Body: White
	Cap: -
	Inner-cap: -
UN Approval:	-
Standards conformity:	-
Temperature range	-20°C / +70°C
Sterilizability:	By radiation
Autoclavability:	No
Food contact compliance	The product is suitable for food contact. It meets relevant requirements of the following directives or regulations: 1935/2004/CE as amended, UE 10/2011 as amended



Item code PL	1140	1141	1142
DIMENSIONS			
Capacity	9 l	12 l	17 l
Graduation	1 l	1 l	1 l
Diameter (top):	270 mm	302 mm	335 mm
Diameter (base)	200 mm	220 mm	245 mm
Height	250 mm	280 mm	310 mm
Normalized neck	-	-	-
Dimensional tolerances	-	-	-
PACKAGING			
Pieces per bag	1	1	1
Pieces per box	10	10	10
Pieces per pallet	720	720	720
Pallet dimensions	80x120x220 cm	80x120x220 cm	80x120x220 cm

OTHER REMARKS
-

LAMAPLAST

TECHNICAL DATA SHEET

Item Code PL 1140 - 1141 - 1142

CHEMICAL COMPATIBILITY

Products manufactured by polyethylene or polypropylene are normally suitable for room-temperature contact with many organic solvents, diluted solutions of acids, bases and salts. They are typically not suitable for use with concentrated oxidizing acids and halogenated solvents. Detailed information on physical properties and chemical resistance (including concentration and temperature effect) are available upon request.

Several factors however may effect chemical comptibility such as temperature, concentration, contact time, presence of internal stress, wall/film thickness. The user is advised to carry out its own tests to determine product suitability for the particular environment/application.

STORAGE CONDITIONS

Product should be stored in its original packaging and kept dry at all times. If product is delivered on pallet regular inspection is suggested. Storage area should be clean and dry. Never expose product to direct sunlight.

Optimum storage temperature is between 10°C and 30°C, 20% to 80% RH

Avoid prolonged storage at extreme temperature. Do not exceed the following limits: -10°C / +40°C

LEGAL DISCLAIMER

The information contained in this data sheet are intended for informational purposes only and may be modified without notice. The images are for illustrative purposes and may differ from the actual product. Lamaplast Srl reserves the right to make improvements and / or changes to the product described without notice.