

HiTrap Capto adhere, 1 ml and 5 ml

Capto™ adhere is a multimodal BioProcess™ medium for intermediate purification and polishing of monoclonal antibodies after capture on Protein A medium by packed bed chromatography. In combination with Protein A medium (i.e., MabSelect™ family), Capto adhere offers a robust chromatography platform for the development of monoclonal antibody manufacturing processes.

Capto adhere improves yield, productivity and process economy with:

- High capacity in flow-through mode
- Contaminant removal to formulation levels in post Protein A purification:
 - Leached Protein A
 - Antibody dimers and aggregates
 - Host cell proteins
 - Nucleic acids
 - Viruses
- Wider operational window of pH and conductivity
- Savings in time and operating costs with a two steps chromatographic process

HiTrap™ Capto adhere are prepacked 1 ml and 5 ml columns for screening of loading and elution conditions, and method scouting. The column design, together with a modern chromatography medium, provides fast, reproducible separations in a convenient format. The columns are best used with liquid chromatography systems such as ÄKTA design™ or FPLC™ System but can be operated with a syringe or peristaltic pump.



Connectors

Connectors supplied	Usage	No. supplied
1/16" male/Luer female	Connection of syringe to top of HiTrap column	1
Tubing connector flangeless/M6 female	Connection of tubing (e.g., Peristaltic Pump P1) to bottom of HiTrap column ¹	1
Tubing connector flangeless/M6 male	Connection of tubing (e.g., Peristaltic Pump P1) to top of HiTrap column ²	1
Union 1/16" female/ M6 male	Connection to original FPLC System through bottom of HiTrap column	1
Union M6 female/ 1/16" male	Connection to original FPLC System through top of HiTrap column	1
Stop plug female, 1/16"	Sealing bottom of HiTrap column	5

¹ Union 1/16" female/M6 male is also needed.

² Union M6 female/1/16" male is also needed.

Table of contents

1. Description	4
2. Method design and optimization	7
3. Maintenance	21
4. Ordering information	22
5. Further information	23

1. Description

Column properties

The columns are made of biocompatible polypropylene that does not interact with biomolecules. The columns are delivered with a stopper at the inlet and a snap-off end at the outlet. Table 1 lists the characteristics of HiTrap columns.

Note: HiTrap columns cannot be opened or refilled.

Note: Ensure that the connectors are tight to prevent leakage.

Table. 1. Characteristics of HiTrap columns.

Column volumes	1 and 5 ml
Column dimensions	0.7 × 2.5 cm (1 ml); 1.6 × 2.5 cm (5 ml)
Maximum flow rates	HiTrap 1 ml: 4 ml/min, HiTrap 5 ml: 20 ml/min
Recommended flow rates ¹ :	HiTrap 1 ml: 0.5 ml/min, HiTrap 5 ml: 2.5 ml/min
Maximum back pressure	0.3 MPa (3 bar)

¹ Corresponding to a residence time of 2 min (see chapter about flow velocity and residence time below)

Medium Properties

Capto adhere is a strong anion exchanger with multimodal functionality (Fig 1). The multimodal functionality gives a different selectivity compared to traditional anion exchangers. Capto adhere is designed for post Protein A purification of monoclonal antibodies. Removal of leached Protein A, aggregates, host cell proteins, nucleic acids and viruses from monoclonal antibodies is performed in flow-through mode at which the antibodies pass directly through the column while the contaminants are adsorbed.




Fig 1. The Capto adhere ligand, N-Benzyl-N-methyl ethanol amine, exhibits many functionalities for interaction. The most pronounced are ionic interaction, hydrogen bonding and hydrophobic interaction.

Table 2. Characteristics of Capto adhere

Matrix	highly cross-linked agarose
Functional group	multimodal strong anion exchanger
Total ionic capacity	0.09 – 0.12 mmol Cl ⁻ /ml medium
Particle size ¹	75 µm (d _{50v})
Flow velocity ²	at least 600 cm/h in a 1 m diameter column with 20 cm bed height at 20°C using process buffers with the same viscosity as water at < 3 bar (0.3 MPa)
pH-stability ³	
short term	2-14
long term	3-12
Working temperature ⁴	4 to 30°C
Chemical stability ⁵	all commonly used aqueous buffers, 1 M acetic acid, 1 M sodium hydroxide.
Avoid	oxidizing agents, anionic detergents

¹ d_{50v} is the median particle size of the cumulative volume distribution.

² The capacity for selective removal of some key contaminants may decrease at high flow velocity.

³ Short term pH: pH interval where the medium can be subjected to, for cleaning- or sanitization-in-place.
Long term pH: pH interval where the medium can be operated without significant change in function.

⁴ Capto adhere can be used under cold-room conditions, but the capacity for some key contaminants may decrease.

⁵ No significant change in ionic binding capacity and carbon content after 1 week storage in 1 M NaOH at 40°C.

2. Method design and optimization

Capto adhere is a multimodal ion exchanger designed to be used as a second or third step in monoclonal antibody (MAb) purification processes, (i.e., after capture on Protein A medium)). Removal of leached Protein A, antibody dimers and aggregates (D/A), host cell proteins (HCP), viruses and nucleic acids is preferably performed in flow-through mode where the antibodies pass directly through the column while the contaminants are adsorbed.

General purification protocol

- Adjust pH and conductivity of the sample to loading conditions for flow-through mode.
- Equilibrate the column with loading buffer of the same pH and conductivity as the sample.
- Apply the sample onto the column. Collect the flowthrough fraction.
- Wash out unbound material with loading buffer and collect together with the flowthrough fraction.
- Regenerate column to elute bound material.
- Clean-in-place (CIP).
- Re-equilibrate.

Sample preparation

Before sample loading, pH and conductivity of the sample should be adjusted to desired loading conditions. This is done either by buffer exchange or by direct adjustment of pH and conductivity. Buffers normally used for ion exchange chromatography can also be used also for Capto adhere (Table 2).

Table 2. Recommended buffers.

pH interval	Buffer ^{1,2}	Concentration ³
4 - 5	Acetate	20 - 100 mM
4 - 6	Citrate	20 - 200 mM
5.5 - 6.5	Bis-TRIS	20 - 50 mM
6 - 7.5	Phosphate	50 - 200 mM
7.5 - 8.5	TRIS	20 - 50 mM
8.5 -	Glycin-NaOH	20 - 100 mM

¹ The choice of buffer systems and salts may influence both yield and contaminant clearance.

² Buffers in the interval 5.5 – 8 will normally be most efficient for contaminant removal.

³ Conductivity can be adjusted by addition of salt or by varying the buffer concentration.

Buffer exchange

For preparation of samples for optimization of loading conditions in lab scale, buffer exchange can be performed on HiPrep™ 26/10 Desalting. A typical chromatogram is shown in Figure 2.




Fig. 2. Buffer exchange on HiPrep 26/10 Desalting.

Sample: MabSelect SuRe™ eluted pool

Sample volume: 10 ml

Buffer: 25 mM BIS-Tris, 175 mM NaCl, pH 7.0

Flow rate: 15 ml/min

Pooled desalted material: 13 ml

Conductivity and pH adjustment

For larger volumes of feed, sample preparation is preferably performed by diafiltration or directly by adjustment of pH and conductivity¹.

¹ Buffer exchange may result in reduction of HCP levels and improve column performance.

Initial screening of loading conditions

Balancing product yield against product purity is the major consideration when optimizing a method. When running in flow-through mode, loading conditions will usually be a compromise between conditions favoring yield and conditions favoring contaminant clearance. By adjusting pH and conductivity of the sample as well as the sample load, conditions can be obtained where most contaminants are adsorbed while the monomeric antibodies pass through the column. Optimization of loading conditions is preferably performed by using Design of Experiments (DoE). A common approach in DoE is to define a reference experiment (center point) and perform representative experiments around that point. To be able to define the center point and the variable ranges some initial experiments are required.

To find conditions suitable for the DoE, initial experiments can be performed in binding mode, using a pH gradient for elution (Fig 3, left). The elution position, that is pH at peak maximum, defines the lower pH in the design. The upper pH in the design should normally be about two pH units higher. Experiments can also be performed in flow-through mode, keeping the conductivity constant at a moderate level. A comparison of chromatograms is shown in Figure 3. At high pH (i.e., close to pI for the antibodies) the breakthrough during sample load is delayed, the breakthrough and wash curves are shallow and significant amounts of MAb binds to the adsorbent. A decrease in pH (i.e., further from pI) results in weaker electrostatic interaction between the antibodies and the adsorbent, steeper breakthrough and wash curves and increased yield.

In the DoE, pH, conductivity and load must be included. It is important to include conditions at the higher pH range resulting in lower yield and higher purity as well as conditions at lower pH range resulting in higher yield and lower purity. An example is given below.




Fig 3. Sample: rProtein A elution pool, after buffer exchange on HiPrep 26/10 Desalting.

Binding mode (left): Sample loading at pH 7.8. Load: 1 mg/ml medium.

Elution performed in a pH gradient from 7.8 to 4.0.

Flow-through mode (right): Comparison of chromatograms obtained at different pH. Load 75 mg MAb/ml medium. Conditions: pH 8.0, 2 mS/cm and pH 6.0, 2 mS/cm.

Design of experiments for optimization of loading conditions

Design of experiments (DoE) is recommended for optimization of loading conditions. By systematically varying important parameters (i.e., pH, conductivity and sample load) response surfaces can be obtained for yield and for clearance of key contaminants. The following is an example of how to set up a full factorial DoE with three parameters.

1. Work prior to actual setup of the design.
Perform initial loading experiments at varying pH, as described above. Choose parameters to include and define parameter ranges and responses.
2. Choose design for screening or optimization.
Full factorial design is commonly used in both screening and optimization. A full factorial DoE in 3 parameters will give $2^3 = 8$ experiments + center points

3. Choose center points for the design.
Center points are important in DoE, because they give an indication if there is curvature in the data. Three replicated center points are recommended. A full factorial design in three parameters with three center points gives a total of 11 experiments
4. Systematic variation of the parameters.
Limiting values, high and low, should be used of each parameter. The high and low values should be combined in a way that makes the parameters independent of each other to be able to separate effects. For further information, see www.umetrics.com.

Example of design of experiments

Start material: Monoclonal IgG₁ expressed in CHO cell culture supernatant, initially purified on rProtein A medium.

Sample characteristics: pI ~ 9, leached Protein A 36 ppm, D/A 3.3%¹ and HCP 210 ppm. The experimental setup was a full factorial design^{2, 3} in three variables, load, pH and conductivity, with additional points to resolve curvature effects (Table 3). In all, the number of experiments included in the model was 14, and the measured responses were yield (%) and Protein A (ppm), dimer/aggregate (%) and HCP (ppm) in the flowthrough pool. For each response a separate model was calculated. The models were fitted to MLR (multiple linear regression) and are well explained and show good stability to cross validation.

¹ As determined by analytical size exclusion chromatography on Superdex™ 200 10/300 GL.

² Experiments were designed and evaluated using Modde 7.0 software (Umetrics, Sweden).

³ www.umetrics.com.

Table 3. Design setup¹

Load (mg MAb/ml)	pH	Conductivity (mS/cm)
75	6	2
300	6	2
75	8	2
300	8	2
75	6	15
300	6	15
75	8	15
300	8	15
187.5	7	8.5
187.5	7	8.5
75	7	15
300	7	15
187.5	7	2
187.5	7	15

¹ The design setup includes 2 center points (bold) and 4 additional points at pH 7 to resolve curvature effects.

Parameters affecting the yield

The parameters that affect the yield are shown in the coefficient plot¹ (Fig 4). The plot shows that high sample load, low pH and high conductivity results in high yield. The interaction effects (load $\times$ pH and load $\times$ conductivity) are also significant for the yield response. The response surfaces also show that higher loads will give larger pH window with yield > 90%.




Fig 4. Coefficient plot and response surfaces for the yield model. Load versus pH at different conductivities.

¹ The coefficient plot describes the impact on the response from the investigated parameters. In the case above it can be seen that load is positively correlated to the response, meaning that a higher load will give a higher value on the response, pH is negatively correlated to the response, meaning that a lower pH will give a higher value on the response and conductivity is positively correlated to the response, but smaller, meaning that a higher conductivity will also give a higher response value, but not to the same extent as the effect of Load.

The interaction effects that are present in the coefficient plot (Load $\times$ pH and Load $\times$ Conductivity) means that if, for example pH is changed the response will not only be changed with the effect of pH but also with the effect of Load at that specific pH. The same goes for the Load $\times$ Conductivity interaction.

Parameters affecting the Protein A clearance

The coefficient plot shows that high pH will give good Protein A clearance. The conductivity by itself did not significantly affect the response, but there is a significant interaction effect for pH $\times$ conductivity (Fig 5). If this term is high, the Protein A clearance will be low. Load was not a significant factor for this response.

The response surfaces show that high pH and low conductivity will give high Protein A clearance.




Fig 5. Coefficient plot and response surfaces for the Protein A model. Conductivity *versus* pH. Protein A concentration expressed in ppm.

Parameters affecting dimer/aggregate clearance

The coefficient plot (Fig 6) shows that pH is the most important parameter and that high pH will give low D/A concentration in the flowthrough pool. The load parameter is also significant, but very small. The load should be low to give high D/A-clearance. There is also a significant curvature effect assigned to pH. If pH is too high or too low the D/A response will increase. The conductivity did not significantly affect D/A-clearance. The response curve shows that the load has only small affect on D/A-clearance, so only pH has to be considered.




Fig 6. Coefficient plot and response surfaces for the D/A model. Load versus pH. D/A concentration expressed in %.

Parameters affecting host cell proteins (HCP) clearance

The coefficient plot (Fig 7) and response curves shows that low sample load, low conductivity and high pH will give low HCP values.




Fig 7. Coefficient plot and response surfaces for the HCP model. Conductivity *versus* pH. HCP concentration expressed in ppm.

Conclusions

The response surfaces above show the influence of sample load, pH and conductivity on four different responses (yield of monomeric MAb and clearance of Protein A, dimer/aggregates and HCP respectively), and how to reach desired values for each of them. Even though the optimal conditions for each response is not the same, there is quite a large area where acceptable values can be obtained for all four responses.

Suggested loading conditions for this MAb could be a sample load of 200 mg/ml, pH 7 and conductivity 8.5 mS/cm.

General trends

Each monoclonal antibody is unique, and the level of contaminants varies between different cell lines and differences in previous purification steps. This implies that it may be difficult to predict optimal loading conditions.

However, based on design of experiments performed with several different antibodies some general trends have been identified (Fig 8).

- For best yield load should be high, the pH low and conductivity high.
- For the best D/A-clearance the pH should be high, while load and conductivity should be low. D/A-clearance is often less affected by conductivity than Protein A and HCP clearance.
- For the best Protein A- and HCP-clearance the pH should be high and conductivity low.




Fig 8. General trends with respect to loading conditions for yield, D/A-, Protein A- and HCP-clearance.

Loading conditions will therefore be a compromise between conditions favoring yield and conditions favoring contaminant clearance. Optimal loading conditions will be a balance between load, pH and conductivity. Consequently, for optimization of the loading step, all three parameters should be varied in the same experimental series.

In Table 4 optimal loading conditions for five different antibodies are shown. As can be seen, pH should normally be below the isoelectric point, while optimal conductivity is harder to predict.

Table 4. Optimal loading conditions for different MABs.

MAB	pI	pH	Conductivity (mS/cm)
MAB 1	~ 9	7.0	8
MAB 2	8.3 - 8.9	5.5	3
MAB 3	7.5 - 8.4	6.0	2
MAB 4	7.7 - 8.0	7.0	20
MAB 5	6.5 - 9.0	7.7	20

Flow velocity and residence time

For efficient removal of contaminants in flow-through mode, residence time¹ should be 2 minutes or more. Longer residence time may result in more efficient contaminant removal.

Bed height in HiTrap Capto adhere 1 ml and 5 ml columns is 2.5 cm. This implies flow rates of ≤ 0.5 ml/min (75 cm/h) for HiTrap 1 ml and ≤ 2.5 ml/min for HiTrap 5 ml.

In production scale bed heights of 10 - 20 cm are recommended. Recommended flow velocity is between 150 - 600 cm/h.

¹ Residence time, $\tau = L/u$, where L is the bed height in cm and u is the linear velocity (cm/h).

Wash out unbound material

After sample load, continue to wash out unbound MAb with loading buffer until the UV-curve starts to level off. The wash fractions can normally be pooled together with the flowthrough fractions. How much of the wash fractions that is collected is a balance between yield and dilution of the pooled material.




Fig 9. Example of wash after sample application.

3. Maintenance

Regeneration

After each step, elute any reversibly bound material with low pH (e.g., 0.1 M acetate, pH 3.0). Regenerate the medium by washing until the column effluent shows stable conductivity and pH values. Recommended flow rate: 3.8 ml/min (600 cm/h) for HiTrap 1 ml and 20 ml/min for HiTrap 5 ml.

Cleaning-in-place

Cleaning-in-place (CIP) is recommended after each cycle. A standard protocol for CIP is to wash with 1 M NaOH using a contact time of 15 minutes. Recommended flow rate: 1 ml/min (150 cm/h) for HiTrap 1 ml and 5 ml/min for HiTrap 5 ml.

For further information about CIP, see instruction for Capto adhere (28-9064-05)

Re-equilibration

At the end of each purification cycle, and after regeneration and cleaning-in-place, the column should be re-equilibrated with 5 bed volumes of loading buffer, or until the column effluent shows stable conductivity and pH values. Recommended flow rate: 3.8 ml/min (600 cm/h) for HiTrap 1 ml and 20 ml/min for HiTrap 5 ml.

Storage

Wash with 2 column volumes of distilled water followed by 2 column volumes of 20% ethanol. Store at +4 to +30°C.

Do not freeze. Ensure that the column is sealed well to avoid drying out.

After storage, equilibrate with at least 5 column volumes start buffer before use.

4. Ordering information

Product	Pack size	Code No
HiTrap Capto adhere	5 x 1 ml	28-4058-44
HiTrap Capto adhere	5 x 5 ml	28-4058-46

Related products

Product	Pack size	Code No
Capto adhere	25 ml	17-5444-10
Capto adhere	100 ml	17-5444-01
HiTrap MabSelect	5 x 1 ml	28-4082-53
HiTrap MabSelect	5 x 5 ml	28-4082-56
HiTrap MabSelect SuRe	5 x 1 ml	11-0034-93
HiTrap MabSelect SuRe	5x5 ml	11-0034-95
HiTrap MabSelect Xtra™	5 x 1 ml	28-4082-58
HiTrap MabSelect Xtra	5 x 5 ml	28-4082-56
HiPrep 26/10 Desalting	1 x 53 ml	17-5087-01
HiPrep 26/10 Desalting	4 x 53 ml	17-5087-02

Accessories

Product	Pack size	Code No.
1/16" male/luer female	2	18-1112-51
Union luerlock female/M6 female	2	18-1027-12
Union 1/16" female/M6 male	6	18-1112-57
Tubing connector flangless/M6 male	2	18-1017-98
Tubing connector flangless/M6 female	2	18-1003-68
Union M6 female/1/16" male	5	18-3858-01
Stop plug female, 1/16"	5	11-0004-64
Fingertight stop plug, 1/16"	5	11-0003-55

Literature

Product	Code No
Data file Capto adhere	28-9078-88
Application note: Optimization of loading conditions on Capto adhere using design of experiments	28-9078-89
Application note: Two step purification of monoclonal IgG1 from CHO cell supernatant	28-9078-92
Application note: Selective removal of aggregates with Capto adhere	28-9078-93

5. Further information

For the latest news, more product information and our handbooks, visit:

www.gehealthcare.com/protein-purification

www.gehealthcare.com/hitrap

www.gehealthcare.com

GE Healthcare Bio-Sciences AB
Björkgatan 30
751 84 Uppsala
Sweden

GE Healthcare Europe GmbH
Munzinger Strasse 5
D-79111 Freiburg
Germany

GE Healthcare UK Ltd
Amersham Place
Little Chalfont
Buckinghamshire, HP7 9NA
UK

GE Healthcare Bio-Sciences Corp
800 Centennial Avenue
P.O. Box 1327
Piscataway, NJ 08855-1327
USA

GE Healthcare Bio-Sciences KK
Sanken Bldg.
3-25-1, Hyakunincho
Shinjuku-ku, Tokyo 169-0073
Japan

Capto, BioProcess, MabSelect, MabSelect Xtra, HiTrap, ÄKTA design, FPLC, HiPrep, MabSelect SuRe and Superdex are trademarks of GE Healthcare companies. GE, imagination at work, and GE monogram are trademarks of General Electric Company.

All goods and services are sold subject to the terms and conditions of sale of the company within GE Healthcare which supplies them. GE Healthcare reserves the right, subject to any regulatory and contractual approval, if required, to make changes in specifications and features shown herein, or discontinue the product described at any time without notice or obligation. Contact your local GE Healthcare representative for the most current information.

© 2006 General Electric Company – All rights reserved.

GE Healthcare Bio-Sciences AB, a General Electric Company.



imagination at work