Technical data sheet

stericlin® Seal Seam Integrity Test “Liquid Control” 3FSZB830104

Article-no.: 3FSZB830104	Revision No.: 2
Date: 05.02.2024	Page: 1 of 1

Field of application:	For use in see-through packaging made of Tyvek® and film The sealed seam integrity test shows channels and defects in sealing seams quickly and reliably.
Material:	- Polyester metallisiert - Polyethylen
Size:	Wide of reel: 45 mm
Sterilisation suitability:	n/a
Technical data:	weight 62 g/m² colour ink: red
Print / indicator:	Print: 1-colour black Indicator: n/a
Standards/Normes:	DIN EN ISO 11607
Shipping unit:	Contents can: 30 pieces rolled an perforated + directions vor use can labeld with stericlin® label
Shelf life:	If stored under proper conditions from date of manufacture 2 years. Store dark, protect from sunlight and keep dry. Temperature: +15°C - +25°C Relative air humidity 35 % - 50 %
Substances:	Our product does not contain natural latex, PVC, Bisphenol A, Colophony, TSE/BSE risk materials, SVHC Substances and Phthalates as part of the formulations. We confirm, that the concentration at lead, mercurial, cadmium, chromate (VI) in products, packaging or packaging components does not exceed the value of 100 ppm by weight.

Technical data is submitted to the usual variations of operating procedures. Therefore it is not compulsory and does not exempt from validation and operating tests.