TECHNICAL DATA SHEET

BRANDON XXTM black Mid ESD S3S No. 760501 Sz. 36 - 48







LABELLING ACCORDING TO STANDARD

Standard for safety footwear EN ISO 20345:2022 S3S	Basic requirement for S3S: **A** Antistatic shoe - **E** Energy absorption in the heel - **WPA** Water penetration and absorption - **S** Textile penetration protection - Closed heel area - Basic Slip resistance test on ceramic tile + NaLS (soap solution) - Profiled outsole
Additional requirements	**FO** FUEL RESISTANCE **SR** SLIP RESISTANCE on ceramic tile with glycerine.

FORM

Safety laced boot 	Form B - in size 42, the upper height must be at least 11.3 cm.

AREAS OF APPLICATION

Areas of application	Areas where there is a risk of electrostatic discharge (ESDS/ESD) Workplaces on hard Undergrounds: The revolutionary Infinergy® sole core cushions impacts and provides for a rebound effect when the compressive impulse subsides - for more energy in every step.

FEATURES

ESD equipment	Thanks to its excellent discharge capability, the shoe is suitable for work in ESD sensitive or electrostatically protected areas (EPA). The shoes comply to the standard 61340-5-1.
Sizes (unisex model)	• Expanded size range: available in sizes 36 - 48
Certification in accordance with DGUV rule 112-191	• Certified for orthopaedic inserts

FEATURES	
Padded upper edge	• Excellent wearing comfort: the padded upper edge protects the Achilles tendon.
Full, padded bellows tongue	• Excellent wearing comfort: The tongue prevents pressure marks and avoids dirt from entering into the shoe.
Leather-free equipment	• Suitable for persons allergic to leather
UPPER MATERIAL	
Hydrophobized microfibre	• Areas of application S2/S3 • Synthetic material • Particularly soft • Retains its shape • Tear-resistant • Dries quickly • Abrasion-resistant and light • Water penetration and absorption in accordance with EN ISO 20345 S2; an improved resistance against water penetration is achieved by a special hydrophobation of the material
LINING	
Breathable fabric lining	• Climate-regulating • Good ventilation • Skin-friendly • High absorption and emission of moisture
Heel pocket lining	• The abrasion-resistant microfibre material is particularly sturdy and provides for a pleasant wearing comfort.
TOE PROTECTION CAP	
Composite toe cap 	• Protection against impacts of min. 200 joules and pressure loading of min. 15 kN • Permanent edge coverage for cushioning • Ergonomically shaped • Comfortable toe room • Good coverage of the little toe area • Low weight - weighs less than conventional steel caps • 100% metal-free • 100% anti-magnetic
INLAY SOLE	
PENETRATION RESISTANCE	
Metal-free penetration protection	The textile midsole complies with the penetration safety standard EN 12568 and furthermore fulfils the additional requirements for penetration protection in accordance with EN ISO 20344 / 20345. The light and flexible material enables an increased elasticity of the shoe, which can particularly be recognized when working on uneven grounds or on your knees. The textile variant offers 100 % foot coverage compared to steel midsoles (foot coverage 85 % due to limits in the shoe manufacturing process). Being 100 % metal-free and antimagnetic, this equipment is used as penetration protection in safety shoes.

OUTSOLE

WELLMAXX TRAINERS MONO mono-density sole with profile  	• Excellent slip resistance • Antistatic
	Outsole: PU (polyurethane) • Colour: black • Profile depth: 3.5 mm • Abrasion-resistant • Heat-resistant to approx. 130°C • Flexible at cold temperatures to approx. -20°C • Notch-resistant • Oil and fuel resistant • The core made of Infinergy® provides a very good cushioning with rebound effect