TECHNICAL DATA SHEET

jo_TWIST BOA® Low S1P No. 12761 Sz. 38 - 48







LABELLING ACCORDING TO STANDARD

Standard for safety footwear EN ISO 20345 S1P	Basic requirement for S1P: **A** Antistatic shoe - **E** Energy absorption in the heel - **FO** Fuel resistance - **P** Penetration resistance - Closed heel area
Additional requirements	**SRC** Slip resistance: Slip resistant on floors of ceramic tiles with a sodium lauryl sulfate (SLS) solution and on steel floors with glycerol. When it comes to slip resistance as defined by EN ISO 20345, SRC signifies the best possible rating a safety shoe can reach.

FORM

Safety shoe 	Form A - in size 42, the upper height must not exceed 11.2 cm.

AREAS OF APPLICATION

Areas of application	Dry work areas Industry, storage, transport, assembly etc. Areas where there is a risk of penetration from pointed and sharp objects (S1P)

FEATURES

Sizes (unisex model)	• Expanded size range: available in sizes 38 - 48
Padded upper edge	• Excellent wearing comfort: the padded upper edge protects the Achilles tendon.
Padded tongue	• Excellent wearing comfort: The tongue prevents pressure marks.
Heel loop	• Quicker into the shoe: The heel loop makes it easier to get inside the shoe
BOA® closure system	Quick and practical: The shoe comes without laces, buckles or velcros, and can be opened / closed with just one hand. BOA®

UPPER MATERIAL	
Hydrophobized nubuck leather	• Areas of application S2/S3 • Natural material • Wear-resistant • Breathable • Water penetration/absorption in accordance with EN ISO 20345 S2 • By hydrophobation, higher resistance against water penetration and water absorption
Textile material	• Areas of application S1 • Synthetic material • Retains its shape • Tear-resistant • Quick drying • Abrasion resistant and light
LINING	
Breathable fabric lining	• Climate-regulating • Good ventilation • Skin-friendly • High absorption and emission of moisture
Heel pocket lining	• The abrasion-resistant microfibre material is particularly sturdy and provides for a pleasant wearing comfort.
TOE PROTECTION CAP	
Composite toe cap 	• Protection against impacts of min. 200 joules and pressure loading of min. 15 kN • Permanent edge coverage for cushioning • Ergonomically shaped • Comfortable toe room • Good coverage of the little toe area • Low weight - weighs less than conventional steel caps • 100% metal-free • 100% anti-magnetic COMPOSITE TOE CAP
INLAY SOLE	
Full-length inlay sole JORI 	• The full-length, exchangeable inlay sole provides the highest possible comfort in safety shoes. • The inlay sole is functionally absorbing and releasing moisture and thus provides for a pleasant foot climate. • Antistatic

PENETRATION RESISTANCE	
Metal-free penetration protection	The textile midsole complies with the penetration safety standard EN 12568 and furthermore fulfils the additional requirements for penetration protection in accordance with EN ISO 20344 / 20345. The light and flexible material enables an increased elasticity of the shoe, which can particularly be recognized when working on uneven grounds or on your knees. Thanks to its thermo-insulating effect, it also keeps the foot dry and warm. The textile variant offers 100 % foot coverage compared to steel midsoles (foot coverage 85 % due to limits in the shoe manufacturing process). Being 100 % metal-free and antimagnetic, this equipment is used as penetration protection in safety shoes.
OUTSOLE	
jo_TWIST double-density sole with profile  	• Excellent slip resistance • Antistatic
	Outsole: PU (polyurethane) • Colour: lightgrey • Profile depth: 3.0 mm • Particularly abrasion-resistant • Heat-resistant to approx. 130°C • Flexible at cold temperatures to approx. -20°C • Oil and fuel resistant
	Midsole: PU (polyurethane) • The soft PU core provides a good impact absorption and high wearing comfort