

Product Name:	NSWDR231SSS/0
Description:	<p>Corepoint Scientific™ White Diamond Series Laboratory and Medical Stainless Steel Refrigerator 23 Cu. Ft. capacity  One swing solid door, self-closing, right hinged, not reversible  5 ea. Adjustable Shelves  Microprocessor temperature controller  Touch Screen Digital Temperature Display with user friendly interface  Alarm Module with battery back-up to support temperature monitoring and alarms  Password-protected control panel  C°/F° switchable  0.1° resolution  Adjustable operating temperature: 1°C to 10°C (34°F to 50°F)  Active temperature scale bar display  Resettable 1-point min/max history  Digital 24-hour temperature chart  Temperature data logging  USB port for data transfer and software updates  Real-time operational display clock  4-20mA output  Adjustable alarm volume  Audible and visual high/low temperature alarms  2 probes; 1 in air and 1 in sample bottle  Continuous product (simulated) temperature display  Sensor error alarm  Power failure alarm  Door ajar alarm  Low battery alarm  Alarm validation (audible, visual, and remote alarm)  Alarm mute with ring back  Remote alarm contacts  Customizable alarm time delay settings  Forced draft air circulation  Keyed door lock  Magnetic door gaskets for positive seal  Integrated door handle  LED interior lights are safety shielded and switch controlled  Probe access port (3/4")  Stainless steel exterior  White-powder coated aluminum interior with 304 stainless steel floor  Easily cleaned smooth interior  Hydrocarbon natural refrigerant (R290)  Three year parts and labor warranty, plus an additional two year compressor parts warranty  4 swivel casters (5 3/4")  Exterior dimensions: 26 7/8" W x 33 3/4" D x 83 1/4" H with casters; 77 1/2" H without casters  Cycle defrost  115V, 60 Hz, 3 Amps, 1/5 HP  ETL listed  Shipping weight: 311 lbs.</p>