

# SAFETY DATA SHEET

Creation Date 29-Nov-2014 Revision Date 29-Nov-2014 Revision Number 1

### 1. Identification

Product Name Fix-Rite II

Cat No.: 76150, S76150, 76155

Synonyms No information available

Recommended Use Laboratory chemicals.

Uses advised against No Information available

Details of the supplier of the safety data sheet

Company

Richard Állan Scientific A Subsidiary of Thermo Fisher Scientific

4481 Campus Drive Kalamazoo, MI 49008 Tel: (800) 522-7270 Emergency Telephone Number Chemtrec US: (800) 424-9300

Chemtrec US: (800) 424-9300 Chemtrec EU: 001 (202) 483-7616

# 2. Hazard(s) identification

#### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids

Serious Eye Damage/Eye Irritation

Category 2
Specific target organ toxicity (single exposure)

Category 3

Target Organs - Central nervous system (CNS).

Specific target organ toxicity - (repeated exposure) Category 2

Target Organs - Kidney, Liver.

### Label Elements

### Signal Word

Danger

## **Hazard Statements**

Highly flammable liquid and vapor Causes serious eye irritation May cause drowsiness or dizziness May cause damage to organs through prolonged or repeated exposure



#### **Precautionary Statements**

#### Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

#### Response

Get medical attention/advice if you feel unwell

### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

#### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

#### **Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

#### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

#### Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

### **Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Repeated exposure may cause skin dryness or cracking

# 3. Composition / information on ingredients

Component	CAS-No	Weight %
Acetone	67-64-1	20-25
Polyethylene glycol	25322-68-3	1 - 2
Isopropyl alcohol	67-63-0	80-83
Water	7732-18-5	1 - 2

### 4. First-aid measures

General Advice If symptoms persist, call a physician. Show this safety data sheet to the doctor in

attendance.

**Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Obtain medical attention. Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while

rinsing. If symptoms persist, call a physician.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Obtain medical attention.

If skin irritation persists, call a physician. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a

physician.

**Inhalation** Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth

resuscitation if victim ingested or inhaled the substance; induce artificial respiration with a respiratory medical device. Obtain medical attention. Immediate medical attention is not required. Move to fresh air in case of accidental inhalation of vapors. If symptoms persist,

call a physician.

Ingestion Do not induce vomiting. Obtain medical attention. Clean mouth with water and drink

afterwards plenty of water. Do not induce vomiting without medical advice. Never give

anything by mouth to an unconscious person. Consult a physician.

Most important symptoms/effects Breathing difficulties. Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting

Notes to Physician Treat symptomatically

## 5. Fire-fighting measures

Suitable Extinguishing Media CO 2, dry chemical, dry sand, alcohol-resistant foam. Cool closed containers exposed to fire

with water spray.

Unsuitable Extinguishing Media Water may be ineffective

**Flash Point** 12.2 °C / 54 °F

Method - No information available

**Autoignition Temperature** 

**Explosion Limits** 

No information available

**Upper** 12.0 vol % **Lower** 2.5 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

### **Specific Hazards Arising from the Chemical**

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated or if contaminated with water. Keep product and empty container away from heat and sources of ignition.

### **Hazardous Combustion Products**

**Environmental Precautions** 

Carbon monoxide (CO) Carbon dioxide (CO2) peroxides

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

**NFPA** 

Health	Flammability	Instability	Physical hazards
2	3	0	N/A

#### 6. Accidental release measures

Personal Precautions Use personal protective equipment. Remove all sources of ignition. Take precautionary

measures against static discharges. Avoid contact with skin, eyes and clothing. Evacuate

personnel to safe areas. Keep people away from and upwind of spill/leak.

Should not be released into the environment. See Section 12 for additional ecological information. Do not flush into surface water or sanitary sewer system. Prevent further

leakage or spillage if safe to do so. Prevent product from entering drains.

**Methods for Containment and Clean** Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary **Up** measures against static discharges. Keep in suitable, closed containers for disposal.

# 7. Handling and storage

Revision Date 29-Nov-2014 Fix-Rite II

Handling Wear personal protective equipment. Keep away from open flames, hot surfaces and

sources of ignition. Take precautionary measures against static discharges. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing. Do not ingest. Pay

attention to flashback. No information available. Do not take internally.

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat Storage

and sources of ignition. Flammables area. Keep containers tightly closed in a cool,

well-ventilated place. Keep in properly labeled containers.

## 8. Exposure controls / personal protection

#### **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	TWA: 500 ppm	(Vacated) TWA: 750 ppm	IDLH: 2500 ppm
	STEL: 750 ppm	(Vacated) TWA: 1800 mg/m <sup>3</sup>	TWA: 250 ppm
		(Vacated) STEL: 2400 mg/m <sup>3</sup>	TWA: 590 mg/m <sup>3</sup>
		(Vacated) STEL: 1000 ppm	_
		TWA: 1000 ppm	
		TWA: 2400 mg/m <sup>3</sup>	
Isopropyl alcohol	TWA: 200 ppm	(Vacated) TWA: 400 ppm	IDLH: 2000 ppm
	STEL: 400 ppm	(Vacated) TWA: 980 mg/m <sup>3</sup>	TWA: 400 ppm
		(Vacated) STEL: 500 ppm	TWA: 980 mg/m <sup>3</sup>
		(Vacated) STEL: 1225 mg/m <sup>3</sup>	STEL: 500 ppm
		TWA: 400 ppm	STEL: 1225 mg/m <sup>3</sup>
		TWA: 980 mg/m <sup>3</sup>	_

Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV
Acetone	TWA: 500 ppm	TWA: 1000 ppm	TWA: 500 ppm
	TWA: 1190 mg/m <sup>3</sup>	TWA: 2400 mg/m <sup>3</sup>	STEL: 750 ppm
	STEL: 1000 ppm	STEL: 1260 ppm	
	STEL: 2380 mg/m <sup>3</sup>	STEL: 3000 mg/m <sup>3</sup>	
Isopropyl alcohol	TWA: 400 ppm	TWA: 400 ppm	TWA: 200 ppm
	TWA: 985 mg/m <sup>3</sup>	TWA: 980 mg/m <sup>3</sup>	STEL: 400 ppm
	STEL: 500 ppm	STEL: 500 ppm	
	STEL: 1230 mg/m <sup>3</sup>	STEL: 1225 mg/m <sup>3</sup>	

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

**Engineering Measures** Ensure adequate ventilation, especially in confined areas. Use explosion-proof

electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers

are close to the workstation location.

Personal Protective Equipment

**Hygiene Measures** 

Eye/face Protection Skin and body protection **Respiratory Protection** 

Tightly fitting safety goggles. Face-shield. Long sleeved clothing. Apron. Impervious gloves.

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if

exposure limits are exceeded or if irritation or other symptoms are experienced.

When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area

and clothing.

# 9. Physical and chemical properties

**Physical State** Liquid Clear Colorless **Appearance** pungent

Odor **Odor Threshold** No information available No information available pН

**Melting Point/Range** No data available

**Boiling Point/Range** 56.1 - 82 °C / 133 - 179.6 °F

Flash Point 12.2 °C / 54 °F
Evaporation Rate No information available
Flammability (solid,gas) No information available

Flammability or explosive limits

 Upper
 12.0 vol %

 Lower
 2.5 vol %

Vapor PressureNo information availableVapor DensityNo information availableRelative DensityNo information availableSolubilitySoluble in water

Partition coefficient; n-octanol/water

Autoignition Temperature

Decomposition Temperature

Viscosity

No data available
No information available
No information available
No information available

## 10. Stability and reactivity

Reactive Hazard None known, based on information available

**Stability** Stable under normal conditions.

Conditions to Avoid Incompatible products. Heat, flames and sparks.

Incompatible Materials Strong oxidizing agents, Strong reducing agents, Strong acids, Metals

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), peroxides

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

## 11. Toxicological information

**Acute Toxicity** 

**Product Information**No acute toxicity information is available for this product

Oral LD50Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.Dermal LD50Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.Vapor LC50Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

**Component Information** 

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Acetone	5800 mg/kg (Rat)	> 15800 mg/kg (rabbit)	76 mg/l, 4 h, (rat)
		> 7400 mg/kg (rat)	
Polyethylene glycol	Not listed	20 mL/kg (Rabbit)	Not listed
Isopropyl alcohol	, , ,		72.6 mg/L (Rat)4 h

Toxicologically Synergistic

No information available

**Products** 

Delayed and immediate effects as well as chronic effects from short and long-term exposure

 Irritation
 Irritating to eyes and skin

 Sensitization
 No information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Acetone	67-64-1	Not listed	Not listed	Not listed	Not listed	Not listed
Polyethylene glycol	25322-68-3	322-68-3 Not listed		Not listed	Not listed	Not listed
Isopropyl alcohol	67-63-0	Not listed	Not listed	Not listed	Not listed	Not listed
Water	7732-18-5	Not listed	Not listed	Not listed	Not listed	Not listed

IARC: (International Agency for Research on Cancer) IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

**Mutagenic Effects** No information available

Experiments have shown reproductive toxicity effects on laboratory animals. **Reproductive Effects** 

**Developmental Effects** Developmental effects have occurred in experimental animals.

**Teratogenicity** Teratogenic effects have occurred in experimental animals.

Central nervous system (CNS) STOT - single exposure

STOT - repeated exposure Kidney Liver

**Aspiration hazard** No information available

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting

**Endocrine Disruptor Information** No information available

**Other Adverse Effects** See actual entry in RTECS for complete information.

# 12. Ecological information

### **Ecotoxicity**

Do not empty into drains.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Acetone	NOEC = 430 mg/l (algae; 96	Oncorhynchus mykiss: LC50	EC50 = 14500 mg/L/15 min	EC50 = 8800 mg/L/48h
	h)	= 5540 mg/l 96h		EC50 = 12700 mg/L/48h
		Alburnus alburnus: LC50 =		EC50 = 12600  mg/L/48h
		11000 mg/l 96h		_
		Leuciscus idus: LC50 =		
		11300 mg/L/48h		
		Salmo gairdneri: LC50 =		
		6100 mg/L/24h		
Polyethylene glycol	Not listed	LC50 = 10 g/L/96h	Not listed	Not listed
Isopropyl alcohol	1000 mg/L EC50 > 72 h	1400000 μg/L LC50 96 h	= 35390 mg/L EC50	13299 mg/L EC50 = 48 h
	1000 mg/L EC50 > 96 h	11130 mg/L LC50 96 h 9640	Photobacterium	9714 mg/L EC50 = 24 h
		mg/L LC50 96 h	phosphoreum 5 min	_

Persistence and Degradability No information available

**Bioaccumulation/ Accumulation** No information available.

Mobility

Component	log Pow
Acetone	-0.24
Isopropyl alcohol	0.05

## 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Acetone - 67-64-1	U002	-

## 14. Transport information

DOT

**UN-No** UN1993

Proper Shipping Name FLAMMABLE LIQUID, N.O.S. Proper technical name (ISOPROPANOL, ACETONE)

Hazard Class 3
Packing Group ||

**TDG** 

**UN-No** UN1993

Proper Shipping Name FLAMMABLE LIQUID, N.O.S.

Hazard Class 3
Packing Group ||

IATA

**UN-No** UN1993

Proper Shipping Name FLAMMABLE LIQUID, N.O.S.

Hazard Class 3
Packing Group

IMDG/IMO

UN-No UN1993

Proper Shipping Name FLAMMABLE LIQUID, N.O.S.

Hazard Class 3
Packing Group ||

# 15. Regulatory information

All of the components in the product are on the following Inventory lists: Australia X = listed China Canada The product is classified and labeled according to EC directives or corresponding national laws The product is classified and labeled in accordance with Directive 1999/45/EC Europe TSCA Korea Philippines

#### **International Inventories**

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Acetone	Х	Х	-	200-662-2	-		Χ	Χ	Х	Х	Χ
Polyethylene glycol	X	X	-	-	-	>1<4.5 mol ethoxyl ated units, consist ing of 50% w/w or more of specie s of the same molecu lar weight		Х	X	X	X
Isopropyl alcohol	X	Χ	-	200-661-7			Χ	Χ	Χ	X	Х
Water	X	Х	-	231-791-2	-		Χ	-	Χ	Х	Χ

#### Legend:

- X Listed
- E Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

#### U.S. Federal Regulations

TSCA 12(b) Not applicable

#### **SARA 313**

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Isopropyl alcohol	67-63-0	80-83	1.0

### SARA 311/312 Hazardous Categorization

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes
Sudden Release of Pressure Hazard No
Reactive Hazard No

Clean Water Act Not applicable

Clean Air Act Not applicable

**OSHA** Occupational Safety and Health Administration

Not applicable

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Acetone	5000 lb	-

**California Proposition 65** 

This product does not contain any Proposition 65 chemicals

## State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Acetone	X	X	X	-	X
Isopropyl alcohol	X	X	X	-	X

## **U.S. Department of Transportation**

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

### **U.S. Department of Homeland Security**

This product contains the following DHS chemicals:

Component	DHS Chemical Facility Anti-Terrorism Standard		
Acetone	2000 lb STQ		

#### **Other International Regulations**

Mexico - Grade Serious risk, Grade 3

#### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

#### **WHMIS Hazard Class**

B2 Flammable liquid D2B Toxic materials



## 16. Other information

Prepared By Regulatory Affairs

Richard Allan Scientific

A Subsidiary of Thermo Fisher Scientific

Tel: (800) 522-7270

 Creation Date
 29-Nov-2014

 Revision Date
 29-Nov-2014

 Print Date
 29-Nov-2014

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS)

#### **Disclaimer**

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of SDS**