Description: Corepoint Scientific™ General Purpose Stainless Steel Refriger   49 Cu. Ft. capacity Two swing solid doors, self-closing, not reversible   6 ea. Adjustable Shelves Digital display microprocessor temperature controller	
49 Cu. Ft. capacity Two swing solid doors, self-closing, not reversible 6 ea. Adjustable Shelves	
Adjustable operating temperature: 1°C to 10°C (34°F to 50°F) Audible and visual Hi/Lo temperature alarm 2 probes; 1 in air and 1 in sample bottle Sensor error alarm Continuous product (simulated) temperature display Remote alarm contacts Forced draft air circulation Keyed door locks Magnetic door gaskets for positive seal Integrated door handle LED interior lights are safety shielded and switch controlled Probe access port (3/4") Stainless steel exterior White-powder coated aluminum interior with 304 stainless steel Easily cleaned smooth interior Hydrocarbon natural refrigerant (R290) 2 year parts and labor warranty, plus an additional 3 year compressor parts warranty 4 swivel casters (5 3/4") Exterior dimensions: 54" W x 33 <sup>3</sup> /4" D x 83 1/4" H with casters; 1 1/2" H without casters Cycle defrost 115V, 60 Hz, 4.5 Amps, 1/4 HP ETL listed Shipping weight: 479 lbs.	floor