

# Tetrahydrofuran UV

340-4

Version 1.6 Revision Date 06/05/2018 Print Date 10/17/2019

### **SECTION 1. IDENTIFICATION**

Product name Tetrahydrofuran UV

Number 000000011440

**Product Use Description** Solvent

Manufacturer or supplier's

details

Honeywell International Inc. 1953 South Harvey Street Muskegon, MI 49442

For more information call 1-800-368-0050

+1-231-726-3171

(Monday-Friday, 9:00am-5:00pm)

In case of emergency call Medical: 1-800-498-5701 or +1-303-389-1414

Transportation (CHEMTREC): 1-800-424-9300 or

+1-703-527-3887

(24 hours/day, 7 days/week)

#### SECTION 2. HAZARDS IDENTIFICATION

### **Emergency Overview**

Form : liquid

Color : clear and colourless

Odor : ether-like

### Classification of the substance or mixture

or mixture

Classification of the substance : Flammable liquids, Category 2 Acute toxicity, Category 4, Oral

Eye irritation, Category 2A Carcinogenicity, Category 2

Specific target organ toxicity - single exposure, Category 3,

Page 1 / 14



# Tetrahydrofuran UV

## 340-4

Version 1.6 Revision Date 06/05/2018 Print Date 10/17/2019

Respiratory system

### GHS Label elements, including precautionary statements

Symbol(s) :







Signal word : Danger

Hazard statements : Highly flammable liquid and vapour.

Harmful if swallowed.

Causes serious eye irritation. May cause respiratory irritation. Suspected of causing cancer.

Precautionary statements : Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and

understood.

Keep away from heat/sparks/open flames/hot surfaces. No

smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/ eye protection/ face protection.

#### Response:

IF SWALLOWED: Call a POISON CENTER/doctor if you feel

IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF INHALED: Remove victim to fresh air and keep at rest in a

position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rınsıng.

IF exposed or concerned: Get medical advice/ attention.

Rinse mouth.



# Tetrahydrofuran UV

## 340-4

Version 1.6 Revision Date 06/05/2018 Print Date 10/17/2019

If eye irritation persists: Get medical advice/ attention.

In case of fire: Use dry sand, dry chemical or alcohol-resistant

foam for extinction.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Keep cool. Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

## Carcinogenicity

ACGIH: Tetrahydrofuran 109-99-9

A3: Confirmed animal carcinogen

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Formula : C4H8O

Chemical nature : Substance

Chemical name	CAS-No.	Concentration
Tetrahydrofuran	109-99-9	100.00 %

### **SECTION 4. FIRST AID MEASURES**

General advice : If unconscious, place in recovery position and seek medical

advice.

Inhalation : Remove to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is present. Call a physician.

Skin contact : Wash off immediately with plenty of water for at least 15

minutes. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use. Call a physician.

Page 3 / 14



## Tetrahydrofuran UV

340-4

Version 1.6 Revision Date 06/05/2018 Print Date 10/17/2019

Eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Protect unharmed eye. Call a physician.

Ingestion : Do not induce vomiting without medical advice. Never give

anything by mouth to an unconscious person. Call a physician.

Notes to physician

Indication of immediate medical attention and special treatment needed, if

necessary

: Treat symptomatically.

#### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Foam

Carbon dioxide (CO2)

Dry powder

Unsuitable extinguishing

media

: Do not use a solid water stream as it may scatter and spread

fire

Specific hazards during

firefighting

: Extremely flammable.

Vapours may form explosive mixtures with air.

Vapours are heavier than air and may spread along floors. Vapors may travel to areas away from work site before

igniting/flashing back to vapor source.

May form explosive peroxides.

In case of fire hazardous decomposition products may be

produced such as: Carbon monoxide Carbon dioxide (CO2)

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus and protective suit.

Further information : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, : Wear personal protective equipment.

Page 4 / 14



# Tetrahydrofuran UV

## 340-4

Version 1.6 Revision Date 06/05/2018 Print Date 10/17/2019

protective equipment and emergency procedures

Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Ensure adequate ventilation. Remove all sources of ignition.

Do not swallow.

Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing.

**Environmental precautions** 

Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Discharge into the environment must be avoided.

Do not flush into surface water or sanitary sewer system. Do not allow run-off from fire fighting to enter drains or water

courses.

Methods and materials for containment and cleaning

Ventilate the area.

No sparking tools should be used. Use explosion-proof equipment.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national

regulations (see section 13).

#### **SECTION 7. HANDLING AND STORAGE**

#### Handling

Precautions for safe

handling

: Wear personal protective equipment.

Use only in well-ventilated areas. Keep container tightly closed.

Do not smoke.

Do not swallow.

Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing.

Advice on protection against :

fire and explosion

May form explosive peroxides.

Keep away from fire, sparks and heated surfaces.

Take precautionary measures against static discharges.

Ensure all equipment is electrically grounded before beginning

transfer operations.

Use explosion-proof equipment.

Keep product and empty container away from heat and sources

of ignition.

No sparking tools should be used.

No smoking.



# Tetrahydrofuran UV

340-4

Version 1.6 Revision Date 06/05/2018 Print Date 10/17/2019

**Storage** 

Conditions for safe storage,

including any incompatibilities

Store in area designed for storage of flammable liquids. Protect

from physical damage.

Keep containers tightly closed in a dry, cool and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep away from heat and sources of ignition.

Keep away from direct sunlight.

Protect from exposure to air/oxygen (peroxide formation).

Protect against light.

Store away from incompatible substances.

Container hazardous when empty.

Do not pressurize, cut, weld, braze, solder, drill, grind or expose

containers to heat or sources of ignition.

Further information on storage conditions

Keep containers tightly closed in a dry, cool and well-ventilated

place.

Keep under nitrogen.

Protect from exposure to air/oxygen (peroxide formation).

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Ensure that eyewash stations and safety showers are close to

the workstation location.

Engineering measures : Use with local exhaust ventilation.

Prevent vapour buildup by providing adequate ventilation during

and after use.

Eye protection : Do not wear contact lenses.

Wear as appropriate:

Safety glasses with side-shields
If splashes are likely to occur, wear:

Goggles or face shield, giving complete protection to eyes

Hand protection : Solvent-resistant gloves

Gloves must be inspected prior to use.

Replace when worn.

Skin and body protection : Wear as appropriate:

Solvent-resistant apron

Flame retardant antistatic protective clothing.

If splashes are likely to occur, wear:

Page 6 / 14



# Tetrahydrofuran UV

## 340-4

Version 1.6 Revision Date 06/05/2018 Print Date 10/17/2019

Protective suit

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory

equipment.

For rescue and maintenance work in storage tanks use

self-contained breathing apparatus.

Use NIOSH approved respiratory protection.

Hygiene measures : When using, do not eat, drink or smoke.

Wash hands before breaks and immediately after handling the

product.

Keep working clothes separately.

Remove and wash contaminated clothing before re-use.

Do not swallow.

Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing.

This material has an established AIHA ERPG exposure limit. The current list of ERPG exposure limits can be found at http://www.aiha.org/insideaiha/GuidelineDevelopment/ERPG/D

ocuments/2011erpgweelhandbook\_table-only.pdf.

**Exposure Guidelines** 

Components	CAS-No.	Value	Control parameters	Upda te	Basis
Tetrahydrofuran	109-99-9	SKIN_DE S : Skin designati on:	Can be absorbed through the skin.	2008	ACGIH:US. ACGIH Threshold Limit Values
Tetrahydrofuran	109-99-9	TWA : Time weighted average	(50 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values
Tetrahydrofuran	109-99-9	STEL : Short term exposure limit	(100 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values
Tetrahydrofuran	109-99-9	REL: Recomm ended exposure limit (REL):	590 mg/m3 (200 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards



# Tetrahydrofuran UV

# 340-4

Version 1.6 Revision Date 06/05/2018 Print Date 10/17/2019

Tetrahydrofuran	109-99-9	STEL: Short term exposure limit	735 mg/m3 (250 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards
Tetrahydrofuran	109-99-9	PEL: Permissi ble exposure limit	590 mg/m3 (200 ppm)	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
Tetrahydrofuran	109-99-9	STEL: Short term exposure limit	735 mg/m3 (250 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)
Tetrahydrofuran	109-99-9	TWA: Time weighted average	590 mg/m3 (200 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state : liquid

Color : clear and colourless

Odor : ether-like

pH : Note: Not applicable

Melting point/range : -108.5 °C

Boiling point/boiling range : 66 °C

Flash point : 7 °F (-14 °C)

Method: closed cup

Evaporation rate : 14.5

Page 8 / 14



# Tetrahydrofuran UV

## 340-4

Version 1.6 Revision Date 06/05/2018 Print Date 10/17/2019

Method: Compared to Butyl acetate.

Lower explosion limit : 2 %(V)

Upper explosion limit : 11.8 %(V)

Vapor pressure : 189 hPa

at 20 °C(68 °F)

Vapor density : 2.5 Note: (Air = 1.0)

Density : 0.8892 g/cm3 at 20 °C

Water solubility : Note: completely soluble

Partition coefficient:

n-octanol/water

: log Pow: 0.46 at 20 °C

Ignition temperature : 321 °C

Decomposition temperature : Note: At normal pressure may be distilled without

decomposition.

Molecular weight : 72.11 g/mol

#### **SECTION 10. STABILITY AND REACTIVITY**

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Hazardous polymerisation may occur.

Conditions to avoid : Heat, flames and sparks.

Keep away from direct sunlight.

Protect from exposure to air/oxygen (peroxide formation).

Page 9 / 14



# Tetrahydrofuran UV

340-4

Version 1.6 Revision Date 06/05/2018 Print Date 10/17/2019

Protect against light.

Incompatible materials : Strong oxidizing agents

Strong acids and strong bases May form explosive peroxides.

May attack many plastics, rubbers and coatings.

Hazardous decomposition

products

: Peroxides

In case of fire hazardous decomposition products may be

produced such as: Carbon monoxide Carbon dioxide (CO2)

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

Acute oral toxicity : LD50: 1,650 mg/kg

Species: Rat

Acute inhalation toxicity : LC50: 53.1 mg/l

Exposure time: 4 h Species: Rat

: LC50: 21000 ppm Exposure time: 3 h Species: Rat

Skin irritation : Species: Rabbit

Result: Mild skin irritation

Note: According to the classification criteria of the European Union, the product is not considered as being a skin irritant.

Eye irritation : Species: Rabbit

Result: Irritating to eyes.

Further information : Note: Confirmed animal carcinogen with unknown relevance to

humans.



# Tetrahydrofuran UV

## 340-4

Version 1.6 Revision Date 06/05/2018 Print Date 10/17/2019

### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity effects**

Toxicity to fish : LC50: 2,160 mg/l

Exposure time: 96 h

Species: Pimephales promelas (fathead minnow)

: LC50: 2,820 mg/l

Species: Leuciscus idus (Golden orfe)

Toxicity to bacteria : LC50: > 580 mg/l

Exposure time: 16 h Species: Bacteria

## Further information on ecology

Additional ecological

information

: Bioaccumulation is unlikely.

### **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods : Observe all Federal, State, and Local Environmental

regulations.

#### **SECTION 14. TRANSPORT INFORMATION**

**DOT** UN/ID No. : UN 2056

Proper shipping name : TETRAHYDROFURAN

Class 3
Packing group II
Hazard Labels 3

**IATA** UN/ID No. : UN 2056

Description of the goods : TETRAHYDROFURAN

Class : 3
Packaging group : II
Hazard Labels : 3
Packing instruction (cargo : 364

aircraft)

Page 11 / 14



# Tetrahydrofuran UV

## 340-4

Version 1.6 Revision Date 06/05/2018 Print Date 10/17/2019

Packing instruction : 353

(passenger aircraft)

Packing instruction : Y341

(passenger aircraft)

**IMDG** UN/ID No. : UN 2056

Description of the goods : TETRAHYDROFURAN

Class : 3 Packaging group : II Hazard Labels : 3

EmS Number : F-E, S-D Marine pollutant : no

### **SECTION 15. REGULATORY INFORMATION**

#### **Inventories**

US. Toxic Substances

Control Act

: On TSCA Inventory

Australia. Industrial

Chemical (Notification and

Assessment) Act

: On the inventory, or in compliance with the inventory  $% \left( x\right) =\left( x\right) ^{2}$ 

: All components of this product are on the Canadian DSL

Canada. Canadian Environmental Protection

Act (CEPA). Domestic Substances List (DSL)

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Existing Chemicals Inventory (KECI)

: On the inventory, or in compliance with the inventory

Philippines. The Toxic

Substances and Hazardous and Nuclear Waste Control

Act

: On the inventory, or in compliance with the inventory

China. Inventory of Existing

Chemical Substances

: On the inventory, or in compliance with the inventory

New Zealand. Inventory of

Chemicals (NZIoC), as published by ERMA New

. Zealand : On the inventory, or in compliance with the inventory



# Tetrahydrofuran UV

340-4

Version 1.6 Revision Date 06/05/2018 Print Date 10/17/2019

#### **National regulatory information**

US. EPA CERCLA

Hazardous Substances (40

CFR 302)

: The following component(s) of this product is/are subject to release reporting under 40 CFR 302 when release exceeds the

Reportable Quantity (RQ):

Reportable quantity: 1000 lbs

: Tetrahydrofuran 109-99-9

SARA 302 Components : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 Components : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard Chronic Health Hazard Reactivity Hazard

**CERCLA Reportable** 

Quantity

: 1000 lbs

California Prop. 65 : This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

Massachusetts RTK : Tetrahydrofuran 109-99-9

New Jersey RTK : Tetrahydrofuran 109-99-9

Pennsylvania RTK : Tetrahydrofuran 109-99-9

#### **SECTION 16. OTHER INFORMATION**

HMIS III NFPA

Health hazard : 2\* 2 Flammability : 3 3

Physical Hazard : 1

Page 13 / 14



# Tetrahydrofuran UV

340-4

Version 1.6 Revision Date 06/05/2018 Print Date 10/17/2019

Instability : 1

\* - Chronic health hazard

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

#### **Further information**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 04/14/2014

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group