

Bacterial Filtration Efficiency (BFE) Final Report

RightCare KN95 5-PLY DISPOSABLE FACE MASK REF#: RCKN95 / UPC: Test Article:

860002882352

Purchase Order: Q-155904-Z8Q4N5

Study Number: 1485862-S01 Study Received Date: 27 Jan 2022 Test Started Date: 31 Jan 2022 Test Finished Date: 08 Feb 2022

> Testing Facility: Nelson Laboratories, LLC

> > 6280 S. Redwood Rd.

Salt Lake City, UT 84123 U.S.A.

Standard Test Protocol (STP) Number: STP0004 Rev 19 Test Procedure(s):

Deviation(s):

Summary: The BFE test is performed to determine the filtration efficiency of test articles by comparing the bacterial counts upstream of the test article to the bacterial counts downstream. A suspension of Staphylococcus aureus was aerosolized using a nebulizer and delivered to the test article at a constant flow rate and fixed air pressure. The challenge delivery was maintained at 1.7 - 3.0 x 10³ colony forming units (CFU) with a mean particle size (MPS) of $3.0 \pm 0.3 \mu m$. The aerosols were drawn through a sixstage, viable particle, Andersen sampler for collection. This test method complies with ASTM F2101-19 and EN 14683:2019+AC:2019, Annex B.

All test method acceptance criteria were met. Testing was performed in compliance with US FDA good manufacturing practice (GMP) regulations 21 CFR Parts 210, 211 and 820.

Test Side: Inside

~40 cm² BFE Test Area:

BFE Flow Rate: 28.3 Liters per minute (L/min)

Conditioning Parameters: $85 \pm 5\%$ relative humidity (RH) and $21 \pm 5^{\circ}$ C for a minimum of 4 hours

Test Article Dimensions: ~210 mm x ~160 mm

2.7 x 10³ CFU Positive Control Average:

<1 CFU Negative Monitor Count:

> MPS: 3.1 µm





James Luskin electronically approved

Study Completion Date and Time

14 Feb 2022 19:58 (+00:00)

Study Director

James Luskin



Results:

Test Article Number	Percent BFE (%)
1	>99.9 ^a
2	>99.9
3	>99.9 ^a
4	>99.9 ^a
5	>99.9 ^a

^a There were no detected colonies on any of the Andersen sampler plates for this test article.

The filtration efficiency percentages were calculated using the following equation:

$$\% BFE = \frac{C-T}{C} \times 100$$

C = Positive control average

T = Plate count total recovered downstream of the test article Note: The plate count total is available upon request

wrh