

BC721-56 ACTIVATOR 0.25M ETT, 56L SSPDS

000000011308

Version 1.3

Revision Date 05/27/2014

Print Date 08/10/2016

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Activator 0.25M ETT

MSDS Number : 000000011308

Product Use Description : Pharmaceutical, Laboratory Use

Note : This sample is for research and development purposes only. The handling and use of this material must be supervised by qualified individuals. The chemical, physical and toxicological properties of this material have not been fully investigated. Use due precaution in handling, storage and disposal.

Manufacturer or supplier's details : Honeywell International Inc.
115 Tabor Road
Morris Plains, NJ 07950-2546

For more information call : 1-800-368-0050
+1-231-726-3171
(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701 or +1-303-389-1414
: **Transportation (CHEMTREC): 1-800-424-9300 or +1-703-527-3887**
:
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Form : liquid

Color : colourless

Odor : sweet ether-like

Classification of the substance or mixture

Classification of the : Flammable liquids, Category 2

BC721-56 ACTIVATOR 0.25M ETT, 56L SSPDS

000000011308

Version 1.3

Revision Date 05/27/2014

Print Date 08/10/2016

substance or mixture Eye irritation, Category 2A
 Specific target organ toxicity - single exposure, Category 1,
 Central nervous system, Respiratory system
 Specific target organ toxicity - repeated exposure, Category 2,
 Central nervous system, Respiratory system, Kidney, Blood,
 Liver

GHS Label elements, including precautionary statements

Symbol(s)



Signal word

: Danger

Hazard statements

: Highly flammable liquid and vapour.
 Causes serious eye irritation.
 Causes damage to organs.
 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

: **Prevention:**
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Keep container tightly closed.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
 Wash skin thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Wear protective gloves/ eye protection/ face protection.

Response:
 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF exposed: Call a POISON CENTER or doctor/ physician.
 If eye irritation persists: Get medical advice/ attention.
 In case of fire: Use dry sand, dry chemical or alcohol-resistant

BC721-56 ACTIVATOR 0.25M ETT, 56L SSPDS

000000011308

Version 1.3

Revision Date 05/27/2014

Print Date 08/10/2016

foam for extinction.

Storage:

Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture

Chemical Name	CAS-No.	Concentration
Acetonitrile	75-05-8	96.00 %
5-Ethylthio-1H-Tetrazole	89797-68-2	4.00 %

SECTION 4. FIRST AID MEASURES

Inhalation : Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is present. Call a physician.

Skin contact : Wash off immediately with plenty of water for at least 15 minutes. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use. Call a physician.

Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician.

BC721-56 ACTIVATOR 0.25M ETT, 56L SSPDS

000000011308

Version 1.3

Revision Date 05/27/2014

Print Date 08/10/2016

Ingestion : Call a physician. Do not induce vomiting without medical advice. Immediate medical attention is required. Never give anything by mouth to an unconscious person.

Notes to physician

Treatment : Treat as cyanide poisoning. Symptoms of poisoning may not appear for several hours. Keep under medical supervision for at least 48 hours.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Carbon dioxide (CO₂)
Dry chemical
Alcohol-resistant foam
Cool closed containers exposed to fire with water spray.

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

Specific hazards during firefighting : Flammable.
Vapours may form explosive mixtures with air.
Vapours are heavier than air and may spread along floors.
Vapors may travel to areas away from work site before igniting/flashing back to vapor source.
In case of fire hazardous decomposition products may be produced such as:
Hydrogen cyanide (hydrocyanic acid)
Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

Special protective equipment for firefighters : Wear self-contained breathing apparatus and protective suit.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear personal protective equipment.
Immediately evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Ensure adequate ventilation.

BC721-56 ACTIVATOR 0.25M ETT, 56L SSPDS

000000011308

Version 1.3

Revision Date 05/27/2014

Print Date 08/10/2016

Remove all sources of ignition.
Do not swallow.
Avoid breathing vapours, mist or gas.
Avoid contact with skin, eyes and clothing.

Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Discharge into the environment must be avoided.
Do not flush into surface water or sanitary sewer system.
Do not allow run-off from fire fighting to enter drains or water courses.

Methods for cleaning up : Ventilate the area.
No sparking tools should be used.
Use explosion-proof equipment.
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE**Handling**

Handling : Wear personal protective equipment.
Use only in well-ventilated areas.
Keep container tightly closed.
Do not smoke.
Do not swallow.
Avoid breathing vapours, mist or gas.
Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion : Keep away from fire, sparks and heated surfaces.
Take precautionary measures against static discharges.
Ensure all equipment is electrically grounded before beginning transfer operations.
Use explosion-proof equipment.
Keep product and empty container away from heat and sources of ignition.
No sparking tools should be used.
No smoking.

Storage

BC721-56 ACTIVATOR 0.25M ETT, 56L SSPDS

000000011308

Version 1.3

Revision Date 05/27/2014

Print Date 08/10/2016

Requirements for storage areas and containers : Store in area designed for storage of flammable liquids. Protect from physical damage. Keep containers tightly closed in a dry, cool and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep away from heat and sources of ignition. Keep away from direct sunlight. Store away from incompatible substances. Container hazardous when empty. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Ensure that eyewash stations and safety showers are close to the workstation location.

Engineering measures : Use with local exhaust ventilation. Prevent vapour buildup by providing adequate ventilation during and after use.

Eye protection : Do not wear contact lenses. Wear as appropriate: Safety glasses with side-shields If splashes are likely to occur, wear: Goggles or face shield, giving complete protection to eyes

Hand protection : Solvent-resistant gloves. Gloves must be inspected prior to use. Replace when worn.

Skin and body protection : Wear as appropriate: Solvent-resistant apron Flame retardant antistatic protective clothing If splashes are likely to occur, wear: Protective suit

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. For rescue and maintenance work in storage tanks use self-contained breathing apparatus. Use NIOSH approved respiratory protection.

BC721-56 ACTIVATOR 0.25M ETT, 56L SSPDS

000000011308

Version 1.3

Revision Date 05/27/2014

Print Date 08/10/2016

Hygiene measures : When using do not eat, drink or smoke.
 Wash hands before breaks and immediately after handling the product.
 Keep working clothes separately.
 Remove and wash contaminated clothing before re-use.
 Do not swallow.
 Avoid breathing vapours, mist or gas.
 Avoid contact with skin, eyes and clothing.

Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Update	Basis
Acetonitrile	75-05-8	TWA : time weighted average	(20 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values
Acetonitrile	75-05-8	SKIN_DE S : Skin designati on:	Can be absorbed through the skin.	2008	ACGIH:US. ACGIH Threshold Limit Values
Acetonitrile	75-05-8	REL : Recomm ended exposure limit (REL):	34 mg/m3 (20 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards
Acetonitrile	75-05-8	PEL : Permissi ble exposure limit	70 mg/m3 (40 ppm)	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
Acetonitrile	75-05-8	TWA : time weighted average	70 mg/m3 (40 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)

BC721-56 ACTIVATOR 0.25M ETT, 56L SSPDS

000000011308

Version 1.3

Revision Date 05/27/2014

Print Date 08/10/2016

Acetonitrile	75-05-8	STEL : Short term exposure limit	105 mg/m ³ (60 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)
--------------	---------	--	-----------------------------------	------	---

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Color	: colourless
Odor	: sweet ether-like
pH	: 2.6
Melting point/freezing point	: -46 °C Note: The physical data is that of the main component.
Boiling point/boiling range	: 82 °C Note: The physical data is that of the main component.
Flash point	: < 45 °F (7 °C) Method: closed cup
Lower explosion limit	: 3 %(V) Note: The physical data is that of the main component.
Upper explosion limit	: 16 %(V) Note: The physical data is that of the main component.
Vapor pressure	: 97 hPa at 20 °C(68 °F)Note: The physical data is that of the main component.
Vapor density	: 1.42 Note: The physical data is that of the main component.

BC721-56 ACTIVATOR 0.25M ETT, 56L SSPDS

000000011308

Version 1.3

Revision Date 05/27/2014

Print Date 08/10/2016

Density : 0.795 g/cm³ at 20 °C
0.790 g/cm³ at 25 °C

Water solubility : Note: completely soluble

Ignition temperature : 524 °C
Method: The physical data is that of the main component.

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Hazardous polymerisation does not occur.

Conditions to avoid : Heat, flames and sparks.
Keep away from direct sunlight.

Incompatible materials to avoid : Acids
Bases
Oxidizing agents
Reducing agents
Sulfites
Perchlorates
May attack many plastics, rubbers and coatings.

Hazardous decomposition products : In case of fire hazardous decomposition products may be produced such as:
Hydrogen cyanide (hydrocyanic acid)
Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

BC721-56 ACTIVATOR 0.25M ETT, 56L SSPDS

000000011308

Version 1.3

Revision Date 05/27/2014

Print Date 08/10/2016

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity
Acetonitrile : LD50: 2,460 mg/kg
Species: rat

Acute inhalation toxicity
Acetonitrile : LC50: 16000 ppm
Exposure time: 4 h
Species: rat

Acute dermal toxicity
Acetonitrile : LD50: > 2,000 mg/kg
Species: rabbit

Eye irritation
Acetonitrile : Species: rabbit
Result: Irritating to eyes.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity to fish
Acetonitrile : flow-through test
LC50: 1,640 mg/l
Exposure time: 96 h
Species: Pimephales promelas (fathead minnow)

Further information on ecology**SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods : Observe all Federal, State, and Local Environmental

BC721-56 ACTIVATOR 0.25M ETT, 56L SSPDS

000000011308

Version 1.3

Revision Date 05/27/2014

Print Date 08/10/2016

regulations.

SECTION 14. TRANSPORT INFORMATION

DOT UN/ID No. : UN 1648
 Proper shipping name : ACETONITRILE SOLUTION
 Class : 3
 Packing group : II
 Hazard Labels : 3

IATA UN/ID No. : UN 1648
 Description of the goods : ACETONITRILE SOLUTION
 Class : 3
 Packaging group : II
 Hazard Labels : 3
 Packing instruction (cargo aircraft) : 364
 Packing instruction (passenger aircraft) : 353
 Packing instruction (passenger aircraft) : Y341

IMDG UN/ID No. : UN 1648
 Description of the goods : ACETONITRILE SOLUTION
 Class : 3
 Packaging group : II
 Hazard Labels : 3
 EmS Number : F-E, S-D
 Marine pollutant : no

SECTION 15. REGULATORY INFORMATION**Inventories**

US. Toxic Substances : Not On TSCA Inventory
 Control Act

Australia. Industrial : 5-Ethylthio-1H-Tetrazole 89797-68-2
 Chemical (Notification and : Not in compliance with the inventory
 Assessment) Act

BC721-56 ACTIVATOR 0.25M ETT, 56L SSPDS

000000011308

Version 1.3

Revision Date 05/27/2014

Print Date 08/10/2016

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL)	: 5-Ethylthio-1H-Tetrazole : This product contains the following components that are not on the Canadian DSL nor NDSL.	89797-68-2
Japan. Kashin-Hou Law List	: 5-Ethylthio-1H-Tetrazole : Not in compliance with the inventory	89797-68-2
Korea. Toxic Chemical Control Law (TCCL) List	: 5-Ethylthio-1H-Tetrazole : Not in compliance with the inventory	89797-68-2
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	: 5-Ethylthio-1H-Tetrazole : Not in compliance with the inventory	89797-68-2
China. Inventory of Existing Chemical Substances	: 5-Ethylthio-1H-Tetrazole : Not in compliance with the inventory	89797-68-2
New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand	: 5-Ethylthio-1H-Tetrazole : On the inventory, or in compliance with the inventory	89797-68-2

National regulatory information

TSCA	: This material must be used in compliance with the TSCA Research and Development Exemption requirements (40 CFR 720.36).
TSCA	: Products used for the synthesis of drug substances are exempt from the requirements of TSCA. (40 CFR 720.30(a) & 720.3(e)(6))
US. EPA CERCLA	: The following component(s) of this product is/are subject to

BC721-56 ACTIVATOR 0.25M ETT, 56L SSPDS

000000011308

Version 1.3

Revision Date 05/27/2014

Print Date 08/10/2016

Hazardous Substances (40 CFR 302) : release reporting under 40 CFR 302 when release exceeds the Reportable Quantity (RQ):

Reportable quantity: 5000 lbs
: Acetonitrile 75-05-8

SARA 302 Components : SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components : The following components are subject to reporting levels established by SARA Title III, Section 313:
: Acetonitrile 75-05-8

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Chronic Health Hazard

CERCLA Reportable Quantity : 5208 lbs

California Prop. 65 : WARNING! This product contains a chemical known to the State of California to cause cancer.
Acrylonitrile 107-13-1

Massachusetts RTK : Acetonitrile 75-05-8

New Jersey RTK : Acetonitrile 75-05-8

Pennsylvania RTK : Acetonitrile 75-05-8

WHMIS Classification : B2: Flammable liquid
D1A: Very Toxic Material Causing Immediate and Serious Toxic Effects
D2B: Toxic Material Causing Other Toxic Effects
This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

BC721-56 ACTIVATOR 0.25M ETT, 56L SSPDS

000000011308

Version 1.3

Revision Date 05/27/2014

Print Date 08/10/2016

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 2*	2
Flammability	: 3	3
Physical Hazard	: 0	
Instability	:	0

* - Chronic health hazard

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 03/29/2011

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group