World Headquarters Hach Company P.O.Box 389 Loveland, CO USA 80539 (970) 669-3050

MATERIAL SAFETY DATA SHEET

Emergency Telephone Numbers: (Medical and Transportation)

24 Hour Service

8am - 4pm CST

(303) 623-5716

(515)232-2533

MSDS No: M00439

4 CHELDON PROPUCE AND COMPANY PROPUENTS ATTOM

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Molybdate Reagent

Catalog Number: 223653

Hach Company P.O.Box 389 Loveland, CO USA 80539 (970) 669-3050

MSDS Number: M00439 Chemical Name: Not applicable CAS Number: Not applicable.

Additional CAS No. (for hydrated forms): Not applicable

Chemical Formula: Not applicable *Chemical Family:* Not applicable

Intended Use: Laboratory Reagent Phosphate determination

2. HAZARDS IDENTIFICATION

GHS Classification:

Hazard categories: Corrosive to Metals: Met. Corr. 1 . Skin Corrosion/Irritation: Skin Corr. 1A

GHS Label Elements:

DANGER



Hazard statements: May be corrosive to metals. . Causes severe skin burns and eye damage.

Precautionary statements: P234: Keep only in original container. Wash thoroughly after handling. Wear protective gloves / protective clothing / eye protection / face protection. IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

HMIS:

Health: 3
Flammability: 0
Reactivity: 2

Protective Equipment: X - See protective equipment, Section 8.

NFPA:

Health: 3 Flammability: 0 Reactivity: 2

Symbol: Water Reactive

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Components according to GHS: Yes

Ammonium Molybdate

CAS Number: 12027-67-7

Chemical Formula: (NH₄)₆Mo₇O₂₄ · 4H₂O

GHS Classification: Acute Tox. 4, H302; Eye irrit. 2, H319; Skin Irrit. 2, H315; STOT SE 3, H335

Percent Range: 1.0 - 10.0

Percent Range Units: weight / weight

PEL: 5 mg/m³ as Mo **TLV:** 5 mg/m³ as Mo

Sulfuric Acid

CAS Number: 7664-93-9 Chemical Formula: H₂SO₄

GHS Classification: Met. Corr. 1 H290; Skin Corr. 1A, H314

Percent Range: 40.0 - 50.0

Percent Range Units: weight / weight

PEL: 1 mg/m^3

TLV: 1 mg/m³ (TWA); 3 mg/m³ (STEL)

Hazardous Components according to GHS: No

Demineralized Water

CAS Number: 7732-18-5 Chemical Formula: H₂O

GHS Classification: Not applicable

Percent Range: 35.0 - 45.0

Percent Range Units: weight / weight

PEL: Not established **TLV:** Not established

Other components, each

CAS Number: Not applicable *Chemical Formula:* Not applicable. *GHS Classification:* Not applicable

Percent Range: 0.1 - 1.0

Percent Range Units: weight / weight

PEL: Not established **TLV:** Not established

4. FIRST AID MEASURES

General Information: In the event of exposure, show this Material Safety Data Sheet and label (where possible) to a doctor.

Advice to doctor: Treat symptomatically.

Eye Contact: Immediately flush eyes with water for 15 minutes. Call physician.

Skin Contact (First Aid): Wash skin with plenty of water for 15 minutes. Call physician immediately.

Inhalation: Remove to fresh air. Give artificial respiration if necessary. Call physician.

Ingestion (First Aid): Do not induce vomiting. Give 1-2 glasses of water. Never give anything by mouth to an

unconscious person. Call physician immediately.

5. FIRE FIGHTING MEASURES

Flammable Properties: Not Flammable, but reacts with most metals to form flammable hydrogen gas. During a fire, corrosive and toxic gases may be generated by thermal decomposition.

Fire Fighting Instruction: As in any fire, wear self-contained breathing apparatus pressure-demand and full protective

Extinguishing Media: Dry chemical. Do NOT use water.

Extinguishing Media NOT To Be Used: Not applicable Do NOT use water.

Fire / Explosion Hazards: Contact with metals gives off hydrogen gas which is flammable May react violently with:

strong bases water

6. ACCIDENTAL RELEASE MEASURES

Spill Response Notice:

Only persons properly qualified to respond to an emergency involving hazardous substances may respond to a spill according to federal regulations (OSHA 29 CFR 1910.120(a)(v)) and per your company's emergency response plan and guidelines/procedures. See Section 13, Special Instructions for disposal assistance. Outside of the US, only persons properly qualified according to state or local regulations should respond to a spill involving chemicals.

Containment Technique: Absorb spilled liquid with non-reactive sorbent material. Stop spilled material from being released to the environment.

Clean-up Technique: Cover spilled material with an alkali, such as soda ash or sodium bicarbonate. Scoop up slurry into a large beaker. Dilute with a large excess of water. Adjust to a pH between 6 and 9 with an alkali, such as soda ash or sodium bicarbonate. Flush reacted material to the drain with a large excess of water. Decontaminate the area of the spill with a soap solution.

Evacuation Procedure: Evacuate local area (15 foot radius or as directed by your facility's emergency response plan) when: any quantity is spilled. If conditions warrant, increase the size of the evacuation.

DOT Emergency Response Guide Number: 154

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes skin clothing Do not breathe mist or vapors. Wash thoroughly after handling. Use with adequate ventilation. Maintain general industrial hygiene practices when using this product.

Storage: Keep container tightly closed when not in use. Protect from: heat Keep away from: alkalies oxidizers reducers metals

Flammability Class: Not applicable

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Use general ventilation to minimize exposure to mist, vapor or dust. Maintain general industrial hygiene practices when using this product.

Personal Protective Equipment:

Eye Protection: safety glasses with top and side shields

Skin Protection: disposable latex gloves In the EU, the selected gloves must satisfy the specifications of EU Directive

89/686/EEC and standard EN 374 derived from it. lab coat

Inhalation Protection: adequate ventilation

Precautionary Measures: Avoid contact with: eyes skin clothing Do not breathe: mist/vapor Wash thoroughly after handling. Use with adequate ventilation. Protect from: heat Keep away from: alkalies oxidizers reducers metals

TLV: Not established PEL: Not established

 $For \ Occupational \ Exposure \ Limits \ (OEL) \ for \ ingredients, see \ section \ 3 - Composition/Information \ on \ Ingredients.:$

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear, colorless liquid

Physical State: Liquid

Molecular Weight: Not applicable.

Odor: None

Odor Threshold: Not applicable.

pH: < 0.5

Metal Corrosivity:

Corrosivity Classification: Classified as corrosive to metals.

Steel: 4.23 in/yr (107.4 mm/yr) **Aluminum:** Not determined.

Specific Gravity/Relative Density (water = 1; air =1): 1.30

Viscosity: Not determined

Solubility:

Water: Miscible.
Acid: Miscible.
Other: Not determined.

Partition Coefficient (n-octanol / water): Not applicable.

Coefficient of Water / Oil: Not applicable.

Melting Point: Not applicable.

Decomposition Temperature: Not determined

Boiling Point: Not determined.

Vapor Pressure: Not determined.

Vapor Density (air = 1): Not determined.

Evaporation Rate (water = 1): 0.12

Volatile Organic Compounds Content: None.

Flammable Properties: Not Flammable, but reacts with most metals to form flammable hydrogen gas. During a fire, corrosive and toxic gases may be generated by thermal decomposition.

Flash Point: Not applicable.

Method: Not applicable

Flammability Limits:

Lower Explosion Limits: Not applicable. Upper Explosion Limits: Not applicable. Autoignition Temperature: Not applicable.

Explosive Properties:

Not classified according to GHS criteria.

Oxidizing Properties:

Not classified according to GHS criteria.

Reactivity Properties:

Not classifed as self-reactive, pyrophoric, self-heating or emitting flammable gases in contact with water according to GHS criteria.

Gas under Pressure:
Not determined

10. STABILITY AND REACTIVITY

Chemical Stability: Stable when stored under proper conditions.

Mechanical Impact: None reported *Static Discharge:* None reported.

Reactivity / Incompatibility: May react violently in contact with: acetic acid chlorosulfonic acid strong bases oxidizers

reducers Incompatible with: metals

Hazardous Decomposition: Contact with metals may release flammable hydrogen gas. Heating to decomposition releases

toxic and/or corrosive fumes of: ammonia nitrogen oxides sulfur oxides

Conditions to Avoid: Exposure to light. Extreme temperatures Heating to decomposition.

11. TOXICOLOGICAL INFORMATION

Toxicokinetics, Metabolism and Distribution: No information available for mixture.

Toxicologically Synergistic Products: None reported

Acute Toxicity: Acute Toxicity Estimate (ATE) - Calculated from Ingredient Toxicity Data

ATE Oral Rat LD50 = 3845 mg/kg

Specific Target Organ Toxicity - Single Exposure (STOT-SE): Based on classification principles, the classification criteria are not met.

Specific Target Organ Toxicity - Repeat Exposure (STOT-RE): Based on classification principles, the classification criteria are not met.

Skin Corrosion/Irritation: Corrosive to skin.

Eye Damage: Corrosive to eyes.

Sensitization: Based on classification principles, the classification criteria are not met.

CMR Effects/Properties (carcinogenic, mutagenic or toxic to reproduction): No germ cell mutagenicity, carcinogenicity or reproductive toxicity data found.

An ingredient of this mixture is: IARC Group 1: Recognized Carcinogen

Sulfuric Acid - The IARC evaluation was based on exposure to the mist or vapor of concentrated sulfuric acid generated during chemical processes.

This product does NOT contain any NTP listed chemicals.

This product does NOT contain any OSHA listed carcinogens.

Symptoms/Effects:

Ingestion: Causes: severe burns May cause: circulatory disturbances diarrhea gastrointestinal tract irritation nausea vomiting rapid pulse and respirations coma death Molybdenum compounds may cause loss of coordination, enzyme activity effects, copper deficiency and gout.

Inhalation: Causes: severe burns May cause: difficult breathing teeth erosion mouth soreness

Skin Absorption: None Reported

Chronic Effects: Molybdenum poisoning signs include loss of appetite, listlessness and reduced growth rate. Excessive exposure to molybdenum compounds may cause gout and anemia. Chronic overexposure may cause erosion of the teeth chronic irritation or inflammation of the lungs cancer

Medical Conditions Aggravated: Pre-existing: Eye conditions Skin conditions Respiratory conditions Gout

12. ECOLOGICAL INFORMATION

Product Ecological Information: --

No ecological data available for this product. Mobility in soil: No data available

Ingredient Ecological Information: Sulfuric Acid: The 48-Hour TLm in flounder is 100-300 ppm.

CEPA Statement: Sulfuric Acid: Persistent, not bioaccumulative or inherently toxic to aquatic organsisms.

13. DISPOSAL CONSIDERATIONS

EPA Waste ID Number: D002

Special Instructions (Disposal): Work in an approved fume hood. Dilute material with excess water making a weaker than 5% solution. Adjust to a pH between 6 and 9 with an alkali, such as soda ash or sodium bicarbonate. Open cold water tap completely, slowly pour the material to the drain. Allow cold water to run for 5 minutes to completely flush the system. *Empty Containers:* Rinse three times with an appropriate solvent. Dispose of empty container as normal trash.

NOTICE (*Disposal*): These disposal guidelines are based on federal regulations and may be superseded by more stringent state or local requirements. Please consult your local environmental regulators for more information. In Europe: Chemical and analysis solutions must be disposed of in compliance with the respective national regulations. Product packaging must be disposed of in compliance with the country-specific regulations or must be passed to a packaging return system.

14. TRANSPORT INFORMATION

```
D.O.T.:
```

D.O.T. Proper Shipping Name: Corrosive Liquid, Acidic, Inorganic, N.O.S.

(<45% Sulfuric Acid in solution)

Hazard Class: 8 Subsidiary Risk: NA ID Number: UN3264 Packing Group: II

T.D.G.:

Proper Shipping Name: Corrosive Liquid, Acidic, Inorganic, N.O.S.

(<45% Sulfuric Acid in solution)

Hazard Class: 8 Subsidiary Risk: NA

PIN: 3264 Group: II I.C.A.O.:

I.C.A.O. Proper Shipping Name: Corrosive Liquid, Acidic, Inorganic, N.O.S.

(<45% Sulfuric Acid in solution)

Hazard Class: 8 Subsidiary Risk: NA ID Number: UN3264 Packing Group: II

I.M.O.:

I.M.O. Proper Shipping Name: Corrosive Liquid, Acidic, Inorganic, N.O.S.

(<45% Sulfuric Acid in solution)

Hazard Class: 8 Subsidiary Risk: NA ID Number: UN3264 Packing Group: II

Additional Information: There is a possibility that this product could be contained in a reagent set or kit composed of various compatible dangerous goods. If the item is NOT in a set or kit, the classification given above applies. If the item IS

part of a set or kit, the classification would change to the following: UN3316 Chemical Kit, Class 9, PG II or III. If the item is not regulated, the Chemical Kit classification does not apply.

15. REGULATORY INFORMATION

U.S. Federal Regulations:

O.S.H.A.: This product meets the criteria for a hazardous substance as defined in the Hazard Communication Standard. (29 CFR 1910.1200)

E.P.A.:

S.A.R.A. Title III Section 311/312 Categorization (40 CFR 370): Immédiat (aigu) Danger pour la santé Reactive Delaved (Chronic) Health Hazard

S.A.R.A. Title III Section 313 (40 CFR 372): This product contains a chemical(s) subject to the reporting requirements of Section 313 of Title III of SARA.

Ammonia

302 (EHS) TPQ (40 CFR 355): Sulfuric Acid 1000 lbs.

304 CERCLA RQ (40 CFR 302.4): Sulfuric Acid 1000 lbs.

304 EHS RQ (40 CFR 355): Sulfuric Acid - RQ 1000 lbs.

Clean Water Act (40 CFR 116.4): Sulfuric acid - RQ 1000 lbs.

RCRA: Contains RCRA regulated substances. See Section 13, EPA Waste ID Number.

State Regulations:

California Prop. 65: No Prop. 65 listed chemicals are present in this product.

Identification of Prop. 65 Ingredient(s): None

California Perchlorate Rule CCR Title 22 Chap 33: No

Trade Secret Registry: Not applicable

National Inventories:

U.S. Inventory Status: All ingredients in this product are listed on the TSCA 8(b) Inventory (40 CFR 710).

CAS Number: Not applicable.

Canadian Inventory Status: All ingredients of this product are DSL Listed.

EEC Inventory Status: All ingredients used to make this product are listed on EINECS / ELINCS.

Australian Inventory (AICS) Status: All ingredients are listed.

New Zealand Inventory (NZIoC) Status: All components either listed or exempt.

Korean Inventory (KECI) Status: Some ingredients are not listed or exempt.

Japan (ENCS) Inventory Status: All components either listed or exempt.

China (PRC) Inventory (MEP) Status: All components either listed or exempt.

16. OTHER INFORMATION

References: 29 CFR 1900 - 1910 (Code of Federal Regulations - Labor). Air Contaminants, Federal Register, Vol. 54, No. 12. Thursday, January 19, 1989. pp. 2332-2983. Cassaret and Doull's Toxicology, 3rd Ed. New York: Macmillan Publishing Co., Inc., 1986. CCINFO RTECS. Canadian Centre for Occupational Health and Safety. Hamilton, Ontario Canada: 30 June 1993. Gosselin, R. E. et al. Clinical Toxicology of Commercial Products, 5th Ed. Baltimore: The Williams and Wilkins Co., 1984. IARC Monographs on the Evaluation of the Carcinogenic Risks to Humans. World Health Organization (Volumes 1-42) Supplement 7. France: 1987. List of Dangerous Substances Classified in Annex I of the EEC Directive (67/548) - Classification, Packaging and Labeling of Dangerous Substances, Amended July 1992. Sixth Annual Report on Carcinogens, 1991. U.S. Department of Health and Human Services. Rockville, MD: Technical Resources, Inc. 1991. Technical Judgment. TLV's Threshold Limit Values and Biological Exposure Indices for 1992-1993. American Conference of Governmental Industrial Hygienists, 1992.

Complete Text of H phrases referred to in Section 3: H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage.

Revision Summary: . Substantial revision to comply with EU Reg 1272/2008, Reg 1907/2006 and UN GHS (ST/SG/AC.10/36/Add.3).

Date of MSDS Preparation:

Day: 02

Month: May

Year: 2012

MSDS Prepared: MSDS prepared by Product Compliance Department extension 3350

CCOHS Evaluation Note: It is offered under exemption from WHMIS labeling as specified in the Controlled Products Regulation (CPR) Section 17. It is offered under the interim policy that was established by Health Canada permitting use of GHS-formatted safety data sheets in Canada prior to revision of CPR to GHS. This product has been classified and labeled in accordance with the requirements of GHS (ST/SG/AC.10/36/Add.3). This SDS has been prepared in accordance with the requirements of GHS (ST/SG/AC.10/36/Add.3).

Legend:

NA - Not Applicable w/w - weight/weight
ND - Not Determined w/v - weight/volume
NV - Not Available v/v - volume/volume

USER RESPONSIBILITY: Each user should read and understand this information and incorporate it in individual site safety programs in accordance with applicable hazard communication standards and regulations.

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

HACH COMPANY ©2012