

# **FT402 Immersion Cooler**

# with immersion probe for rapid cooling of liquids

JULABO immersion coolers are primarily employed for countercooling open bath circulators to ambient temperature or below as well as for rapidly cooling liquids. JULABO immersion coolers have a small footprint and represent an economic solution preventing tap water usage for cooling. Ease of operation make this model series the i deal instruments for a variety of cooling applications.

# Your advantages

- · Rapid cooling of liquids down to low temperatures
- Counter-cooling of liquids in combination with heating circulators
- · Environmentally friendly by saving precious tap water
- User-friendly operation and handling
- · Compact design, small footprint
- · Dry ice substitution
- · Environmentally friendly by conserving precious tap water
- · Integrated temperature control and display
- With external Pt100 sensor (200 x 6 mm dia., stainless steel)





### **Technical Data**

. common Data	
Order No.	9650842
Model series	FT Series
Category	Immersion Coolers
Working temperature range (°C)	-40 +30
Temperature stability (°C)	±0.5
Temperature Display	LED
Cooling capacity (Medium Ethanol)	°C 20 10 -20 -40 kW 0.45 0.36 0.14 0.03
Refrigerant	R404A
Ambient temperature	535 °C
Dimensions W x L x H (inch)	7.9 x 11.8 x 16.9
Weight (LBS)	53
Order information	Refrigerant: 115V/60Hz = R134a ; 230V/50Hz = R404a.
Cooling of compressor	Air
Power requirement V / Hz / A	115/60/4
Immersion probe	4.7 x 2 (I x dia.) inch
Connection tube (L) inch	47.2
Available voltage versions	230 V / 50 Hz 115 V / 60 Hz

# **JULABO** Contact

JULABO USA Inc.

884 Marcon Boulevard, Allentown, PA 18109

Phone: 610-231-0250

Phone: 800-458-5226 (Toll-Free)

info.us@julabo.com

# JULABO Services

Product finder, Accessory search, 1 PLUS Warranty, Catalog download, Callback service, Operating manuals, Safety data sheets, Software and more

www.julabo.com

Technical changes without prior notification. Images may deviate from the original.