



NF15-RD-ECO-GR

ISO 374-1:2016/TYPE A

EN388:2016

EN374-5:2016



AJKLMNOPT



4101X



ABRASION



PUNCTURE

NEWTRILE™

HANDLE THE HOSTILE

EcoTek®

Biodegradability Technology



vwr.com

Protection for the Most Demanding Environments

The industry's first reusable chemical protection gloves with EcoTek® Biodegradability Technology. Advanced chemical protection now has a smaller carbon footprint.



NEWTRILE™

Nitrile Chemical Protection and Performance

featuring
EcoTek®

NF15-RD-ECO-GR

15 MIL FLOCK-LINED NITRILE CHEMICAL RESISTANT GLOVES



Flock-lined, hand specific, nitrile rubber chemical resistance gloves, case hardened for enhanced performance

- 15 mil thick and 13 inch cuff length for added protection
- EcoTek® Biodegradability Technology accelerates landfill breakdown without any performance loss*
- SW® nitrile gloves with EcoTek® biodegrade by 92.6% in only 2 years and 6 months*
- Embossed recessed-diamond surface for wet/dry grip
- Case hardened for enhanced physical and chemical performance while providing easier and more comfortable donning and doffing

Ideal Applications:

- Boat Manufacturing
- Chemical
- Food
- Housekeeping
- Janitorial
- Machinery & Equipment
- Transportation



Recessed diamond grip pattern



Flock-lined inner surface for comfortable wear

13 inch cuff for added coverage and protection

PRODUCT ATTRIBUTES

SPECIFICATIONS	NF15-RD-ECO-GR
PRODUCT TYPE:	Chemical-Resistant
PUNCTURE LEVEL:	ANSI 2 — EN388 1
ABRASION LEVEL:	ANSI 6 — EN388 4
LINER MATERIAL:	Advanced Flocking
MATERIAL:	Nitrile with EcoTek®
COLOR:	Green
GRIP FINISH:	Recessed Diamond
CONSTRUCTION:	Unsupported
FIT TYPE:	Hand Specific
CUFF STYLE:	Straight
THICKNESS:	15 mil
LENGTH:	13"
ORIGIN COUNTRY:	Sri Lanka

STANDARDS & CERTIFICATIONS

FDA 21 CFR 177.2600
COMPONENT MATERIALS
COMPLY WITH FDA REGULATIONS
FOR FOOD CONTACT

Please visit swsafety.com/symbols for information on standards used in this document.



NF15-RD-ECO-GR ORDERING INFORMATION

N515092	S: 7
N515093	M: 8
N515094	L: 9
N515095	XL: 10
N515096	2XL: 11

12 Pairs per Bag, 12 Bags per Case



SW®
33278 Central Avenue, Unit 102, Union City, CA 94587, USA
Tel: +1.510.429.8692 | Fax: +1.510.487.5347

Trademarks and registered trademarks are the property of SW and its affiliates.
©2022 SW. All rights reserved.

*ASTM D5526-12 is a standard test method for determining anaerobic biodegradation of plastics in accelerated landfill conditions. Current biodegradation results do not predict future results.

For samples visit
swsafety.com/newtrile