

Isopropyl Alcohol**323-4**

Version 1.0

Revision Date 02/16/2018

Print Date 02/16/2018

SECTION 1. IDENTIFICATION

Product name : Isopropyl Alcohol

Number : 000000022794

Product Use Description : Solvent

Manufacturer or supplier's details : Manufactured by:
Honeywell International Inc.
1953 South Harvey Street
Muskegon, MI 49442
USA

Distributed by:
VWR International
2360 Argentia Road
Mississauga, Ontario L5N 5Z7
CANADA

For more information call : 1-800-932-5000
(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701 or +1-303-389-1414
: **Transportation (CHEMTREC): 1-800-424-9300 or**
: **+1-703-527-3887**
:
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Form : liquid

Color : colourless

Odor : slight alcohol-like

Isopropyl Alcohol**323-4**

Version 1.0

Revision Date 02/16/2018

Print Date 02/16/2018

Classification of the substance or mixture

Classification of the substance or mixture : Flammable liquids, Category 2
Eye irritation, Category 2A
Specific target organ toxicity - single exposure, Category 3,
Central nervous system

GHS Label elements, including precautionary statements

Symbol(s)



Signal word

: Danger

Hazard statements

: Highly flammable liquid and vapour.
Causes serious eye irritation.
May cause drowsiness and dizziness.

Precautionary statements

: **Prevention:**
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting/ equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ eye protection/ face protection.**Response:**

IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Call a POISON CENTER/doctor if you feel unwell.
If eye irritation persists: Get medical advice/ attention.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

Isopropyl Alcohol

323-4

Version 1.0

Revision Date 02/16/2018

Print Date 02/16/2018

Store in a well-ventilated place. Keep container tightly closed.
Keep cool.
Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula : C₃H₈O

Chemical nature : Substance

Chemical name	CAS-No.	Concentration
Isopropanol	67-63-0	100.00 %

SECTION 4. FIRST AID MEASURES

Inhalation : Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is present. Call a physician.

Skin contact : Wash off immediately with plenty of water for at least 15 minutes. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use. Call a physician if irritation develops or persists.

Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician.

Ingestion : Do not induce vomiting without medical advice. Immediate medical attention is required. Never give anything by mouth to an unconscious person. Call a physician.

Isopropyl Alcohol**323-4**

Version 1.0

Revision Date 02/16/2018

Print Date 02/16/2018

Notes to physician

Indication of immediate medical attention and special treatment needed, if necessary : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
Cool closed containers exposed to fire with water spray.
- Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.
- Specific hazards during firefighting : Flammable.
Vapours may form explosive mixtures with air.
Vapours are heavier than air and may spread along floors.
Vapors may travel to areas away from work site before igniting/flashing back to vapor source.
In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide
Carbon dioxide (CO₂)
- Special protective equipment for firefighters : Wear self-contained breathing apparatus and protective suit.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Wear personal protective equipment.
Immediately evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not swallow.
Avoid breathing vapours, mist or gas.
Avoid contact with skin, eyes and clothing.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.

Isopropyl Alcohol

323-4

Version 1.0

Revision Date 02/16/2018

Print Date 02/16/2018

Discharge into the environment must be avoided.
Do not flush into surface water or sanitary sewer system.
Do not allow run-off from fire fighting to enter drains or water courses.

Methods and materials for containment and cleaning up : Ventilate the area.
No sparking tools should be used.
Use explosion-proof equipment.
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Handling

Precautions for safe handling : Wear personal protective equipment.
Use only in well-ventilated areas.
Keep container tightly closed.
Do not smoke.
Do not swallow.
Avoid breathing vapours, mist or gas.
Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion : Keep away from fire, sparks and heated surfaces.
Take precautionary measures against static discharges.
Ensure all equipment is electrically grounded before beginning transfer operations.
Use explosion-proof equipment.
Keep product and empty container away from heat and sources of ignition.
No sparking tools should be used.
No smoking.

Storage

Conditions for safe storage, including any incompatibilities : Store in area designed for storage of flammable liquids. Protect from physical damage.
Keep containers tightly closed in a dry, cool and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Keep away from heat and sources of ignition.
Keep away from direct sunlight.
Store away from incompatible substances.

Isopropyl Alcohol**323-4**

Version 1.0

Revision Date 02/16/2018

Print Date 02/16/2018

Container hazardous when empty.
Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Protective measures : Ensure that eyewash stations and safety showers are close to the workstation location.
- Engineering measures : Use with local exhaust ventilation.
Prevent vapour buildup by providing adequate ventilation during and after use.
- Eye protection : Do not wear contact lenses.
Wear as appropriate:
Safety glasses with side-shields
If splashes are likely to occur, wear:
Goggles or face shield, giving complete protection to eyes
- Hand protection : Solvent-resistant gloves
Gloves must be inspected prior to use.
Replace when worn.
- Skin and body protection : Wear as appropriate:
Solvent-resistant apron
Flame retardant antistatic protective clothing.
If splashes are likely to occur, wear:
Protective suit
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
For rescue and maintenance work in storage tanks use self-contained breathing apparatus.
Use NIOSH approved respiratory protection.
- Hygiene measures : When using do not eat, drink or smoke.
Wash hands before breaks and immediately after handling the product.
Keep working clothes separately.
Remove and wash contaminated clothing before re-use.
Do not swallow.
Avoid breathing vapours, mist or gas.
Avoid contact with skin, eyes and clothing.

Exposure Guidelines

Components	CAS-No.	Value	Control	Upda	Basis
------------	---------	-------	---------	------	-------

Isopropyl Alcohol

323-4

Version 1.0

Revision Date 02/16/2018

Print Date 02/16/2018

			parameters	te	
Isopropanol	67-63-0	STEL : Short term exposure limit	984 mg/m3 (400 ppm)	07 2009	CAD AB OEL:Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)
Isopropanol	67-63-0	TWA : Time weighted average	492 mg/m3 (200 ppm)	07 2009	CAD AB OEL:Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)
Isopropanol	67-63-0	STEL : Short term exposure limit	(400 ppm)	07 2007	CAD BC OEL:Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)
Isopropanol	67-63-0	TWA : Time weighted average	(200 ppm)	07 2007	CAD BC OEL:Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Isopropyl Alcohol

323-4

Version 1.0

Revision Date 02/16/2018

Print Date 02/16/2018

Isopropanol	67-63-0	TWA : Time weighted average	(200 ppm)	03 2011	CAD MB OEL:Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)
Isopropanol	67-63-0	STEL : Short term exposure limit	(400 ppm)	03 2011	CAD MB OEL:Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)
Isopropanol	67-63-0	TWA : Time weighted average	(200 ppm)	11 2010	CAD ON OEL:Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)
Isopropanol	67-63-0	STEL : Short Term Exposure Limit (STEL):	(400 ppm)	11 2010	CAD ON OEL:Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)
Isopropanol	67-63-0	8 HR ACL : 8 hour average contamin ation limit:	(200 ppm)	05 2009	CAD SK OEL:Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Isopropyl Alcohol

323-4

Version 1.0

Revision Date 02/16/2018

Print Date 02/16/2018

Isopropanol	67-63-0	15 MIN ACL : 15 minute average contamin ation limit:	(400 ppm)	05 2009	CAD SK OEL:Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)
-------------	---------	--	-----------	------------	---

Isopropanol	67-63-0	TWA : Time weighted average	983 mg/m3 (400 ppm)	12 2008	OEL (QUE):Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)
-------------	---------	--------------------------------------	------------------------	------------	---

Isopropanol	67-63-0	STEL : Short term exposure limit	1,230 mg/m3 (500 ppm)	12 2008	OEL (QUE):Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)
-------------	---------	--	--------------------------	------------	---

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Color	: colourless
Odor	: slight alcohol-like
Odor threshold	: Note: no data available
pH	: Note: Not applicable
Melting point/range	: -88 °C
Boiling point/boiling range	: 82.3 °C

Isopropyl Alcohol**323-4**

Version 1.0

Revision Date 02/16/2018

Print Date 02/16/2018

Flash point	: 54 °F (12 °C) Method: closed cup
Evaporation rate	: Note: no data available
Lower explosion limit	: 2.0 %(V)
Upper explosion limit	: 12.0 %(V)
Vapor pressure	: 44 hPa at 20 °C(68 °F)
Vapor density	: 2.1 Note: (Air = 1.0)
Density	: 0.785 g/cm ³ at 20 °C
Water solubility	: Note: completely soluble
Partition coefficient: n-octanol/water	: Note: no data available
Ignition temperature	: 399 °C
Decomposition temperature	: Note: no data available
Viscosity, dynamic	: 2.1 mPa.s at 25 °C
Viscosity, kinematic	: Note: no data available
Molecular weight	: 60.11 g/mol

Isopropyl Alcohol**323-4**

Version 1.0

Revision Date 02/16/2018

Print Date 02/16/2018

SECTION 10. STABILITY AND REACTIVITY

Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Hazardous polymerization does not occur.
Conditions to avoid	: Heat, flames and sparks. Keep away from direct sunlight.
Incompatible materials	: Strong acids Strong oxidizing agents Keep away from metals. Acetaldehyde Aluminium Chlorine Ethylene oxide Isocyanates Oxygen May attack many plastics, rubbers and coatings.
Hazardous decomposition products	: In case of fire hazardous decomposition products may be produced such as: Carbon monoxide Carbon dioxide (CO ₂)

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity	: LD50: 5,045 mg/kg Species: Rat
Acute inhalation toxicity	: LC50: 16000 ppm Exposure time: 8 h Species: Rat
Acute dermal toxicity	: LD50: 12,800 mg/kg Species: Rabbit
Skin irritation	: Species: Rabbit Result: slight irritation

Isopropyl Alcohol**323-4**

Version 1.0

Revision Date 02/16/2018

Print Date 02/16/2018

Eye irritation : Species: Rabbit
Result: Severe eye irritation

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity effects**

Toxicity to fish : LC50: > 5 g/l
Exposure time: 24 h
Species: Carassius auratus (goldfish)

: LC50: 8,970 mg/l
Exposure time: 48 h
Species: Leuciscus idus (Golden orfe)

: LC50: 10,400 mg/l
Exposure time: 96 h
Species: Pimephales promelas (fathead minnow)

Toxicity to daphnia and other aquatic invertebrates : EC50: > 100 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)

Toxicity to algae : LC50: > 2,000 mg/l
Exposure time: 72 h
Species: Desmodesmus subspicatus (green algae)

Toxicity to bacteria : EC50: 35,390 mg/l
Exposure time: 5 min
Species: Photobacterium phosphoreum

Elimination information (persistence and degradability)

Biodegradability : Biochemical Oxygen Demand (BOD)
Biochemical oxygen demand within 5 days
Value: 58 %

Further information on ecology

Isopropyl Alcohol**323-4**

Version 1.0

Revision Date 02/16/2018

Print Date 02/16/2018

Additional ecological information : Accumulation in aquatic organisms is unlikely.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Observe all Federal, State, and Local Environmental regulations.

SECTION 14. TRANSPORT INFORMATION

TDG UN/ID No. : UN 1219
 Proper shipping name : Isopropanol
 Class : 3
 Packing group : II
 Hazard Labels : 3

IATA UN/ID No. : UN 1219
 Description of the goods : Isopropanol
 Class : 3
 Packaging group : II
 Hazard Labels : 3
 Packing instruction (cargo aircraft) : 364
 Packing instruction (passenger aircraft) : 353
 Packing instruction (passenger aircraft) : Y341

IMDG UN/ID No. : UN 1219
 Description of the goods : Isopropanol
 Class : 3
 Packaging group : II
 Hazard Labels : 3
 EmS Number : F-E, S-D
 Marine pollutant : no

SECTION 15. REGULATORY INFORMATION**Inventories**

US. Toxic Substances Control Act : On TSCA Inventory

Isopropyl Alcohol

323-4

Version 1.0

Revision Date 02/16/2018

Print Date 02/16/2018

Australia. Industrial Chemical (Notification and Assessment) Act : On the inventory, or in compliance with the inventory

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL) : All components of this product are on the Canadian DSL

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Existing Chemicals Inventory (KECI) : On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act : On the inventory, or in compliance with the inventory

China. Inventory of Existing Chemical Substances : On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand : On the inventory, or in compliance with the inventory

National regulatory information

WHMIS

Components : Isopropanol 67-63-0

NPRI

Components : Isopropanol 67-63-0

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 2*	1
Flammability	: 3	3
Physical Hazard	: 0	
Instability	:	0

Isopropyl Alcohol**323-4**

Version 1.0

Revision Date 02/16/2018

Print Date 02/16/2018

* - Chronic health hazard

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group