Butylhydroxytoluene



1. Product and company identification

Product name Product code	: Butylhydroxytoluene : 8.17074
Supplier	: EMD Millipore Corp. 290 Concord Rd. Billerica, MA 01821 1-978-715-1335 Technical Service Monday - Friday: 8:00 - 6:00 PM EST
Synonym	: 2,6-di-t-butyl-4-methylphenol
Material uses	: Other non-specified industry: Analytical reagent.
Validation date	: 11/26/2013.
In case of emergency	: 800-424-9300 CHEMTREC (USA) 613-996-6666 CANUTEC (Canada) 24 Hours/Day: 7 Days/Week

2. Hazards identification

Emergency overview	WARNING!
	CAUSES EYE AND SKIN IRRITATION. MAY CAUSE DAMAGE TO THE FOLLOWING ORGANS: LUNGS, NERVOUS SYSTEM, LIVER, RESPIRATORY TRACT, SKIN, EYES, THYROID. May cause long lasting harmful effects to aquatic life.
	Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.
Physical state	Solid. [Crystals.]
OSHA/HCS status	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Routes of entry	Dermal contact. Eye contact. Inhalation. Ingestion.
Potential acute health effect	
Inhalation	Dust may cause mechanical irritation.
Ingestion	Ingestion may cause gastrointestinal irritation and diarrhea.
Skin	Irritating to skin.
Eyes	Irritating to eyes.
Potential chronic health effe	
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.
Target organs	May cause damage to the following organs: lungs, the nervous system, liver, upper respiratory tract, skin, eyes, thyroid.
Medical conditions aggravated by over- exposure	Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.
See toxicological information	section 11)

3. Composition/information on ingredients

Name Butylhydroxytoluene CAS number 128-37-0 % by weight 100 4. First aid measures 100 Eye contact : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately. Skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes

- tact
 In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
- Inhalation : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
- Ingestion
- : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

5. Fire-fighting measures

Flammability of the product	: Combustible when exposed to heat or flame.
Extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Not suitable	: None known.
Special exposure hazards	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Special remarks on fire hazards	: Development of hazardous combustion gases or vapors possible in the event of fire. Avoid contact with oxidizing substances.
Special remarks on explosion hazards	: Avoid all possible sources of ignition (spark or flame).

6. Accidental release measures

Personal precautions	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods for cleaning up		
Spill	:	Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7. Handling and storage

Handling

: Do not ingest. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

: Store in accordance with local regulations. Store in original container, protected from direct sunlight. Keep container tightly closed and sealed until ready for use.

8. Exposure controls/personal protection

Ingredient	Exposure limits
Butylhydroxytoluene	OSHA PEL 1989 (United States, 3/1989). TWA: 10 mg/m ³ 8 hour(s). NIOSH REL (United States, 4/2013). TWA: 10 mg/m ³ 10 hour(s). ACGIH TLV (United States, 6/2013). TWA: 2 mg/m ³ 8 hour(s). Form: Inhalable fraction and vapor

Consult local authorities for acceptable exposure limits.

Engineering measures	: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Personal protection	
Respiratory	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Hands	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: nitrile rubber
Eyes	 Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. Recommended: safety glasses with side-shields
Skin	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: lab coat
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

Physical state	: Solid. [Crystals.]
Flash point	: Open cup: 126.67°C (260°F)
Auto-ignition temperature	: 470°C (878°F)
Color	: White.
Odor	: Odorless.
Molecular weight	: 220.35 g/mole

9. Physical and chemical properties

Molecular formula	: C15-H24-O
рН	: Not available.
Boiling/condensation point	: 265°C (509°F)
Melting/freezing point	: 69 to 70°C (156.2 to 158°F)
Relative density	: 1.048
Vapor pressure	: 0.0013 kPa (0.01 mm Hg) [20°C]
Vapor density	: 7.6 [Air = 1]
Odor threshold	: Not available.
Evaporation rate	: Not available.
VOC	: 0 % (w/w)
Solubility	: Insoluble in the following materials: water

10. Stability and reactivity

Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Hazardous polymerization	: Under normal conditions of storage and use, hazardous polymerization will not occur.
Conditions to avoid	: No specific data.
Materials to avoid	 Reactive or incompatible with the following materials: oxidizing materials, metals, acids and alkalis. Avoid all possible sources of ignition (spark or flame). Avoid generating dust. Incompatible with peroxides, bases, sulfuric acids, and strong acids.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Conditions of reactivity	:

Avoid all possible sources of ignition (spark or flame).

11. Toxicological information

Acute toxicity						
Product/ingredient name Butylhydroxytoluene			Test Route D50 Oral	Species Rat		Result ⊳2000 mg/kg
Irritation/Corrosion						
Product/ingredient name		Res	sult	Species	Score	Observation
Butylhydroxytoluene		Eye: irrita	s - Moderate nt	Rabbit	-	-
		Skin	- Mild irritant	Human	-	-
		Skin irrita	- Moderate nt	Rabbit	-	-
Carcinogenicity						
Classification						
Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Butylhydroxytoluene	A4	3	-	-	-	-
No known significant effects or critica	I hazards.					
Mutagenicity						
	I h a manda					

No known significant effects or critical hazards.

Teratogenicity

No known significant effects or critical hazards.

12. Ecological information

Aquatic ecotoxicity				
Product/ingredient name Butylhydroxytoluene	A	esult cute EC50 1.44 mg/L cute EC50 1440 ug/L resh water	Species Daphnia Daphnia - Water flea - Daphnia pulex - Neonate - < 24 hours	Exposure 48 hours 48 hours
Partition coefficient: n- octanol/water	: 5.1			
Bioconcentration factor	: 330 to 1800			
Environmental effects	: This product s	hows a high bioaccumula	ation potential.	
Other adverse effects	: No known sigr	nificant effects or critical h	nazards.	

13. Disposal considerations

The information presented only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	-	CHEMICALS, N.O.S.	-	-		No additional remark.

: Packing group

15. Regulatory information

United States		
HCS Classification	:	Irritating material Target organ effects
U.S. Federal regulations	:	TSCA 8(a) IUR: Not determined United States inventory (TSCA 8b): This material is listed or exempted.
		TSCA (Toxic Substance Control Act): This product is listed on the TSCA Inventory.
		SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found. SARA 302/304/311/312 hazardous chemicals: Butylhydroxytoluene SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Butylhydroxytoluene: Immediate (acute) health hazard, Delayed (chronic) health hazard
DEA List I Chemicals (Precursor Chemicals)	:	Not listed
DEA List II Chemicals (Essential Chemicals)	:	Not listed
Massachusetts Substances	:	This material is listed.
New Jersey Hazardous Substances	:	This material is listed.
Pennsylvania RTK Hazardous Substances	:	This material is listed.
<u>Canada</u>		
WHMIS (Canada)	:	Class D-2B: Material causing other toxic effects (Toxic).

15. Regulatory information

-	•
Canadian lists	: CEPA Toxic substances: This material is not listed.
	Canadian ARET: This material is not listed.
	Canadian NPRI: This material is listed.
	Alberta Designated Substances: This material is not listed.
	Ontario Designated Substances: This material is not listed.
	Quebec Designated Substances: This material is not listed.

CEPA DSL / CEPA NDSL : This material is listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

EU regulations

Hazard symbol or symbols



Risk phrases

- R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 S61- Avoid release to the environment. Refer to special instructions/safety data sheet.
- Safety phrases International regulations

International lists

Australia inventory (AICS): This material is listed or exempted.
 China inventory (IECSC): This material is listed or exempted.
 Japan inventory: This material is listed or exempted.
 Korea inventory: This material is listed or exempted.
 New Zealand Inventory of Chemicals (NZIoC): This material is listed or exempted.
 Philippines inventory (PICCS): This material is listed or exempted.

16. Other information

National Fire Protection Association (U.S.A.)



Notice to reader

The statements contained herein are based upon technical data that EMD Millipore Corp. believes to be reliable, are offered for information purposes only and as a guide to the appropriate precautionary and emergency handling of the material by a properly trained person having the necessary technical skills. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use, storage and disposal of these materials and the safety and health of employees and customers and the protection of the environment. EMD MILLIPORE CORP. MAKES NO REPRESENTATION OR WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE, WITH RESPECT TO THE INFORMATION HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS.