

# SAFETY DATA SHEET

Creation Date 27-Jan-2014 Revision Date 27-Jan-2014 Revision Number 1

### 1. Identification

Product Name 95% Dehydrant

Cat No. : 6301, 6315, 6355, V6301

Synonyms Denatured Ethyl alcohol

Recommended Use Laboratory chemicals

Uses advised against No Information available

### Details of the supplier of the safety data sheet

Company

Richard Allan Scientific A Subsidiary of Thermo Fisher Scientific

4481 Campus Drive Kalamazoo, MI 49008 Tel: (800) 522-7270

# **Emergency Telephone Number**

Chemtrec US: (800) 424-9300 Chemtrec EU: 001 (202) 483-7616

# 2. Hazard(s) identification

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 2

Specific target organ toxicity (single exposure) Category 1

Target Organs - Central nervous system (CNS), Optic nerve.

Specific target organ toxicity - (repeated exposure) Category 1

Target Organs - Kidney, Liver, spleen, Blood.

### **Label Elements**

### Signal Word

Danger

### **Hazard Statements**

Highly flammable liquid and vapor May cause drowsiness or dizziness

Causes damage to organs

Causes damage to organs through prolonged or repeated exposure



### **Precautionary Statements**

#### Prevention

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

### Response

IF exposed: Call a POISON CENTER or doctor/physician

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

#### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

In case of fire: Use CO2, dry chemical, or foam for extinction

# Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

#### Disposal

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

#### Other hazards

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. Cannot be made non-poisonous. WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

### 3. Composition / information on ingredients

#### Haz/Non-haz

Component	CAS-No	Weight %
Isopropyl alcohol	67-63-0	4-5
Ethyl alcohol	64-17-5	83-86
Methyl alcohol	67-56-1	4-5
Water	7732-18-5	5-7

### 4. First-aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention

is required.

**Inhalation** Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth resuscitation

if victim ingested or inhaled the substance; induce artificial respiration with a respiratory

medical device. Immediate medical attention is required.

**Ingestion** Do not induce vomiting. Call a physician or Poison Control Center immediately.

Most important symptoms/effects Breathing difficulties. Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting.

Notes to Physician Treat symptomatically.

# 5. Fire-fighting measures

Suitable Extinguishing Media CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam.

Unsuitable Extinguishing Media Water may be ineffective

**Flash Point** 17.2°C / 63.0°F

**Method -** No information available.

Autoignition Temperature 362.8°C / 685°F

**Explosion Limits** 

**Upper** 19.0 vol % **Lower** 3.3 vol %

Sensitivity to mechanical

impact

No information available.

Sensitivity to static discharge No information available.

### **Specific Hazards Arising from the Chemical**

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Hazardous Combustion Products Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Formaldehyde.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

**NFPA** 

Health	Flammability	Instability	Physical hazards
3	3	0	N/A

### 6. Accidental release measures

Personal Precautions Use personal protective equipment. Remove all sources of ignition. Take precautionary

measures against static discharges. Do not get in eyes, on skin, or on clothing.

**Environmental Precautions**Should not be released into the environment. See Section 12 for additional ecological

Information.

Up

Methods for Containment and Clean Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary measures against static discharges. Keep in suitable, closed containers for disposal.

# 7. Handling and storage

Use only under a chemical fume hood. Use explosion-proof equipment. Keep away from open Handling

flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Wear personal protective equipment. Do not breathe vapors or spray mist. Do not

get in eyes, on skin, or on clothing.

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat Storage

and sources of ignition. Flammables area.

Strong oxidizing agents. Strong acids. **Incompatible Products** 

# 8. Exposure controls / personal protection

#### **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
Isopropyl alcohol	TWA: 200 ppm	(Vacated) TWA: 400 ppm	IDLH: 2000 ppm
	STEL: 400 ppm	(Vacated) TWA: 980 mg/m <sup>3</sup>	TWA: 400 ppm
		(Vacated) STEL: 500 ppm	TWA: 980 mg/m <sup>3</sup>
		(Vacated) STEL: 1225 mg/m <sup>3</sup>	STEL: 500 ppm
		TWA: 400 ppm	STEL: 1225 mg/m <sup>3</sup>
		TWA: 980 mg/m <sup>3</sup>	
Ethyl alcohol	STEL: 1000 ppm	(Vacated) TWA: 1000 ppm	IDLH: 3300 ppm
		(Vacated) TWA: 1900 mg/m <sup>3</sup>	TWA: 1000 ppm
		TWA: 1000 ppm	TWA: 1900 mg/m <sup>3</sup>
		TWA: 1900 mg/m <sup>3</sup>	
Methyl alcohol	TWA: 200 ppm	(Vacated) TWA: 200 ppm	IDLH: 6000 ppm
-	STEL: 250 ppm	(Vacated) TWA: 260 mg/m <sup>3</sup>	TWA: 200 ppm
	Skin	(Vacated) STEL: 250 ppm	TWA: 260 mg/m <sup>3</sup>
		(Vacated) STEL: 325 mg/m <sup>3</sup>	STEL: 250 ppm
		Skin	STEL: 325 mg/m <sup>3</sup>
		TWA: 200 ppm	_
		TWA: 260 mg/m <sup>3</sup>	

Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV
Isopropyl alcohol	TWA: 400 ppm	TWA: 400 ppm	TWA: 200 ppm
	TWA: 985 mg/m <sup>3</sup>	TWA: 980 mg/m <sup>3</sup>	STEL: 400 ppm
	STEL: 500 ppm	STEL: 500 ppm	
	STEL: 1230 mg/m <sup>3</sup>	STEL: 1225 mg/m <sup>3</sup>	
Ethyl alcohol	TWA: 1000 ppm	TWA: 1000 ppm	STEL: 1000 ppm
	TWA: 1880 mg/m <sup>3</sup>	TWA: 1900 mg/m <sup>3</sup>	
Methyl alcohol	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm
	TWA: 262 mg/m <sup>3</sup>	TWA: 260 mg/m <sup>3</sup>	STEL: 250 ppm
	STEL: 250 ppm	STEL: 250 ppm	Skin
	STEL: 328 mg/m <sup>3</sup>	STEL: 310 mg/m <sup>3</sup>	
	Skin		

Legend

ACGIH - American Conference of Industrial Hygiene OSHA - Occupational Safety and Health Administration NIOSH IDLH: Immediately Dangerous to Life or Health

**Engineering Measures** Use only under a chemical fume hood. Use explosion-proof

electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are

close to the workstation location.

### **Personal Protective Equipment**

**Eye/face Protection** Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's

eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166

**Skin and body protection** Wear appropriate protective gloves and clothing to prevent skin exposure

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN

149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice

### 9. Physical and chemical properties

Physical StateLiquidAppearanceClearOdoraromatic

Odor Threshold<br/>pHNo information available.<br/>No information available.

**Evaporation Rate**No information available. **Flammability (solid,gas)**No information available.

Flammability or explosive limits

 Upper Lower
 19.0 vol %

 Lower
 3.3 vol %

 Vapor Pressure
 40 mmHg

 Vapor Density
 1.24

 Relative Density
 0.822

SolubilitySoluble in waterPartition coefficient; n-octanol/waterNo data availableAutoignition Temperature362.8°C / 685°F

Decomposition temperatureNo information available.ViscosityNo information available.

### 10. Stability and reactivity

**Reactive Hazard**None known, based on information available.

**Stability** Stable under normal conditions.

**Conditions to Avoid** Incompatible products. Heat, flames and sparks.

Incompatible Materials Strong oxidizing agents, Peroxides, Metals, Acids, Acid anhydrides, Acid chlorides

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), Formaldehyde

Hazardous Polymerization Hazardous polymerization does not occur

Hazardous Reactions None under normal processing

### 11. Toxicological information

### **Acute Toxicity**

**Product Information**No acute toxicity information is available for this product

Oral LD50Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.Dermal LD50Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.Vapor LC50Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

**Component Information** 

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isopropyl alcohol	5840 mg/kg (Rat)	13900 mg/kg (Rat)	72.6 mg/L (Rat) 4 h
		12870 mg/kg ( Rabbit )	
Ethyl alcohol	7060 mg/kg (Rat)	Not listed	20000 ppm/10H ( Rat )
Methyl alcohol	5628 mg/kg (Rat)	15800 mg/kg (Rabbit)	64000 ppm (Rat) 4 h
•			83.2 mg/L (Rat) 4 h

**Toxicologically Synergistic** 

**Products** 

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes

**Sensitization** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Isopropyl alcohol	67-63-0	Not listed				
Ethyl alcohol	64-17-5	Group 1	Not listed	A3	X	Not listed
Methyl alcohol	67-56-1	Not listed				
Water	7732-18-5	Not listed				

IARC: (International Agency for Research on Cancer)

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

Mutagenic Effects Mutagenic effects have occurred in humans.

**Reproductive Effects** Adverse reproductive effects have occurred in humans..

**Developmental Effects** Substances known to cause developmental toxicity in humans.

**Teratogenicity** Teratogenic effects have occurred in humans..

**STOT - single exposure** Central nervous system (CNS), Optic nerve.

**STOT - repeated exposure** Kidney, Liver, spleen, Blood.

**Aspiration hazard** No information available.

both acute and delayed tiredness, nausea and vomiting.

Endocrine Disruptor Information No information available

Other Adverse Effects Tumorigenic effects have been reported in experimental animals.. See actual entry in RTECS

for complete information.

### 12. Ecological information

### **Ecotoxicity**

Symptoms / effects,

.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Isopropyl alcohol	1000 mg/L EC50 > 72 h 1000 mg/L EC50 > 96 h	1400000 µg/L LC50 96 h 9640 mg/L LC50 96 h 11130 mg/L LC50 96 h	= 35390 mg/L EC50 Photobacterium phosphoreum 5 min	13299 mg/L EC50 = 48 h 9714 mg/L EC50 = 24 h

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethyl alcohol	EC50 (72h) = 275 mg/l	Fathead minnow (Pimephales	Photobacterium	EC50 = 9268 mg/L/48h
	(Chlorella vulgaris)	promelas) LC50 = 14200	phosphoreum:EC50 = 34634	EC50 = 10800  mg/L/24h
		mg/l/96h	mg/L/30 min	
		_	Photobacterium	
			phosphoreum:EC50 = 35470	
			mg/L/5 min	
Methyl alcohol	Not listed	Pimephales promelas: LC50	EC50 = 39000 mg/L 25 min	EC50 > 10000 mg/L 24h
		> 10000 mg/L 96h	EC50 = 40000 mg/L 15 min	-
		_	EC50 = 43000 mg/L 5 min	

Persistence and Degradability

No information available.

Bioaccumulation/ Accumulation

No information available

Mobility .

Component	log Pow
Isopropyl alcohol	0.05
Ethyl alcohol	-0.32
Methyl alcohol	-0.74

# 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl alcohol - 67-56-1	U154	-

# 14. Transport information

DOT

**UN-No** UN1170

Proper Shipping Name ETHANOL SOLUTION

Hazard Class 3
Packing Group

**TDG** 

UN-No UN1170

Proper Shipping Name ETHANOL SOLUTION

Hazard Class 3
Packing Group ||

<u>IATA</u>

**UN-No** UN1170

Proper Shipping Name ETHANOL SOLUTION

Hazard Class 3
Packing Group ||

IMDG/IMO

**UN-No** UN1170

Proper Shipping Name ETHANOL SOLUTION

Hazard Class 3
Packing Group

# 15. Regulatory information

#### International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	CHINA	KECL
Isopropyl alcohol	X	X	-	200-661-7	-		X	X	Χ	X	Χ
Ethyl alcohol	Χ	Χ	-	200-578-6	-		Χ	Χ	Х	Χ	Χ
Methyl alcohol	Х	Χ	-	200-659-6	-		Χ	Х	Х	Х	Χ
Water	Х	Χ	-	231-791-2	-		Χ	-	Χ	X	Χ

#### Legend:

- X Listed
- E Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule
- T Indicates a substance that is the subject of a Section 4 test rule under TSCA.
- XU Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).
- Y1 Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.
- Y2 Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

### **U.S. Federal Regulations**

**TSCA 12(b)** 

Not applicable

#### **SARA 313**

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Isopropyl alcohol	67-63-0	4-5	1.0
Methyl alcohol	67-56-1	4-5	1.0

### SARA 311/312 Hazardous Categorization

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes
Sudden Release of Pressure Hazard No
Reactive Hazard No

### **Clean Water Act**

Not applicable

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Water	-	1 LB	-	-

#### Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	Χ		-

#### **OSHA** - Occupational Safety and Health Administration

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Methyl alcohol	5000 lb	-

### **California Proposition 65**

This product contains the following Proposition 65 chemicals: Ethyl alcohol is only a considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage.

Component	CAS-No	California Prop. 65	Prop 65 NSRL
Ethyl alcohol	64-17-5	Developmental	-
•		•	
Methyl alcohol	67-56-1	Methanol	-

### State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Isopropyl alcohol	X	X	X	-	X
Ethyl alcohol	X	X	X	-	X
Methyl alcohol	X	X	X	X	X

### **U.S. Department of Transportation**

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

### **U.S. Department of Homeland Security**

This product does not contain any DHS chemicals.

### Other International Regulations

Mexico - Grade Serious risk, Grade 3

#### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

B2 Flammable liquid D1B Toxic materials D2A Very toxic materials



# 16. Other information

Prepared By Regulatory Affairs

Richard Allan Scientific

A Subsidiary of Thermo Fisher Scientific

Tel: (800) 522-7270

 Creation Date
 17-Mar-2010

 Revision Date
 27-Jan-2014

 Print Date
 27-Jan-2014

Revision Summary "\*\*\*", and red text indicates revision

#### Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of SDS**