

Material Safety Data Sheet

Acetone, For Histology, Glassware Washing and other General Applications



Section 1. Product and Company Identification

Product name : Acetone, For Histology, Glassware Washing and other General Applications
Product code : AX0125
Synonym : Dimethyl Ketone; 2-Propanone
Material uses : Other non-specified industry: Analytical reagent.
Manufacturer : EMD Chemicals Inc.
P.O. Box 70
480 Democrat Road
Gibbstown, NJ 08027
856-423-6300 Technical Service
Monday - Friday: 8:00 - 5:00 PM
Validation date : **8/7/2006.**
Print date : 8/7/2006.
In case of emergency : 800-424-9300 CHEMTREC (USA)
613-996-6666 CANUTEC (Canada)
24 Hours/Day: 7 Days/Week

Section 2. Hazards Identification

Physical state : Liquid.
Odor : Pungent.
OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Emergency overview : DANGER!
EXTREMELY FLAMMABLE LIQUID AND VAPOR.
HARMFUL IF INHALED OR SWALLOWED.
CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION.
CAUSES DAMAGE TO THE FOLLOWING ORGANS: RESPIRATORY TRACT, SKIN, CENTRAL NERVOUS SYSTEM, EYE, LENS OR CORNEA.
VAPOR MAY CAUSE FLASH FIRE.
Do not ingest. Avoid contact with skin and clothing. Avoid breathing vapor or mist. Keep away from heat, sparks and flame. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.
Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.
Potential acute health effects
Eyes : Irritating to eyes.
Skin : Irritating to skin.
Inhalation : Toxic by inhalation. Irritating to respiratory system.
Ingestion : Toxic if swallowed.
Carcinogenic effects : No known significant effects or critical hazards.
Mutagenic effects : No known significant effects or critical hazards.
Teratogenicity / Reproductive toxicity : No known significant effects or critical hazards.
Medical conditions aggravated by over-exposure : Repeated skin exposure can produce local skin destruction or dermatitis. Repeated or prolonged exposure to the substance can produce lung damage. Repeated or prolonged contact with spray or mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to the substance can produce target organs damage.

See toxicological information (section 11)

Continued on Next Page

Section 3. Composition/Information on Ingredients

United States

<u>Name</u>	<u>CAS number</u>	<u>% by Weight</u>
Acetone	67-64-1	100

Section 4. First Aid Measures

- Eye contact** : Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention.
- Skin contact** : Get medical attention immediately. Flush contaminated skin with plenty of water. Continue to rinse for at least 10 minutes. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing or wear gloves. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Inhalation** : Get medical attention immediately. Move exposed person to fresh air. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Ingestion** : Get medical attention immediately. Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Section 5. Fire Fighting Measures

- Flammability of the product** : Extremely flammable liquid and vapor. Vapor may cause flash fire. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.
- Products of combustion** : These products are carbon oxides (CO, CO₂).
- Extinguishing media**
 - Suitable** : Use dry chemical, CO₂, water spray (fog) or foam.
 - Not suitable** : Do not use water jet.
- Special exposure hazards** : Not available.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Special remarks on fire hazards** : Dangerous fire and explosion risk. Vapor may travel a considerable distance to source of ignition and flash back.

Section 6. Accidental Release Measures

- Personal precautions** : Immediately contact emergency personnel. Eliminate all ignition sources. Keep unnecessary personnel away. Use suitable protective equipment. Do not touch or walk through spilled material.
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Methods for cleaning up** : If emergency personnel are unavailable, contain spilled material. For small spills, add absorbent (soil may be used in the absence of other suitable materials) and use a non-sparking or explosion-proof means to transfer material to a sealable, appropriate container for disposal. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

Section 7. Handling and Storage

- Handling** : Do not ingest. Avoid contact with eyes, skin and clothing. Keep container closed. Use only with adequate ventilation. Avoid breathing vapor or mist. Keep away from heat, sparks and flame. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Wash thoroughly after handling.
- Storage** : Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

Section 8. Exposure Controls/Personal Protection

Product name

United States

Acetone

Exposure limits

ACGIH (United States, 1996).

STEL: 1782 mg/m³ 15 minute/minutes.

TWA: 1188 mg/m³ 8 hour/hours.

OSHA (United States, 1989).

STEL: 2400 mg/m³ 15 minute/minutes.

TWA: 1800 mg/m³ 8 hour/hours.

ACGIH TLV (United States, 1/2006).

STEL: 1782 mg/m³ 15 minute/minutes. Form: All forms

STEL: 750 ppm 15 minute/minutes. Form: All forms

TWA: 1188 mg/m³ 8 hour/hours. Form: All forms

TWA: 500 ppm 8 hour/hours. Form: All forms

NIOSH REL (United States, 12/2001).

TWA: 590 mg/m³ 10 hour/hours. Form: All forms

TWA: 250 ppm 10 hour/hours. Form: All forms

OSHA PEL (United States, 8/1997).

TWA: 2400 mg/m³ 8 hour/hours. Form: All forms

TWA: 1000 ppm 8 hour/hours. Form: All forms

OSHA PEL 1989 (United States, 3/1989). Notes: The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors.

STEL: 2400 mg/m³ 15 minute/minutes. Form: All forms

STEL: 1000 ppm 15 minute/minutes. Form: All forms

TWA: 1800 mg/m³ 8 hour/hours. Form: All forms

TWA: 750 ppm 8 hour/hours. Form: All forms

Consult local authorities for acceptable exposure limits.

Section 8. Exposure Controls/Personal Protection

- Engineering measures** : Use only with adequate ventilation. If user operations generate dust, fumes, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Personal protection**
- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.
Recommended: splash goggles
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Body: Recommended: lab coat
- Respiratory** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: butyl rubber
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 9. Physical and Chemical Properties

- Physical state** : Liquid.
- Flash point** : Closed cup: -18.15°C (-0.7°F).
- Auto-ignition temperature** : 464.85°C (868.7°F)
- Flammable limits** : Lower: 2.6% Upper: 12.8%
- Color** : Colorless.
- Odor** : Pungent.
- Molecular weight** : 58.09 g/mole
- Molecular formula** : C₃H₆O
- Boiling/condensation point** : 56.12°C (133°F)
- Melting/freezing point** : -94.25°C (-137.7°F)
- Critical temperature** : 234.9°C (454.8°F)
- Relative density** : 0.791 (Water = 1)
- Vapor density** : 2 (Air = 1)
- Odor threshold** : 100 ppm
- Evaporation rate** : 6.06 compared with(n-BUTYL ACETATE=1)

Section 10. Stability and Reactivity

- Stability and reactivity** : The product is stable.
- Incompatibility with various substances** : Extremely reactive or incompatible with the following materials: oxidizing materials and acids.
- Hazardous decomposition products** : COx carbon oxides (CO, CO₂)
- Hazardous polymerization** : Will not occur.
- Conditions of reactivity** : Extremely flammable in the presence of the following materials or conditions: open flames, sparks and static discharge, heat, shocks and mechanical impacts and oxidizing materials.
Dangerous fire and explosion risk. Vapor may travel a considerable distance to source of ignition and flash back.
Extremely explosive in the presence of the following materials or conditions: open flames, sparks and static discharge, heat, shocks and mechanical impacts and oxidizing materials.

Section 11. Toxicological Information

Toxicity data

United States

<u>Product/ingredient name</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
Acetone	LD50	5800 mg/kg	Oral	Rat
	LD50	5340 mg/kg	Oral	Rabbit
	LDLo	714 mg/kg	Oral	human
	LDLo	8000 mg/kg	Oral	Dog

Chronic effects on humans : **CARCINOGENIC EFFECTS** A4 (Not classifiable for humans or animals.) by ACGIH. Causes damage to the following organs: upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Other toxic effects on humans : Very hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion, of inhalation.

Specific effects

Carcinogenic effects : No known significant effects or critical hazards.

Mutagenic effects : No known significant effects or critical hazards.

Teratogenicity / Reproductive toxicity : No known significant effects or critical hazards.

Sensitization

Ingestion : No known significant effects or critical hazards.

Inhalation : Irritating to respiratory system.

Eyes : Irritating to eyes.

Skin : Irritating to skin.

Section 12. Ecological Information

Ecotoxicity data

United States

<u>Product/ingredient name</u>	<u>Species</u>	<u>Period</u>	<u>Result</u>
Acetone	Daphnia magna (EC50)	48 hour/hours	23.5 mg/l
	Pimephales promelas (EC50)	48 hour/hours	8990 mg/l
	Daphnia magna (EC50)	48 hour/hours	13500 mg/l
	Daphnia magna (LC50)	96 hour/hours	>100 mg/l
	Pimephales promelas (LC50)	96 hour/hours	>100 mg/l
	Oncorhynchus mykiss (LC50)	96 hour/hours	5540 mg/l

Environmental precautions : No known significant effects or critical hazards.

Section 12. Ecological Information

Products of degradation : These products are carbon oxides (CO, CO₂) and water.
Toxicity of the products of biodegradation : The products of degradation are less toxic than the product itself.

Section 13. Disposal Considerations


Waste disposal : The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Section 14. Transport Information

Regulatory information	UN number	Proper shipping name	Class	PG*	Label	Additional information
DOT Classification	UN1090	ACETONE	3	II		Reportable quantity 5000 lbs. (2268 kg)

PG* : Packing group

Section 15. Regulatory Information

United States

HCS Classification : Flammable liquid
Toxic material
Irritating material
Target organ effects

U.S. Federal regulations : TSCA 8(b) inventory: Listed

Section 15. Regulatory Information

SARA 302/304/311/312 extremely hazardous substances: No products were found.
SARA 302/304 emergency planning and notification: No products were found.
SARA 302/304/311/312 hazardous chemicals: Acetone
SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Acetone :
Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard
Clean Water Act (CWA) 307: No products were found.
Clean Water Act (CWA) 311: No products were found.
Clean Air Act (CAA) 112 accidental release prevention: No products were found.
Clean Air Act (CAA) 112 regulated flammable substances: No products were found.
Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

State regulations : Pennsylvania RTK: Acetone : (environmental hazard, generic environmental hazard)
Massachusetts RTK: Acetone
New Jersey: Acetone

Canada

WHMIS (Canada) : Class B-2: Flammable liquid
Class D-2B: Material causing other toxic effects (Toxic).

CEPA DSL/CEPA NDSL : CEPA DSL: Acetone

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

EU regulations

Hazard symbol/symbols :



Risk phrases : R11- Highly flammable.
R36- Irritating to eyes.

Safety phrases : S2- Keep out of the reach of children.
S9- Keep container in a well-ventilated place.
S16- Keep away from sources of ignition - No smoking.
S26- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.


International regulations

International lists : Australia (NICNAS): Acetone
China: Acetone
Germany water class: Acetone
Japan (METI): Acetone
Korea (TCCL): Acetone
Philippines (RA6969): Acetone

Section 16. Other Information

Label requirements : DANGER!
EXTREMELY FLAMMABLE LIQUID AND VAPOR.
HARMFUL IF INHALED OR SWALLOWED.
CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION.
CAUSES DAMAGE TO THE FOLLOWING ORGANS: RESPIRATORY TRACT, SKIN,
CENTRAL NERVOUS SYSTEM, EYE, LENS OR CORNEA.
VAPOR MAY CAUSE FLASH FIRE.

National Fire Protection Association (U.S.A.) :



Notice to reader

The statements contained herein are based upon technical data that EMD Chemicals Inc. believes to be reliable, are offered for information purposes only and as a guide to the appropriate precautionary and emergency handling of the material by a properly trained person having the necessary technical skills. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use, storage and disposal of these materials and the safety and health of employees and customers and the protection of the environment. EMD CHEMICALS INC. MAKES NO REPRESENTATION OR WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE, WITH RESPECT TO THE INFORMATION HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS.