

## PURA 30 Water Bath

### High quality. Practical. Durable.

PURA water baths stand for a straightforward and safe working in the laboratory. The high-quality water baths offer a temperature stability of  $\pm 0.15\text{ °C}$  <sup>2)</sup>. The working temperature range of  $+18\text{ °C}$  to  $99.9\text{ °C}$  <sup>1)</sup> allows a wide range of applications, such as routine laboratory work, temperature applications for samples, incubation, material testing, corrosion testing, temperature control applications of cultures as well as temperature tests of food and beverages and in the dental field.

<sup>1)</sup> with counter-cooling/bath cover (accessories)

<sup>2)</sup> with bath cover (accessories)



Made in Germany

All models (except PURA 4) come with an integrated drain screw for quick and clean draining of the baths. PURA water baths can be used flexibly and can be easily transported through ergonomic side recessed grips. Non-slip rubber feet ensure a firm footing and more safety in the laboratory.

The units are splash-proof, feature a (membrane) keypad and temperature display (LED) for ease of use. There are no disturbing parts inside the bath so that the entire inner surface can be used to safely temperature-control even small sample containers.

### Your advantages

- Ease of use
- Bright display
- Splash-proof protected mains switch
- Built-in dry running protection
- No disturbing elements in the bath
- Platform included as standard
- Integrated timer
- Non-slip rubber feet
- Ergonomic recessed grips
- Integrated drain screw

### Technical Data

Order No.	9550530
Model series	PURA
Category	Water Baths
Working temperature range (°C)	+18 ... +99.9
Temperature stability (°C)	$\pm 0.15$
Setting / display resolution	0.1 °C
Temperature Display	LED
Heating capacity (kW)	1.3
Bath opening / bath depth (W x L / D inch)	30.3 x 10.6 x 7.1
Filling volume liters	4.8 ... 36
Ambient temperature	5...40 °C

Dimensions W x L x H (inch)	33.9 x 13.8 x 26
Weight (LBS)	32
IP Code	IP21
Bath cover	optional
Possible number of test tube racks (accessory)	7
Alarm signal	acoustically & optical
Available voltage versions	230 V / 50-60 Hz 100 - 115 V / 60 Hz

## Characteristics



### Less is more.

Thanks to their design, PURA water baths require a minimum amount of water so that even small sample containers stand safely.



### Ease of use.

The controls on the front side are easy to reach and use.



### Lightweight.

PURA water baths impress with their low weight and can be flexibly used.



### Easy handling.

A frontally integrated drain screw allows clean, safe, and effortless emptying of the baths.



### Start. Stopp. Timer.

PURA water baths offer an internal timer function. After expiration of the set time, a signal sounds and the device either continues operation or switches off.



### Brilliant.

Very bright display makes it easy to read even from a distance.



### Tilting – no, thank you.

The PURA water bath design is tiltproof. Non-slip rubber feet prevent slipping and carrying handles simplify the transport.



### Easy cleaning.

PURA does not incorporate any interfering functional elements. The smooth surfaces can be cleaned quickly and without residue.