20 Cu. Ft. capacity One solid swing door, right hinged, not reversible Microprocessor Temperature Controller Adjustable operating temperature range: 1°-10°C Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms Sample simulated digital temperature display; .1° Resolution Adjustable temperature display in Celsius or Fahrenheit Audible and visual high/low temperature alarms Sensor error alarm Power failure alarm Resettable 1-point Min/Max History Remote alarm contacts Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back 5 adjustable shelves Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Leveling legs One probe access port (3/8") White textured cabinet and door High density urethane foam cabinet and door insulation Natural, Hydrocarbon Refrigerant (R600a) Two year parts and labor warranty Utilizes ATEX and non-sparking components for safety Exterior dimensions: 30 3/4" W x 29" D x 74 5/8"H Cycle defrost 115V, 60 Hz, 3 Amps, 1/4 HP	Product Name:	VWR-HC-FRP-20 76579-152
VWR Standard Series Natural Refrigerant Flammable Storage Refrigerator 20 Cu. Ft. capacity One solid swing door, right hinged, not reversible Microprocessor Temperature Controller Adjustable operating temperature range: 1°-10°C Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms Sample simulated digital temperature display; .1° Resolution Adjustable temperature display in Celsius or Fahrenheit Audible and visual high/low temperature alarms Sensor error alarm Power failure alarm Resettable 1-point Min/Max History Remote alarm contacts Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back 5 adjustable shelves Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Leveling legs One probe access port (3/8") White textured cabinet and door High density urethane foam cabinet and door insulation Natural, Hydrocarbon Refrigerant (R600a) Two year parts and labor warranty Utilizes ATEX and non-sparking components for safety Exterior dimensions: 30 3/4" W x 29" D x 74 5/8"H Cycle defrost 115V, 60 Hz, 3 Amps, 1/4 HP		
ETL listed Units meet NFPA guidelines 45 and 70 Shipping weight: 260 lbs.	Description:	VWR Standard Series Natural Refrigerant Flammable Storage Refrigerator 20 Cu. Ft. capacity One solid swing door, right hinged, not reversible Microprocessor Temperature Controller Adjustable operating temperature range: 1°-10°C Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms Sample simulated digital temperature display; .1° Resolution Adjustable temperature display in Celsius or Fahrenheit Audible and visual high/low temperature alarms Sensor error alarm Power failure alarm Resettable 1-point Min/Max History Remote alarm contacts Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back 5 adjustable shelves Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Leveling legs One probe access port (3/8") White textured cabinet and door High density urethane foam cabinet and door insulation Natural, Hydrocarbon Refrigerant (R600a) Two year parts and labor warranty Utilizes ATEX and non-sparking components for safety Exterior dimensions: 30 3/4" W x 29" D x 74 5/8"H Cycle defrost 115V, 60 Hz, 3 Amps, 1/4 HP ETL listed Units meet NFPA guidelines 45 and 70