accuc@ld

ARG1PV456



21.5" x 17.5" x 19.75" (H x W x D)

Performance series Pharma-Vac 1 cu.ft. glass door allrefrigerator certified to NSF/ANSI 456 Vaccine Storage Standard

Highlights:

Certified to NSF/ANSI 456 Vaccine Storage Standard

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

Product Features:

Certified to NSF/ANSI 456 Vaccine Storage Standard	Designed and tested to comply with the new NSF Vaccine Storage Standard	
Purpose-built design	Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC guidelines	
+/-1°C Variation	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period	
Certificate of calibration included	2-year calibration certificate included for your records	
Antimicrobial silver ion-coated handle	Powder-coated handle with naturally occurring silver ions to help reduce germ spread	
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +2 to +8°C	
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range	
Remote alarm contacts	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)	
Automatic defrost with adjustable cycle defrost	Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup	

accuc@ld

ARG1PV456 Specifications:

Overview		
Height of Cabinet	21.5" (55 cm)	
Width	17.5" (44 cm)	
Width with Door Open	18.0" (46 cm)	
Depth	19.75" (50 cm)	
Depth with Handle	21.5" (55 cm)	
Depth with door at 90°	36.0" (91 cm)	
Capacity	1.0 cu.ft. (28 L)	
Defrost Type	Automatic	
Door	Glass	
Cabinet	White	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Sanitation	ETL-S to NSF 456	
Amps	0.6	
Voltage/Frequency	115 V AC/60 Hz	
Weight	63.0 lbs. (29 kg)	
Shipping Weight	108.0 lbs. (49 kg)	
Parts & Labor Warranty	2 Years	
Compressor Warranty	5 Years	
UPC	761101090603	
Refrigerator Features		
Door Swing	RHD	
Reversible	Yes	
Shelf Type	Wire	
Shelf Qty	3	
Adjustable Shelves	Yes	
Thermostat Type	Digital	
Fan Type	Interior	
Refrigerant Type	R600a	
Refrigerant Amount	0.71oz.	
Interior Light	Yes	
Temperature Range	2 to 8°C	
Dimensions		
Interior Height	15.75" (40 cm)	
Interior Width	14.0" (36 cm)	
Interior Depth	8.0" (20 cm)	



