

SAFETY DATA SHEET



Acetone

BDH1101

Version 1.5

Revision Date 03/19/2015

Print Date 05/08/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Acetone

MSDS Number : 000000011657

Product Use Description : Solvent

Manufactured for : VWR International LLC
Radnor Corporate Center
Building One
Suite 200
100 Matsonford Road
Radnor PA 19087

For more information call : (Monday-Friday, 8:00am-5:00pm)
1-800-932-5000

In case of emergency call : (24 hours/day, 7 days/week)
1-800-424-9300 (USA Only)
For Transportation Emergencies:
1-800-424-9300 (CHEMTREC - Domestic)
1-613-996-6666 (CANUTEC - Canada)

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Form : liquid, clear

Color : colourless

Odor : sweet mint-like

Acetone**BDH1101**

Version 1.5

Revision Date 03/19/2015

Print Date 05/08/2015

GHS Label elements, including precautionary statements

Symbol(s)



Signal word

: Danger

Hazard statements

: Highly flammable liquid and vapour.
Causes eye irritation.
May cause respiratory irritation.
May cause drowsiness and dizziness.

Precautionary statements

: **Prevention:**
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting/ equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ eye protection/ face protection.**Response:**IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Call a POISON CENTER or doctor/ physician if you feel unwell.
If eye irritation persists: Get medical advice/ attention.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.**Storage:**

SAFETY DATA SHEET



Acetone

BDH1101

Version 1.5

Revision Date 03/19/2015

Print Date 05/08/2015

Store in a well-ventilated place. Keep container tightly closed.
Keep cool.
Store locked up.

Disposal:

Dispose of contents/container in accordance with local, state & federal regulations.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula : C₃H₆O

Chemical nature : Substance

Chemical Name	CAS-No.	Concentration
Acetone	67-64-1	100.00 %

SECTION 4. FIRST AID MEASURES

Inhalation : Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is present. Call a physician.

Skin contact : Wash off immediately with plenty of water for at least 15 minutes. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use. Call a physician if irritation develops or persists.

Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician.

SAFETY DATA SHEET



Acetone

BDH1101

Version 1.5

Revision Date 03/19/2015

Print Date 05/08/2015

Ingestion : Do not induce vomiting without medical advice. If a person vomits when lying on his back, place him in the recovery position. Never give anything by mouth to an unconscious person. Call a physician.

Notes to physician

Treatment : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Dry chemical
Foam
Carbon dioxide (CO₂)
Cool closed containers exposed to fire with water spray.

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

Specific hazards during firefighting : Extremely flammable.
Vapours may form explosive mixtures with air.
Vapours are heavier than air and may spread along floors.
Vapors may travel to areas away from work site before igniting/flashing back to vapor source.
In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide
Carbon dioxide (CO₂)

Special protective equipment for firefighters : Wear self-contained breathing apparatus and protective suit.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear personal protective equipment. Unprotected persons must be kept away.
Immediately evacuate personnel to safe areas.

**Acetone****BDH1101**

Version 1.5

Revision Date 03/19/2015

Print Date 05/08/2015

Keep people away from and upwind of spill/leak.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not swallow.
Avoid breathing vapours, mist or gas.
Avoid contact with skin, eyes and clothing.

Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Discharge into the environment must be avoided.
Do not flush into surface water or sanitary sewer system.
Do not allow run-off from fire fighting to enter drains or water courses.

Methods for cleaning up : Ventilate the area.
No sparking tools should be used.
Use explosion-proof equipment.
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE**Handling**

Handling : Wear personal protective equipment.
Use only in well-ventilated areas.
Keep container tightly closed.
Do not smoke.
Do not swallow.
Avoid breathing vapours, mist or gas.
Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion : Keep away from fire, sparks and heated surfaces.
Take precautionary measures against static discharges.
Ensure all equipment is electrically grounded before beginning transfer operations.
Use explosion-proof equipment.
Keep product and empty container away from heat and sources of ignition.

**Acetone****BDH1101**

Version 1.5

Revision Date 03/19/2015

Print Date 05/08/2015

No sparking tools should be used.
No smoking.

Storage

Requirements for storage areas and containers : Store in area designed for storage of flammable liquids. Protect from physical damage.
Keep containers tightly closed in a dry, cool and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Keep away from heat and sources of ignition.
Keep away from direct sunlight.
Store away from incompatible substances.
Container hazardous when empty.
Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Ensure that eyewash stations and safety showers are close to the workstation location.

Engineering measures : Use with local exhaust ventilation.
Prevent vapour buildup by providing adequate ventilation during and after use.

Eye protection : Do not wear contact lenses.
Wear as appropriate:
Safety glasses with side-shields
If splashes are likely to occur, wear:
Goggles or face shield, giving complete protection to eyes

Hand protection : Solvent-resistant gloves
Gloves must be inspected prior to use.
Replace when worn.

Skin and body protection : Wear as appropriate:
Solvent-resistant apron

**Acetone****BDH1101**

Version 1.5

Revision Date 03/19/2015

Print Date 05/08/2015

Flame retardant antistatic protective clothing.
If splashes are likely to occur, wear:
Protective suit

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
For rescue and maintenance work in storage tanks use self-contained breathing apparatus.
Use NIOSH approved respiratory protection.

Hygiene measures : When using, do not eat, drink or smoke.
Wash hands and face before breaks and immediately after handling the product.
Keep working clothes separately.
Remove and wash contaminated clothing before re-use.
Do not swallow.
Avoid breathing vapours, mist or gas.
Avoid contact with skin, eyes and clothing.

Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Update	Basis
Acetone	67-64-1	TWA : time weighted average	(500 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values
Acetone	67-64-1	STEL : Short term exposure limit	(750 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values
Acetone	67-64-1	TWA : time weighted average	(250 ppm)	02 2014	ACGIHLIS_P:US. ACGIH Notice of Intended Changes (NIC) to Threshold Limit Values

SAFETY DATA SHEET

**Acetone****BDH1101**

Version 1.5

Revision Date 03/19/2015

Print Date 05/08/2015

Acetone	67-64-1	STEL : Short term exposure limit	(500 ppm)	12 2010	ACGIHLIS_P:US. ACGIH Notice of Intended Changes (NIC) to Threshold Limit Values
Acetone	67-64-1	REL : Recomm ended exposure limit (REL):	590 mg/m3 (250 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards
Acetone	67-64-1	PEL : Permissi ble exposure limit	2,400 mg/m3 (1,000 ppm)	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
Acetone	67-64-1	TWA : time weighted average	1,800 mg/m3 (750 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)
Acetone	67-64-1	STEL : Short term exposure limit	2,400 mg/m3 (1,000 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid, clear
 Color : colourless
 Odor : sweet mint-like

**Acetone****BDH1101**

Version 1.5

Revision Date 03/19/2015

Print Date 05/08/2015

pH	:	Note: Not applicable
Melting point/freezing point	:	-94.8 °C
Boiling point/boiling range	:	56 °C
Flash point	:	-4 °F (-20 °C) Method: closed cup
Evaporation rate	:	12 Method: Compared to Butyl acetate.
Lower explosion limit	:	2 %(V)
Upper explosion limit	:	13 %(V)
Vapor pressure	:	240 hPa at 20 °C(68 °F)
Vapor density	:	2.0 Note: (Air = 1.0)
Density	:	0.79 g/cm ³ at 20 °C
Water solubility	:	Note: completely soluble
Solubility in other solvents	:	Note: no data available
Partition coefficient: n-octanol/water	:	Pow: 0.58 log Pow: -0.24

SAFETY DATA SHEET



Acetone

BDH1101

Version 1.5

Revision Date 03/19/2015

Print Date 05/08/2015

Ignition temperature	: 465 °C
Viscosity, dynamic	: Note: no data available
Viscosity, kinematic	: Note: no data available
Molecular weight	: 58.05 g/mol

SECTION 10. STABILITY AND REACTIVITY

Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Hazardous polymerisation does not occur.
Conditions to avoid	: Heat, flames and sparks. Keep away from direct sunlight.
Incompatible materials to avoid	: Acids Aldehydes Alkalis Amines Ammonia Oxidizing agents Reducing agents Chlorine compounds
Hazardous decomposition products	: In case of fire hazardous decomposition products may be produced such as: Carbon monoxide Carbon dioxide (CO ₂)

SECTION 11. TOXICOLOGICAL INFORMATION

**Acetone****BDH1101**

Version 1.5

Revision Date 03/19/2015

Print Date 05/08/2015

Acute oral toxicity	: LD50: 5,800 mg/kg Species: Rat
Acute inhalation toxicity	: LC50: 32000 ppm Exposure time: 4 h Species: Rat
Acute dermal toxicity	: LD50: > 7,426 mg/kg Species: Guinea pig
Skin irritation	: Species: Rabbit Result: Mild skin irritation Exposure time: 24 h
Eye irritation	: Species: Rabbit Result: Irritation to eyes, reversing within 7 days
Repeated dose toxicity	: Species: Rat NOEL: 19000 ppm Note: 8-Week Inhalation Toxicity Study 5 days/week for 8 weeks Slightly reduced weight gain compared to controls
	: Species: Rat NOEL: 100 mg/kg/d Note: 90-Day Oral Toxicity Study increased liver and kidney weights
	: Species: Rat Lowest observed effect level: 500 mg/kg/d Note: 90-Day Oral Toxicity Study increased liver and kidney weights

**Acetone****BDH1101**

Version 1.5

Revision Date 03/19/2015

Print Date 05/08/2015

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity effects**

- Toxicity to fish : LC50: 5,540 mg/l
Exposure time: 96 h
Species: Oncorhynchus mykiss (rainbow trout)
- : LC50: 8,300 mg/l
Exposure time: 96 h
Species: Lepomis macrochirus (Bluegill sunfish)
- Toxicity to daphnia and other aquatic invertebrates : LC50: 10 mg/l
Exposure time: 24 h
Species: Daphnia magna (Water flea)
- Toxicity to algae : EC50: 3,020 mg/l
Exposure time: 14 d
Species: Chlorella pyrenoidosa (algae)
- Toxicity to bacteria : LC50: > 1,000 mg/l
Species: Bacteria

Elimination information (persistence and degradability)

- Biodegradability : anaerobic
Result: Readily biodegradable
Value: 78 %
Method: OECD 301 D

Further information on ecology

SAFETY DATA SHEET



Acetone

BDH1101

Version 1.5

Revision Date 03/19/2015

Print Date 05/08/2015

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Dispose of contents/ container in accordance with local, state, and federal regulations.

SECTION 14. TRANSPORT INFORMATION

DOT UN/ID No. : UN 1090
Proper shipping name : ACETONE
Class : 3
Packing group : II
Hazard Labels : 3

IATA UN/ID No. : UN 1090
Description of the goods : ACETONE
Class : 3
Packaging group : II
Hazard Labels : 3
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353
Packing instruction (passenger aircraft) : Y341

IMDG UN/ID No. : UN 1090
Description of the goods : ACETONE
Class : 3
Packaging group : II
Hazard Labels : 3
EmS Number : F-E, S-D
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

**Acetone****BDH1101**

Version 1.5

Revision Date 03/19/2015

Print Date 05/08/2015

Inventories

- US. Toxic Substances Control Act : On TSCA Inventory
- Australia. Industrial Chemical (Notification and Assessment) Act : On the inventory, or in compliance with the inventory
- Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL) : All components of this product are on the Canadian DSL.
- Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory
- Korea. Toxic Chemical Control Law (TCCL) List : On the inventory, or in compliance with the inventory
- Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act : On the inventory, or in compliance with the inventory
- China. Inventory of Existing Chemical Substances : On the inventory, or in compliance with the inventory
- New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand : On the inventory, or in compliance with the inventory

National regulatory information

- US. Drug Enforcement Administration (DEA) Listed Precursor and Essential Chemicals (21 CFR 1310) : On the United States Drug Enforcement Authority (DEA) List of Precursors and Essential Chemicals
- : Acetone 67-64-1

SAFETY DATA SHEET



Acetone

BDH1101

Version 1.5

Revision Date 03/19/2015

Print Date 05/08/2015

- SARA 302 Components** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
- SARA 313 Components** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
- SARA 311/312 Hazards** : Fire Hazard
Acute Health Hazard
Chronic Health Hazard
- CERCLA Reportable Quantity** : 5000 lbs
- California Prop. 65** : This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Massachusetts RTK : Acetone 67-64-1

New Jersey RTK : Acetone 67-64-1

Pennsylvania RTK : Acetone 67-64-1

WHMIS Classification : B2: Flammable liquid
D2B: Toxic Material Causing Other Toxic Effects
This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

SECTION 16. OTHER INFORMATION

Health hazard : **HMIS III** 2* **NFPA** 1

**Acetone****BDH1101**

Version 1.5

Revision Date 03/19/2015

Print Date 05/08/2015

Flammability	:	3	3
Physical Hazard	:	0	
Instability	:		0

* - Chronic health hazard

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 06/20/2012

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group