accucold

ARG15ML



72" x 23.38" x 24.38" (H x W x D)

Performance series Med-Lab 15 cu.ft. upright glass door all-refrigerator

Highlights:

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

Additional sensor reads interior air temperature for superior temperature control

| Designed and purpose-built to meet the demanding needs of scientific, life science, laboratory, and medical cold storage applications |
|--|
| The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period |
| Intuitive controls let you adjust the interior temperature between +2 to +10°C |
| Visual and audible alarms alert if the interior temperature rises or falls out of set range |
| Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit) |
| Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup |
| Includes a pre-installed 1/2" probe hole in the right interior wall to allow easier connection to user-provided monitoring equipment |
| Alarm will sound if the door is left ajar for over 4 minutes (adjustable from 1-99 minutes) |
| Battery-powered alarm sounds if the power connection is interrupted |
| |

ACCUCOLD DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799




accucold

ARG15ML Specifications:

| Overview | |
|-------------------------------|---------------------------------|
| Height of Cabinet | 72.0" (183 cm) |
| Width | 23.38" (59 cm) |
| Width with Door Open | 23.88" (61 cm) |
| Depth | 24.38" (62 cm) |
| Depth with Handle | 26.13" (66 cm) |
| Depth with door at 90° | 46.5" (118 cm) |
| Capacity | 15.0 cu.ft. (425 L) |
| Defrost Type | Automatic |
| Door | Glass |
| Cabinet | White |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Amps | 1.4 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 204.2 lbs. (93 kg) |
| Shipping Weight | 224.9 lbs. (102 kg) |
| Estimated Time to Ship | Out of stock; ETA 12/10/2019 |
| Parts & Labor Warranty | 2 Years |
| Compressor Warranty | 5 Years |
| Refrigerator Features | |
| Door Swing | RHD |
| Reversible | Yes |
| Shelf Type | Wire |
| Shelf Qty | 7 |
| Adjustable Shelves | Yes |
| Thermostat Type | Digital |
| Fan Type | Interior |
| Refrigerant Type | R600a |
| Refrigerant Amount | 2.65oz. |
| Interior Light | Yes |
| Temperature Range | 2 to 10ºC |
| Dimensions | |
| Interior Height | 63.25" (161 cm) |
| Interior Width | 20.0" (51 cm) |
| | - |

| | + |
|---------------------------|-------|
| | |
| Interior Depth | 17.0" |
| Compressor Step Height | 6.5" |
| Compressor Step Width | 20.0" |
| Compressor Step Depth | 5.0" |
| | |



12.2.3



accucold

