

Specifications for the ENCORE 4520 General Low-Access Table

Warranty:	4-YEAR
Operation:	Power, non-programmable
Patient Load:	700 lbs. evenly distributed on main couch
Power Adjustments:	Height: Low Access: 18.5" ± .25" to maximum 38" ± .25" Back: Horizontal to 80° ± 2°
Controls:	"Easy Touch" hands free, Foot Control, SELV
Couch Top:	100% seamless vacuum formed style, all steel frame construction
Perineal Recess:	Moulded, no seams, 10" W x 2" D at center point
Pelvic Tilt:	11° ± 2°
Leg Extension:	Extends out 20" from end of seat section
Irrigation Basin:	Stainless steel , 2.5" deep
Master ON/OFF Switch:	Shuts off power to entire product
Stirrups:	Multi-positional, lateral, and length adjustment
Storage:	Side Drawer: Field reversible, 15.5" W x 15" D x 4" H Footend Drawer: Stainless Steel, 16" W x 10.75" D x 4" H
Base Construction:	Fully welded all steel base
Paper Roll Holder:	Accommodates 18" or 21" table paper widths
Accessories:	Grab rails, knee crutches, padded armboard, drawer lock, restraint straps, IV pole, urology basin with screen and drain, headend accessory rails, foot end rails
Power System:	Electro-mechanical operating system
Mains Power Entry:	IEC connection with internal circuit breaker, detachable cord
Table Duty Cycle:	1 minute run / 9 minutes rest
Table Rating:	115V 60Hz 10 amps
Table Dimensions:	Width: 27", Height: 18.5" - 38", Length: 52" (extends to 72")
Certifications:	Classified by UL to ANSI/AAMI ES60601-1 (2005) + AMD 1 (2012), CAN/CSA-C22.2 No. 60601-1 (2014)

ADD-ON OPTIONS

	Electrical Receptacles	Instrument Warmer	Hand Control
-01	•	•	
-02	•		
-03		•	
-04	•	•	•
-05		•	•
-06	•		•
-07			•
	Hospital grade, dual receptacles with easy access dedicated circuit breaker Duty Cycle: Continuous operation Total Load: 3.9 amps Rating: 115V 60Hz	45 Watts, ON/OFF switch with integrated circuit breaker, heats to approximate body temperature Duty Cycle: Continuous operation	"Easy Read", non-programmable, SELV